

4


3

2

1

CONVERSION CHART

INCH	MM
.002	0.05
.010	0.25
.020	0.51
.035	0.88
.051	1.30
.115	2.92
.185	4.70
.200	5.08
.406	10.31



RECOMMENDED HOLE LAYOUT  
TOLERANCE: ±.002  
UNLESS OTHERWISE NOTED

SPECIFICATIONS:

MATERIALS:  
INSULATOR: POLYAMIDE (COLOR: RED)  
SLEEVE: COPPER ALLOY, GOLD OVER NICKEL PLATE.  
CONTACT: COPPER ALLOY, GOLD OVER NICKEL PLATE.

ELECTRICAL:  
CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
CONTACT RATING: 3 AMPS.  
DIELECTRIC WITHSTANDING VOLTAGE: 600 VOLTS.

MECHANICAL:  
OPERATIONAL TEMPERATURE: -67°F TO +257°F  
(-55°C TO +125°C)  
WITHDRAWAL FORCE: 14.1g MIN.

NOTES:

- INTERPRET DRAWING PER ASME Y14.5M-1994.
- ASSEMBLY WILL ACCEPT Ø.016/.020 LEADS.

**OUTLINE DRAWING**  
SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT NOTICE

THIS IS A C.A.D. GENERATED DRAWING.  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



REV	0	1
REVISIONS	INITIAL RELEASE ESR # AG572 K.W. 6/9/95 APP'D: RJS 8/24/95	REVISED ECO# 23-97 L.S. 2-20-97 APP'D: RJS 2/20/97

THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DO NOT SCALE PRINT		ORIGINAL DATE OF DRAWING: 8/9/95	<b>AUGAT</b> INC. 452 JOHN DIETSCH BLVD. ATTLEBORO FALLS, MASS. 02763
TOLERANCES (EXCEPT AS NOTED) ANGULAR = ±1° DECIMAL .XX = ±.005 DECIMAL .XXX = ±.010 DECIMAL .XXXX = ±.015		FILE NAME: 80592G1L	DIRECTORY: ASSY/8000ASSY	DRAWN: K. WIKSTROM	
AUGAT CONFIDENTIAL This document contains information which is the exclusive property of Augat Inc. Distribution, reproduction or use by others is not permitted without the expressed written consent of Augat Inc.		SEE SPECIFICATIONS		CHECKED:	DATE:
FINISH: SEE SPECIFICATIONS		SEE SPECIFICATIONS		APPROVED: R.J.S.	DATE: 8/24/95
		NEXT ASSY:		CODE IDENT. NO. 91506	DWG. SIZE B
				TITLE: <b>OUTLINE DRAWING</b> SOCKET 3 PIN PRINTED CIRCUIT	
				DWG. NO. 8059-261	
				PRODUCT CODE: 022	
				REV. 1	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [IC & Component Sockets](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[0066-3-17-15-30-14-02-0](#) [670](#) [672](#) [673](#) [694-13-640-00-672-000](#) [712-93-120-41-001000](#) [714-93-104-31-018000](#) [8059-4G1-LF](#) [807-22-001-10-001101](#) [807-22-001-10-006101](#) [807-22-001-30-011101](#) [807-22-001-30-012101](#) [807-22-001-30-013101](#) [807-22-001-30-014101](#) [8-1437531-4](#) [8150-6P10](#) [833-93-034-10-001000](#) [851-41-006-10-001000](#) [851-43-008-20-001000](#) [851-43-014-20-001000](#) [851-93-006-20-001000](#) [851-93-010-20-001000](#) [853-43-020-10-001000](#) [86.010.0053.0](#) [116-43-308-41-007000](#) [PX-68LCC](#) [121-13-318-41-001000](#) [121-13-320-41-001000](#) [121-13-308-41-001000](#) [123-43-314-41-801000](#) [123-43-420-41-001000](#) [123-87-320-41-001101](#) [122-13-316-41-001000](#) [123-13-624-41-001000](#) [123-43-306-41-001000](#) [12-3513-11](#) [123-91-320-41-001000](#) [126-43-310-41-002000](#) [AKSUN 37V-T](#) [1437503-9](#) [1437504-1](#) [146-44-308-41-013000](#) [APO-320-G-T](#) [146-43-308-41-012000](#) [160-10-308-00-001000](#) [160-40-320-00-001000](#) [214-99-306-01-670800](#) [232-1270-02-0602](#) [2-382761-4](#) [2-5331677-4](#)