

DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS). THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO. 1583008

TOOL NUMBER	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	INSUL. ADJ.	FLIP LOCATOR	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS ¹		CONTACT DESCRIPTION	APPLIC. SPECIF.	
							LOOSE PIECE	STRIP FORM			
91584-1 91584-3	0.50-1.25 [20-16]	2.10-3.00 [.083-.118]	NO	NO	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[] 170289-[]	170177-[] 170286-[]	MIC Contacts	114-5004 114-5018	
	0.75-1.42 [18-16]	2.16-2.85 [.085-.112]					170222-[]	170221-[]	187 Series FASTON Receptacle	114-5068	
	2.00-2.30 [14]	2.60-3.40 [.102-.134]					170467-[]	170466-[]	MIC Contacts	114-5004 114-5018	
91586-1 91586-3	0.50-0.85 [20-18]	2.1-3.0 [.082-.118]	YES	NO	3.5-4.5 [.138-.177]	1.25-1.35 [.049-.053]	172778-[]	172777-[]	MIC MK II Tab Contacts	114-5072	
	0.50x2 [20x2]										2.60-3.43 [.102-.135]
	1.25-2.27 [16-14]										
91587-1 91587-3	0.30-0.56 [22-20]	1.50-2.20 [.059-.087]	NO	NO	4.0-5.0 [.157-.197]	1.06-1.19 [.042-.047]	170458-[]	170307-[]	MIC Contacts	114-5004 114-5018	
	0.75-0.89 [18]	2.20-2.60 [.087-.102]					170459-[]	170308-[]	MIC MK II Tab Contacts	114-5072	
91589-1 91589-3	0.50-1.25 [20-18]	2.1-3.0 [.083-.118]	NO	NO	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[]	170177-[]	MIC Contacts	114-5004 114-5018	
	1.25-2.30 [16-14]	2.6-3.4 [.102-.134]					170222-[]	170221-[]			
91592-1 91592-3	0.30-0.35 [22]	1.5-2.0 [.060-.079]	NO	NO	3.5-5.5 [.138-.216]	1.05-1.28 [.041-.050]	172776-[]	172775-[]	MIC MK II Receptacle Contacts	114-5071	
	0.50-0.89 [20-18]	2.0-2.6 [.079-.102]									1.20-1.37 [.047-.054]
1804014-1	0.50-0.85 [20-18]	2.10-3.00 [.083-.118]	YES	NO	3.5-5.5 [.138-.216]	1.25-1.45 [.049-.057]	172774-[]	172773-[]	MIC MK II Receptacle Contacts	114-5071	
	0.50x2 [20x2]										
	1.25-2.00 [16-14]	2.60-3.40 [.102-.134]									
	0.50+0.85 [20+18]										

¹ LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.

³ -1 IS A COMPLETE CERTICRIMP II TOOL ASSEMBLY. -3 IS A CERTICRIMP II HEAD SUB ASSEMBLY.

4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

2. AMP, CERTI-CRIMP, FASTON and MIC are trademarks.

CERTI-CRIMP II DATA SHEET

DWG: M. YOUNGER 21FEB2012		MATERIAL: -		HEAT TREAT: -	
CHK: B.A. WOLFE 22FEB2012		APVD: B.A. WOLFE 22FEB2012		NAME: B.A. WOLFE	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± -	
ANGLE: 45° SURFACE TEXTURE:		SCALE: -		SIZE: A1	
P LTR REVISION RECORD A3 REVISED - NEW FORMAT 2-2012 MY BAW		DATE: 2-2012 DWG: MY APVD: BAW		CERTI-CRIMP II TOOL DATA SHEET MULTI-INTERLOCK (MIC) CONNECTORS DRAWING NO: 1583008 SHEET 1 OF 1 REV A3	

LOC A
DIST 00

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crimpers / Crimping Tools](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[010-0096](#) [M225201-06](#) [M225202-37](#) [6-1579015-5](#) [CT150-2-D02](#) [622-6441LF](#) [M322](#) [6-304052-1](#) [63456-0054](#) [63484-3701](#) [63800-8355](#)
[63819-1875](#) [63819-2875](#) [63819-4475](#) [63823-3475](#) [63827-5375](#) [64001-0975](#) [64001-4175](#) [64005-0175](#) [662903-2](#) [690602-6](#) [7-1579001-9](#) [7-](#)
[23471-1](#) [762637-1](#) [808714-1](#) [811242-5](#) [999-50-020083](#) [1-21002-3](#) [1-21002-7](#) [12085270](#) [1-21002-6](#) [1-21113-6](#) [1-22548-4](#) [125442-1](#)
[DCE.91.073.BVC](#) [DCE.91.090.3MVM](#) [DCE.91.130.5MVU](#) [DCE.91.202.BVCM](#) [1338300-1](#) [1-354003-0](#) [1338301-1](#) [DF62/RE-MD](#) [142321](#)
[1456088-1](#) [1490794-1](#) [1-45804-6](#) [1490357-2](#) [1490357-3](#) [AX100749](#) [1-59619-7](#)