

Type CB10 Series

Key Features

- Low Cost
- Robust Enclosed Construction
- Spindle Adjust Versions
- Flame Retardant
- Arrow Position Indicator
- Top, Bottom and Side Adjust Styles
- Stable in High Humidity
- Edgewise Operation Style



Low price, versatility and stable environmental characteristics are important benefits of this product. Featuring an innovative carbon resistive element mounted on film in a fully enclosed package, this potentiometer style is normally chosen for a wide range of applications in industrial, professional and consumer equipment.

Characteristics - Electrical

| | |
|--------------------------|---|
| Resistance Range: | 100R to 10M Linear, 1K to 1M Non-Linear |
| Resistance Values: | 1, 2.2 & 4.7 in each decade |
| Resistance Tolerance: | ± 20% (± 30% above 1 Megohms) |
| End Resistance: | < 3% |
| Power Rating @ 40°C: | 0.15 Watts (derating to zero at 70°C) |
| Maximum Voltage: | Lin. 200V DC / Log. 150V DC |
| Rotational Noise (dRV): | < 5% of Rn nominal |
| Temperature Coefficient: | ±500 ppm/°C (< 100K ohms) |
| Slider Current: | 50mA |
| Resolution: | Essentially Infinite |
| Electrical Adjustment: | 240° Nominal 1 Turn |

Characteristics - Mechanical

| | |
|------------------------|----------------|
| End Torque: | 50 mNm maximum |
| Starting Torque: | 4 to 20 mNm |
| Mechanical Adjustment: | 295° nominal |
| Weight: | 0.8 grams |

Characteristics - Environmental

| | |
|----------------------|--|
| Temperature Range: | -25°C to +70°C |
| Temperature Storage: | 1000 hours at 100°C |
| Rotational Life: | 500 cycles, minimum (10000 cycles-extended life versions) |
| Load Life at 40°C: | ΔR < 10% after 1000 hours |
| Sealing: | Dust proof IP level 5 |
| Climate Category: | 25/70/21 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Trimmer Resistors - Through Hole](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[64W205](#) [M63M103KB40](#) [M63X104KB40](#) [76PR500K](#) [79PR5K](#) [PT15NV24-103A2020](#) [CT6P-103](#) [CB10MV473ME](#) [4270W105K](#)
[56PR2MEG](#) [82PR2KLFTB](#) [62MR100](#) [72XWR20K](#) [9702-2SL-1](#) [89PHR10K](#) [78SR5K](#) [CT15NV15103M](#) [78SBWR1K](#) [343P10](#) [PT15NH02-104A2020-S](#) [VG039NSNXTB103](#) [PTC15NH05-103A2020](#) [PTC15NV02-104A2020](#) [PTC15LV02-103A2020](#) [PT15GV02-27402](#) [RJ-13SR203](#)
[RJ-5EW202](#) [3292W-1-201M](#) [3362F-1-205LF](#) [3362X-1-272LF](#) [3386H-EY5-202LF](#) [3059Y-1-200LF](#) [3386X-DF6-503LF](#) [3260W-1-500](#)
[3329S-1-204LF](#) [PT10MV10-203A2020-S](#) [PT15NV02-503A2020-E-S](#) [PTC10MV10-472A0505](#) [PV36W103C01B00](#) [CN-15.1-22K](#) [CN-15.1-3K3](#) [CN-15.2-10K](#) [CN-15.2-470R](#) [R0141-2-100K](#) [R0141-2-10K](#) [R0141-2-1K](#) [R0141-2-20K](#) [R0141-2-5K](#) [1028F-500K](#) [R16148-1A-1-A22K](#)