

8

4

4 (3+PE)

power

6000 V

500

III

2000 m

max. 75 A\* 630V (AC/DC)

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

-20 °C to 130 °C

when connected IP 66/67

zinc diecast / nickel plated

PA 6.6 mod., UL 94/V0 FKM

signal

4000 V

max. 30 A\* 250 V (AC/DC)

**Technical Data** 

number of pins

rated current rated voltage

mating cycles

Material

housing insulation insert

seals

temperature range protection type

**Electrical Data** 

pollution degree over voltage category

max. height for operation

rated insulation voltage (L-L)

power signal

## 940 Receptacle

## **speedtec** - ready

8-pin Earth-to-Housing Connection according to VDE 0627 flange mount /Flange 40x40 Anti-vibration o-ring

## C EG A 271 NN 00 00 0051 000 C E A 271 N 00 00 0051 000



**Contact Arrangement** mating view





Tools (not part of product contents)

© 2018 TE Connectivity


TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the unartice of merchantability or fitness for a particular purpose. The dimensions in this article are for reference nurses environd are subject to change without

in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mali: intercontec@te.com Web: www.intercontec.biz





**Main Dimensions** Receptacle

\*for max, wire cross-section pay attention to the cross-section of used contacts

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by TE CONNECTIVITY manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-005413001400261300150099RF-12S1N8A90DU1-3637-600-52051612618210368364148R4006A16M0108R5006A18A12016042321R3006A20M005RF-12P1N8A80DURF-12P1N8A90DU41-4001142-010154-22279-44-22281-14-22284-943-0011343-0108843-0120341-4001342-0000843-0034343-0103243-0116243-10000600X518050XSACC-DSI-FS-5P-PG9-L180 SC8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-01338XS2RD4265XS2R-D426-1XS8A-0441859RD04-103R0044459RD04-103R004459RD04-103R004459RD04-103R004459RD04-103R004