

Raychem

TE Internal #: 834799-000

SolderSleeve Shield Terminators, Operating Temperature (Max)

125 °C, Expanded Inside Diameter (Min) .18 in [4.57 mm]

View on TE.com >



Wire Protection & Management > Interconnect Devices > SolderSleeve Shield Terminators



Operating Temperature (Max): 125 °C

Expanded Inside Diameter (Min): 4.57 mm [.18 in]
Recovered Inside Diameter (Max): 1.78 mm [.07 in]

Pre-Installed Lead: No
Wire Size: .34 mm²

Features

Configuration Features

Pre-Installed Lead	No
Dimensions	
Expanded Inside Diameter (Min)	4.57 mm[.18 in]
Recovered Inside Diameter (Max)	1.78 mm[.07 in]
Wire Size	22 AWG
Usage Conditions	
Operating Temperature (Max)	125 °C
Wire Temperature (Max)	85 °C

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (32% in Solder) Cd (18% in Solder) Article Safe Usage Statements:



Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in
	other sources.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought

















Documents

Product Drawings

CWT-3805-W2

English

Datasheets & Catalog Pages

1654025_Sec8_B-155_CWT_D-110_D-1744

English

Raychem Electrical Interconnect Products

English

Product Specifications

SolderSleeve One-Step Wire and Cable Terminators Installation Procedures for CWT and B-155 Products

English

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solder Sleeves & Shield Tubing category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

899170-000 620040N001 620069N003 CTA-0050-01 629624-000 6500750004 6501390002 CX0781-000 696396-000 697080-000 D-150-0331CS2902 D-181-1222-90/9CS2800 D-300-01CS1108 715325N001 908357N001 982127-1 D-436-0182CS246 D-436-37CS2651 D-436-61CS246 D-436-82-CS2621 D-659-0087 E53797N001 CB0213-000 CB0219-000 S200-2-01 S200-4-00CS2904 LSS-81-16AA-CS5575 ST18-2-00 FLX40-020-04-CS8651 325534-000 CTA-0025 D-108-07CS436 D-128-0010 D-141-0108CS404 D-144-41CS1371 D-150-0231-NRCS2896 D-150-1011 395947-000 427243N001 B-801-18-01 515-9 C67137-000 CB0220-000 D-436-0185CS1102 D-436-36CS2908 D-436-37CS2908 D-436-52CS246 D-436-83CS2705 D44133N001 LSS-26-8A