


CUSTOMER DRAWING



Product Name	Component Dimensions					Shall Accommodate Cable with Dimensions		
	Ident. Code	$L \pm 1.75$ ($L \pm 0.07$)	ϕB min	ϕC min	H min	ϕE max	ϕF min	ϕD max
SO96-1-01	SO961R	16.5 (0.650)	1.90 (0.070)	2.65 (0.105)	8.25 (0.325)	2.65 (0.105)	0.90 (0.035)	1.9 (0.075)
SO96-2-01	SO962R	16.5 (0.650)	2.65 (0.105)	3.55 (0.140)	8.25 (0.325)	3.55 (0.140)	1.40 (0.055)	2.65 (0.105)
SO96-3-01	SO963R	16.5 (0.650)	4.30 (0.170)	5.00 (0.195)	8.25 (0.325)	5.00 (0.195)	2.15 (0.085)	4.30 (0.170)
SO96-4-01	SO964R	19.7 (0.775)	5.95 (0.235)	6.45 (0.255)	8.25 (0.325)	6.45 (0.255)	3.30 (0.130)	5.95 (0.235)
SO96-5-01	SO965R	19.7 (0.775)	7.00 (0.277)	7.6 (0.300)	8.25 (0.325)	7.6 (0.300)	4.30 (0.170)	7.00 (0.277)


MATERIALS

- INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
- SOLDER PREFORM WITH FLUX AND THERMAL INDICATOR:
 SOLDER: TYPE Sn96 per ANSI-J-STD-006.
 FLUX: TYPE ROM1 per ANSI-J-STD-004.
 THERMAL INDICATOR: color change orange to colorless.
- MELTABLE RINGS: Stabilized thermoplastic. Color:blue.
- PRE-INSTALLED BRAID: Nickel plated copper strands. CMA 640.


APPLICATION

- These parts are designed to provide an environment protected shield termination on cables, rated for 150°C minimum, meeting the dimensional criteria listed, having nickel plated shields.
- Temperature range: -55°C to +175°C.
 Install using TE Connectivity-approved convection or infrared heating tools in accordance with Raychem process standard RCPS-100-70.
 Infrared tools are not recommended for use with black jackets.

For best results, prepare the cable as shown:



TE Connectivity, TE connectivity (logo), Raychem, and SolderSleeve are trademarks

		RAYCHEM		TITLE: SOLDER SLEEVE DEVICE SHIELD TERMINATION WITH BRAID HIGH TEMPERATURE		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.				DOCUMENT NO.: SO96-X-01		
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	TE Connectivity reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		Revision: 4	Issue Date: April 2020	
DRAWN BY: M. FORONDA	CAGE CODE: 06090	DATE: June 29, 1998	ECO: ECO-20-004961		SCALE: None	SIZE: A
					SHEET: 1 of 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder Sleeves & Shield Tubing](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[D-260-C-A](#) [899170-000](#) [620040N001](#) [620069N003](#) [620263N004](#) [CTA-0050-01](#) [629624-000](#) [6501390002](#) [CX0781-000](#) [CX0782-000](#)
[696396-000](#) [697080-000](#) [715325N001](#) [FLX40-030-02-CS8652](#) [D-436-38CS2908](#) [CB0213-000](#) [CB0219-000](#) [274384-000](#) [285343-000](#)
[970053-000](#) [ST18-2-00](#) [FLX40-020-04-CS8651](#) [317035-000](#) [325534-000](#) [D-100-00-WOTI](#) [D-150-1011](#) [395947-000](#) [427243N001](#) [C03534-](#)
[000](#) [CB0220-000](#) [D44133N001](#) [477436-000](#) [451893-000](#) [931289-000](#) [162583-000](#) [585769N001](#) [610001N004](#) [6200060004](#) [622041N003](#)
[626167-000](#) [EG3678-000](#) [650075N002](#) [6500820003](#) [6500850004](#) [650126N010](#) [650127N005](#) [146201-000](#) [7400720001](#) [CA3200N001](#) [82-A2](#)