

Raychem

TE Internal #: 625380-000

Splices, SolderSleeve Wire Splice, Splice, .17 Splice Wire Insulation

Diameter (Max) 4.32 Splice Wire Insulation Diameter (Max)

View on TE.com >



Terminals & Splices > Splices



Splice Product Type: SolderSleeve Wire Splice

Terminal & Splice Type: Splice

Sealable: No

Splice Wire Insulation Diameter (Max): 4.32 mm [.17 in]

Wire Size: 4800 – 9000 CMA

Features

Product Type Features

Froduct Type realures	
Splice Product Type	SolderSleeve Wire Splice
Sealable	No
Splice Type	In-Line Splice
Serrated	No
Splice Barrel Type	Closed Barrel
Insulated	Yes
Body Features	
Weight per Piece	.46 g
Contact Features	
Terminal & Splice Type	Splice
Termination Features	
Termination Method	Solder
Dimensions	
Splice Wire Insulation Diameter (Max)	4.32 mm[.17 in]
Wire Size	4800 – 9000 CMA
Splice Overall Length	36.8 mm[1.45 in]

Fully Insulated

Usage Conditions

Insulation Requirement



Fluid Resistance	Splash Protection
Operation/Application	
Heavy Duty	No
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	500

Package

Product Compliance

Splice Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (37% in Solder) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought



















Documents

Product Drawings

English

D-110-0101

Datasheets & Catalog Pages

1654025_Sec8_B-155_CWT_D-110_D-1744

English

Product Specifications

Product Specification

Splices, SolderSleeve Wire Splice, Splice, .17 Splice Wire Insulation Diameter (Max) 4.32 Splice Wire Insulation Diameter (Max)



English

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solder Sleeves & Shield Tubing category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

899170-000 620040N001 620069N003 CTA-0050-01 629624-000 6500750004 6501390002 CX0781-000 696396-000 697080-000 D-150-0331CS2902 D-181-1222-90/9CS2800 D-300-01CS1108 715325N001 908357N001 982127-1 D-436-0182CS246 D-436-37CS2651 D-436-61CS246 D-436-82-CS2621 D-659-0087 E53797N001 CB0213-000 CB0219-000 S200-2-01 S200-4-00CS2904 LSS-81-16AA-CS5575 ST18-2-00 FLX40-020-04-CS8651 325534-000 CTA-0025 D-108-07CS436 D-128-0010 D-141-0108CS404 D-144-41CS1371 D-150-0231-NRCS2896 D-150-1011 395947-000 427243N001 B-801-18-01 515-9 C67137-000 CB0220-000 D-436-0185CS1102 D-436-36CS2908 D-436-37CS2908 D-436-52CS246 D44133N001 LSS-26-8A 626168-000