Raychem S200 Shield Terminators

High-Performance, High-Temperature Cable Terminators



Heat-Shrinkable Sleeve for Fast, Reliable, Economical Cable Shield Termination and Grounding

An important extension of the Raychem SolderSleeve family, S200 shield termination devices were developed specifically to address the need for high-temperature connecting, insulating, and sealing for applications in the aerospace and defense industry.



LET'S CONNECT

We make it easy to connect with our experts and are ready to provide all the support you need. Just call your local support number or visit te.com to chat with a Product Information Specialist.

Technical Support

te.com/support-center

+86 400 820 6015 +1 800 522 6752 Asia Pacific North America +81 044 844 8180 North America (Toll) Japan +61 2 9554 2695 EMEA/South Africa +800 0440 5100 Australia +64 (0) 9 634 4580 +31 73 624 6999 New Zealand India (Toll-Free) +800 440 5100

te.com/ADM

AMP, AGASTAT, CII, DEUTSCH, HARTMAN, KILOVAC, LL ROWE, MICRODOT, NANONICS, POLAMCO, Raychem, SEACON, SolderSleeve, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Corporation. Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications

© 2017 TE Connectivity Corporation All Rights Reserved.

1-1773851-1 07/17





Raychem S200 Shield Terminators

Fast, Easy Shield Termination and Grounding to 200°C



ECONOMICAL

- One-piece design allows for a singlestep, simplified installation and a low total installed cost
- Bi-alloy or thermochromic temperature indicator works as a process control aid and simplifies operator training
- Offered in various sizes and ground lead configurations

CAPABLE

- Provides a completely soldered, strain-relieved termination
- Heat-shrinkable sleeve helps provide insulation, inspectability, and strain relief
- Designed for high-temperature applications up to 200°C
- Sealing inserts helps ensure reliable, environmental protection

APPLICATIONS

- Shield termination of cables subjected to a minimum temperature rating of 150°C and maximum operating temperature of 200°C
- Protecting and sealing for BMS 13-60 PTFE wrapped cables and M27500 cables with PTFE/polyimide jackets

Wide Selection

Offered in various sizes and ground lead configurations, our S200 shield termination devices provide environmentally protected shield termination on cables with a minimum temperature rating of 150°C, and silver or nickel-plated shields. They are also available with bi-alloy or thermochromic indicators

Fast Installation and Lower Costs

Convenient to use, the one-piece design of S200 shield termination devices help ensure reliable environmental protection and greatly simplified installation for a lower total installed cost.

MATERIALS

- Solder: Tin 96%/Silver 4% bi-alloy solder
- Tubing: Heat-shrinkable modified fluoropolymer
- Inserts: Thermoplastic fluoropolymer

STANDARDS AND SPECIFICATIONS

Industry Standards:

SAE-AMS-DTL-23053/13 (applies to heat-shrinkable insulation sleeve only)
SAE-AS83519 (modified for 200°C applications)
EU RoHS/ELV compliant

- TE Instruction Sheet: RCPS-100-71
- TE Qualification and Test Report: Available on request

MECHANICAL/ENVIRONMENTAL

- Operating Temperature: 150°C to 200°C
- **Durability**: Heat-shrinkable sleeve adheres and seals to provide a completely soldered, strain-relieved termination

TE Components . . . TE Technology . . . TE Know-how . . . AMP | AGASTAT | CII | HARTMAN | KILOVAC | MICRODOT | NANONICS | POLAMCO | Raychem | Rochester | DEUTSCH SEACON Phoenix | LL ROWE | Phoenix Optix | AFP | SEACON

Empower Engineers to Solve Problems, Moving the World Forward.

ORDERING INFORMATION (TC indicates that this part has a thermochromic indicator)

Without ground lead

Raychem S200 Shield Terminators

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-00	F92583-000	,
1.90	0.90	S200-1-00-TC	CN5417-000	
2.67	1.40	S200-2-00	F94898-000	
2.67	1.40	S200-2-00-TC	CN5418-000	
4.32	2.15	S200-3-00	A65903-000	
4.32	2.15	S200-3-00-TC	CN5419-000	,
5.97	3.30	S200-4-00	E32454-000	,
5.97	3.30	S200-4-00-TC	CN5420-000	
6.98	4.30	S200-5-00	D12074-000	
6.98	4.30	S200-5-00-TC	CN5421-000	

With pre-installed braid: Nickel-plated copper strands in accordance to AA59569F36N0031. (6 Inches)

Jacket OD (m	m) Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-01	CS5526-000	M83519/5-1
2.67	1.40	S200-2-01	D08259-000	M83519/5-2
4.32	2.15	S200-3-01	A77145-000	M83519/5-3
5.97	3.30	S200-4-01	F26506-000	M83519/5-4
6.98	4.30	S200-5-01	A18826-000	M83519/5-5

With pre-installed braid: Ni-plated copper strands per ASTM B355, Class 4. CMA = 1200. (6 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-9020	CJ1037-000	M83519/5-11
1.90	0.90	S200-1-9020-TC	CP7589-000	M83519/5-16
2.67	1.40	S200-2-9020	CJ1039-000	M83519/5-12
2.67	1.40	S200-2-9020-TC	CP4262-000	M83519/5-17
4.32	2.15	S200-3-9020	CJ1041-000	M83519/5-13
4.32	2.15	S200-3-9020-TC	CP6063-000	M83519/5-18
5.97	3.30	S200-4-9020	CJ1042-000	M83519/5-14
5.97	3.30	S200-4-9020-TC	CP6893-000	M83519/5-19
6.98	4.30	S200-5-9020	CJ1043-000	M83519/5-15
6.98	4.30	S200-5-9020-TC	CP7313-000	M83519/5-20

With pre-installed braid: Ni-plated copper strands per ASTM B355, Class 4. CMA = 1800. (6 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-9030	CA7639-000	,
2.67	1.40	S200-2-9030	CA7640-000	,
4.32	2.15	S200-3-9030	CA7641-000	
5.97	3.30	S200-4-9030	CA7642-000	
6.98	4.30	S200-5-9030	CA7643-000	
6.98	4.30	S200-5-9030-TC	CP7417-000	

With pre-installed braid: High nickel-plated copper strands per ASTM-B355 Class 7. CMA = 640. (10 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-01-100HN	D89883-000	'
2.67	1.40	S200-2-01-100HN	A87947-000	
4.30	2.15	S200-3-01-100HN	A59779-000	
5.95	3.30	S200-4-01-100HN	C69495-000	
6.90	4.30	S200-5-01-100HN	D92195-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-55-22-9	EH1934-000	
2.67	1.40	S200-2-55-22-9	EH1935-000	
4.30	2.15	S200-3-55-22-9	EH1936-000	
5.95	3.30	S200-4-55-22-9	EH1938-000	
6.90	4.30	S200-5-55-22-9	EH1939-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-55-20-9	EH1940-000	
2.67	1.40	S200-2-55-20-9	EH1941-000	
4.30	2.15	S200-3-55-20-9	EH1942-000	
5.95	3.30	S200-4-55-20-9	EH1943-000	
6.90	4.30	S200-5-55-20-9	EH1944-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

0.90	00001 55 10 0		
0.50	S200-1-55-18-9	EH1945-000	
1.40	S200-2-55-18-9	EH1946-000	
2.15	S200-3-55-18-9	EH1948-000	
3.30	S200-4-55-18-9	EH1949-000	
4.30	S200-5-55-18-9	EH1950-000	
	1.40 2.15 3.30	1.40 \$200-2-55-18-9 2.15 \$200-3-55-18-9 3.30 \$200-4-55-18-9	1.40 S200-2-55-18-9 EH1946-000 2.15 S200-3-55-18-9 EH1948-000 3.30 S200-4-55-18-9 EH1949-000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solder Sleeves & Shield Tubing category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

D-260-C-A 899170-000 620040N001 620069N003 620263N004 CTA-0050-01 629624-000 6501390002 CX0781-000 CX0782-000 696396-000 697080-000 715325N001 FLX40-030-02-CS8652 D-436-38CS2908 CB0213-000 CB0219-000 274384-000 285343-000 970053-000 ST18-2-00 FLX40-020-04-CS8651 317035-000 325534-000 D-100-00-WOTI D-150-1011 395947-000 427243N001 C03534-000 CB0220-000 D44133N001 477436-000 451893-000 931289-000 162583-000 585769N001 610001N004 6200060004 622041N003 626167-000 EG3678-000 650075N002 6500820003 6500850004 650126N010 650127N005 146201-000 7400720001 CA3200N001 82-A2