D-146-0207 - ACTIVE

Raychem

TE Internal #: 624512-000 SolderSleeve Shield Terminators, Operating Temperature (Max) 150 °C, Expanded Inside Diameter (Min) .181 in [4.6 mm] View on TE.com >



Wire Protection & Management > Interconnect Devices > SolderSleeve Shield Terminators



Operating Temperature (Max): 150 °C Expanded Inside Diameter (Min): 4.6 mm [.181 in] Recovered Inside Diameter (Max): 1.78 mm [.07 in] Pre-Installed Lead: Yes Wire Size: .34 mm²

Features

Configuration Features

Pre-Installed Lead	Yes
Dimensions	
Expanded Inside Diameter (Min)	4.6 mm[.181 in]
Recovered Inside Diameter (Max)	1.78 mm[.07 in]

22 AWG
150 °C
125 °C
Not Compliant
Not Compliant
Not Compliant
Restricted Materials Above Threshold
Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (37% in Solder) Article Safe Usage Statements:

D-146-0207

SolderSleeve Shield Terminators, Operating Temperature (Max) 150 °C, Expanded Inside Diameter (Min) .181 in [4.6 mm]



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Not applicable for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CJ2087-000 HL2010E-KIT-120V

Customers Also Bought



D-146-0207

SolderSleeve Shield Terminators, Operating Temperature (Max) 150 °C, Expanded Inside Diameter (Min) .181 in [4.6 mm]



TE Part #207575-1 PLUG, 7 POS ECONOSEAL

Documents

Product Drawings D-146-0207

English

Datasheets & Catalog Pages Raychem Electrical Interconnect Products

English

Product Specifications
Product Specification

English

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solder Sleeves & Shield Tubing category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

 899170-000
 620040N001
 620069N003
 CTA-0050-01
 629624-000
 6500750004
 6501390002
 CX0781-000
 696396-000
 697080-000
 D-150

 0331CS2902
 D-181-1222-90/9CS2800
 D-300-01CS1108
 715325N001
 908357N001
 982127-1
 D-436-0182CS246
 D-436-37CS2651
 D-436

 61CS246
 D-436-82-CS2621
 D-659-0087
 E53797N001
 CB0213-000
 CB0219-000
 S200-2-01
 S200-4-00CS2904
 LSS-81-16AA-CS5575

 ST18-2-00
 FLX40-020-04-CS8651
 325534-000
 CTA-0025
 D-108-07CS436
 D-128-0010
 D-141-0108CS404
 D-144-41CS1371
 D-150-0231

 NRCS2896
 D-150-1011
 395947-000
 427243N001
 B-801-18-01
 515-9
 C67137-000
 CB0220-000
 D-436-0185CS1102
 D-436-36CS2908
 D

 436-37CS2908
 D-436-52CS246
 D-436-83CS2705
 D44133N001
 LSS-26-8A
 D
 D
 D
 D
 D
 D