


# D3044 Product Details



D3044



Active

## Communications / Signal PC Board Relays



[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- D30 / FP Relay Series
- DC Actuating System
- Input Voltage = 6 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 2 Amps.

[View all Features](#) | [Find Similar Products](#)

[Previous 1 ... 11 12 13 14 \[15\] ... 20 Next](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- [AXICOM Telecom, Signal and RF Relays](#) (PDF, English)
- [TELECOM AND SIGNAL RELAYS](#) (PDF, English)

### Product Specifications:

- [FP2 Relay Datasheet](#) (PDF, English)

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Termination Type = Through Hole

### Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 6
- Contact Current Rating (Amps.) = 2
- [Coil Resistance \(?\)](#) = 360
- Coil Power, Nominal (mW) = 100
- Dielectric Between Coil and Contacts (V rms) = 1100

### Body Related Features:

- [Series](#) = D30 / FP Relay
- Polarized = Yes

### Contact Related Features:

- Number of Bistable Coils = Single
- Mounting Options = PC Board
- Enclosure = Immersion Cleanable
- [FCC Part 68 Isolation](#) = Yes
- Approved Standards = CECC Approved, CSA Certified, UL Recognized
- Contact Material = Silver Nickel, Gold Overlay
- Approx. Dimensions (L x W x H) (mm[in]) = 14.00 x 9.00 x 5.00 [.551 x .354 x .197]
- DIP Package Style = Horizontal
- Contact Type = Bifurcated
- Pin Configuration = DIP

### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Polarized, Bistable
- Coil Suppression Diode = Without

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### Other:

- Brand = Axicom



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [General Purpose Relays](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[APF30318](#) [JVN1AF-4.5V-F](#) [PCN-105D3MHZ](#) [5JO-10000S-SIL](#) [5JO-1000CD-SIL](#) [5JO-400CD-SIL](#) [LY2S-AC220/240](#) [LYQ20DC12](#)  
[6031007G](#) [6131406HQ](#) [6-1393099-8](#) [6-1393122-4](#) [6-1393123-2](#) [6-1393767-1](#) [6-1393843-7](#) [6-1415012-1](#) [6-1419102-2](#) [6-1423698-4](#) [6-](#)  
[1608051-6](#) [6-1608067-0](#) [6-1616170-6](#) [6-1616248-2](#) [6-1616282-3](#) [6-1616348-2](#) [6-1616349-9](#) [6-1616350-1](#) [6-1616350-8](#) [6-1616358-7](#) [6-](#)  
[1616359-9](#) [6-1616360-9](#) [6-1616931-6](#) [6-1617039-1](#) [6-1617052-1](#) [6-1617090-2](#) [6-1617090-5](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617801-8](#) [6-](#)  
[1618107-9](#) [6-1618248-4](#) [M83536/1-027M](#) [CX-4014](#) [MAHC-5494](#) [MAVCD-5419-6](#) [703XCX-120A](#) [7-1393100-5](#) [7-1393111-7](#) [7-1393767-8](#)  
[7-1414968-8](#) [7-1419130-3](#)