

KILOVAC EV200 Series Contactor With 1 Form X (SPST-NO) Contacts Rated 500+ Amps, 12-900 Vdc

Product Facts

- Designed to be the smallest, lightest weight, lowest cost sealed contactor in the industry with its current rating (500+A carry, 2000A interrupt at 320VDC)
- Built-in coil economizer — only 1.7W hold power @ 12VDC and it limits back EMF to 0V. Models requiring external economizer also available
- Optional auxiliary contact for easy monitoring of power contact position
- Hermetically sealed — intrinsically safe, operates in explosive/harsh environments with no oxidation or contamination of coil or contacts, during long periods of non-operation
- Versatile coil/power connections
- UL Recognized for the U.S. and Canada (File E208033) All contact ratings & coil versions may not be UL Recognized
- CE marked for EC applications
- AIAG QS9000 designed, built and approved
- RoHS versions available



EV200 Series Contactor (CZONKA Relay, Type)

Coil Operating Voltage (Valid Over Temperature Range)			
Voltage (Will Operate)	9-36VDC	32-95VDC	48-95VDC
Voltage (Max.)	36VDC	95VDC	95VDC
Pickup (Close) Voltage Max.	9VDC	32VDC	48VDC
Hold Voltage (Min.)	7.5VDC	22VDC	34VDC
Dropout (Open) Voltage (Min.)	6VDC	18VDC	27VDC
Inrush Current (Max.)	3.8A	1.3A	0.7A
Holding Current (Avg.)	0.13A@12V, 0.07A@24V	0.03A@48V	0.02A@72V
Inrush Time (Max.)	130ms	130ms	130ms

Ordering Information

Typical Part Number ► **EV200 A A A N A**

Series: EV200 = 500+ Amp, 12-900VDC Contactor

Contact Form:
 A = Normally Open
 H = Normally Open with NO Aux. Contacts
 G = Normally Open with NC Aux. Contacts ⁴

Coil Voltage:
 A = 9-36VDC (1 = requires external coil economizer)
 D = 32-95VDC (2 = requires external coil economizer)
 J = 48-95VDC (3 = requires external coil economizer)
 R = 28VDC with Mechanical Economizer

Coil Wire Length:
 A = 15.3 in (390 mm)

Coil Terminal Connector:
 N = None
 C = Molex Mini-fit Jr, 2 Skt, Female 18-24, P/N 39-01-2020 & 39-00-0060 +red is pin 1 (A length only)

Mounting & Power Terminals:
 A = Bottom Mount & Male 10mm x M8 Terminals

Performance Data

Contact Arrangement, Power Contacts — 1 Form A (SPST-NO)
Rated Operating Voltage — 12 - 900 VDC
Continuous (Carry) Current, Typical — 500 A @ 85°C, 400 mcm conductors
Consult Factory for required conductors for higher (500+ A) currents
Make/Break Current at Various Voltages 1 — See graph next page
Break Current at 320VDC 1 — 2,000 A, 1 cycle ³
Contact Resistance, Typ. (@200A) — 0.2 mohms
Load Life — See graph next page
Mechanical Life — 1 million cycles
Contact Arrangement, Auxiliary Contacts — 1 Form A (SPST-NO)
Aux. Contact Current, Max. — 2A @ 30VDC / 3A @ 125VAC
Aux. Contact Current, Min. — 100mA @ 8V
Aux. Contact Resistance, Max. — 0.417 ohms @ 30VDC / .150 ohms @ 125VAC
Operate Time @ 25°C — Close (includes bounce), Typ. — 15 ms Bounce (after close only), Max. — 7 ms Release (includes arcing), Max @ 2000A — 12 ms
Dielectric Withstanding Voltage — 2,200 Vrms @ sea level (leakage <1mA)
Insulation Resistance @ 500VDC — 100 megohms ²
Shock, 11ms 1/2 Sine, Peak, Operating — 20 G
Vibration, Sine, 80-2000Hz., Peak — 20 G
Operating Ambient Temperature — -40°C to +85°C
Weight, Nominal — .95 lb. (.43 kg)

Notes:

- 1 Main power contacts
- 2 50 at end of life
- 3 Does not meet dielectric & IR after test, 1700 amp for unit with Aux. Contacts
- 4 Meets IEC 60947-4-1 Annex F Mirror Contact

IEC2136/02

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.

7 KILOVAC High Voltage DC Contactors

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Relays](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[6-1617801-8](#) [6-1618107-9](#) [7-1618273-3](#) [EV250-4A-02](#) [EV250-6A-01](#) [FCA-125-CX8](#) [FCA-325-159](#) [FCA-410-138](#) [8000-S3121](#) [8-1618273-6](#)
[8-1618393-1](#) [GCA63A220VAC60HZ](#) [GCA63A277VAC60HZ](#) [GCA63A600VAC60HZ](#) [1-1672275-3](#) [1-1833005-4](#) [H-16/S1](#) [A711Z](#) [H-8C](#)
[H-8/S11](#) [H-8/S68](#) [ACC530U20](#) [ACC730U30](#) [RF303ZM4-12](#) [DH18DA](#) [1423675-8](#) [AR4-15F13-C01](#) [AR7-41F11](#) [AVR907](#) [15732A200](#)
[B07B032AC1-0329](#) [B329](#) [B490A](#) [1618279-1](#) [BHR124Y](#) [1810DDB-SX](#) [N417](#) [P30C42A12D1-120](#) [2-1617748-6](#) [2-1618375-1](#) [2-1618396-6](#)
[2-1618398-1](#) [JMAPD-5XL](#) [JMGACD-5M](#) [JMGSC-5LW](#) [JMGSCD-5L](#) [PBO-18A1218](#) [PBO-40A3040](#) [K8DSPH1200480VAC](#) [KA-3C-12A](#)