



FS19

Force Load Cell

SPECIFICATIONS

- All stainless steel construction
- Small compression load 350G to 3000G range
- High sensitivity 20 mV/V
- Non-linearity +/-1% FS
- Flex cable for tight space

The FS19 load cell, with ranges from 350G to 3000G, uses proven Microfused sensor technology derived from demanding aerospace and automotive applications which employs micro-machined piezoresistive strain gages fused with high temperature glass to a high performance stainless steel force measuring flexure. This sensing technology eliminates age-sensitive organic epoxies used in traditional load cell designs, providing excellent long term stability. This high sensitivity strain gage allows the load cell to produce 20 mv/V output with low strains and deflection, thus long endurance in the smallest package. The flexure is precisely machined to produce excellent consistency from part to part. Typical applications range from medical devices to appliances and exercise equipment.

FEATURES

- Small size
- High sensitivity
- High overload
- Low deflection
- Long life
- Low cost

APPLICATIONS

- Infusion Pumps
- Load Sensing
- Contact Sensing
- Weighing
- Household Appliances

PERFORMANCE SPECIFICATIONS





All specifications are at 25°C except where indicated.

| PARAMETER | MIN | TYP | MAX | UNITS, NOTES |
|-------------------------------|------------------------|------------|------------|---|
| Force Range | 350/500/1000/2000/3000 | | | G |
| Excitation Voltage | 2 | 5 | 10 | VDC |
| Sensitivities (FSO) | 14 | 20 | 26 | mV/V, Ratiometric to excitation voltage |
| Non-Linearity | -1 | | 1 | %FSO |
| Hysteresis | -1 | | 1 | %FSO |
| Zero Offset | -9 | | +9 | mV/V, Ratiometric to excitation voltage |
| Operating Temperature | 0 | | 40 | °C |
| Storage Temperature | -40 | | 85 | °C |
| Humidity | 0 | | 95 | % RH |
| Safe Load Limit | | | 2x | Rated load |
| Insulation | 50 | | | Meg ohms at 250 VDC |
| Deflection | | | 0.020 | mm at rated load |
| Input Resistance | 1.50K | 2.15K | 2.80K | Ω |
| Output resistances | 1.50K | 2.15K | 2.80K | Ω |
| Thermal Error – Sensitivities | -0.05 | | +0.05 | %FSO / °C |
| Thermal Error –Zeros | -0.5 | | +0.5 | %FSO / °C |
| Response Time | | | 1 | ms |
| ESD | | | ±15 | KV, 10 discharges qualified per IEC |
| Weight | | 1.1 | | gram |
| Weather Proof | | IP43 | | |

FS19

Force Load Cell

DIMENSIONS (mm)



ORDERING INFORMATION

| | | | | |
|---------------|---|-------------|---|--|
| FS1901 | - | 0000 | - | 1000G |
| Model | - | 0000 | - | Force Range |
| FS1901 | - | 0000 | - | 0350G 0500G 1000G 2000G 3000G |

NORTH AMERICA

Measurement Specialties, Inc.,
a TE Connectivity Company
Tel: 1-800-522-6752
Email : customercare.lcsb@te.com

EUROPE

MEAS France SAS,
a TE Connectivity company
Tel: +33 (0) 800-440-5100
Email : customercare.lcsb@te.com

ASIA

Measurement Specialties (China), Ltd.,
a TE Connectivity Company
Tel: +86 400-820-6015
Email: customercare.shzn@te.com

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Force Sensors & Load Cells](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[FC2311-0000-1000-L](#) [ELAF-50N-TS0011](#) [3397-300](#) [060-1436-10-02](#) [060-1436-09-02](#) [060-0571-04-09](#) [FN3030-A1-100N](#) [060-7472-01](#)
[FSAGPDXX005LCSB5](#) [FC2311-0000-0250-L](#) [FC2311-0000-2000-L](#) [FX1901-0001-0025-L](#) [FX1901-0001-0100-L](#) [VBS020601](#) [VBS020701](#)
[MF01-N-221-A04](#) [FS2050-0000-1500-G](#) [FX1900-0000-0025-L](#) [FX1901-0001-0050-L](#) [4543](#) [MF01A-N-221-A01](#) [MF01A-N-221-A03](#)
[MF01A-N-221-A04](#) [MF01A-N-221-A06](#) [MF01-N-220-A01](#) [MF22-N-000-A01](#) [HSFPAR003A](#) [3173-1K](#) [FMAMSDXX005WC2C3](#)
[FMAMSDXX005WCSC3](#) [FMAMSDXX015WCSC3](#) [FMAMSDXX025WCSC3](#) [FS01](#) [FS03](#) [FSAGPDXX001RCAB5](#)
[FSAGPDXX010WCAA5](#) [FSAGPNXX001RC4C5](#) [FSAGPNXX1.5LCAC5](#) [FSG005WNPB](#) [FSG020WNPB](#) [FSG15N1A](#) [FSS005WNGR](#)
[FSS005WNSB](#) [FSS010WNSB](#) [FSS005WNGB](#) [FSS015WNGB](#) [FSS020WNGR](#) [FSS020WNSB](#) [FSS1500NGT](#) [FSS1500NSB](#)