

COIL: @ 25°C


RESISTANCE 40 OHMS ± 10%  
 NOMINAL VOLTAGE 6.0 Vdc  
 MUST OPERATE 3.2 Vdc  
 MUST RELEASE .35 Vdc

ENVIRONMENT:

VIBRATION 10 CPS TO 2000 CPS AT 100 g's  
 SHOCK 65 g's 11 ± 1 MS. DURATION  
 TEMPERATURE -65 °C TO +125 °C

NOTES: RELAY IS RATED FOR GROUNDED CASE APPLICATION

CUSTOMER DATA SHEET



CONTACT RATING: 2 A @ 28 Vdc,  
.3 A @ 115 Vac, .75 A @ 28 Vdc  
(.200 HENRY), LOW LEVEL  
10-50 μA @ 10-50 mVdc

DR. 01-12-82

CK. JAL



**Communications  
Instruments, Inc.**

CUST. QPL  
 CUST. NO. M39016/6-123L

TYPE HFV RELAY

HFV 1201 F01

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Industrial Relays](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[6-1617801-8](#) [6-1618107-9](#) [7-1618273-3](#) [EV250-4A-02](#) [EV250-6A-01](#) [FCA-125-CX8](#) [FCA-325-159](#) [FCA-410-138](#) [8000-S3121](#) [8-1618273-6](#)  
[8-1618393-1](#) [GCA63A220VAC60HZ](#) [GCA63A277VAC60HZ](#) [GCA63A600VAC60HZ](#) [1-1672275-3](#) [1-1833005-4](#) [H-16/S1](#) [A711Z](#) [H-8C](#)  
[H-8/S11](#) [H-8/S68](#) [ACC530U20](#) [ACC730U30](#) [RF303ZM4-12](#) [DH18DA](#) [1423675-8](#) [AR4-15F13-C01](#) [AR7-41F11](#) [AVR907](#) [15732A200](#)  
[B07B032AC1-0329](#) [B329](#) [B490A](#) [1618279-1](#) [BHR124Y](#) [1810DDB-SX](#) [N417](#) [P30C42A12D1-120](#) [2-1617748-6](#) [2-1618375-1](#) [2-1618396-6](#)  
[2-1618398-1](#) [JMAPD-5XL](#) [JMGACD-5M](#) [JMGSC-5LW](#) [JMGSCD-5L](#) [PBO-18A1218](#) [PBO-40A3040](#) [K8DSPH1200480VAC](#) [KA-3C-12A](#)