# JMACD-26XM V ACTIVE

### CII

TE Internal #: 1-1617122-2 TO-5/.100 Grid Relays, 2 Form C, DPDT, 2 C/O, 26.5VDC TO-5/.100 Grid Relay Input Voltage, Coil Suppression Diode View on TE.com >





TO-5/.100 Grid Relay Contact Arrangement: **2 Form C, DPDT, 2 C/O** 

TO-5/.100 Grid Relay Input Voltage: 26.5 VDC

Coil Suppression Diode: With

MOSFET Driver: Without

Transistor Driver: Without

### Features

### Product Type Features

Enclosure Type	Hermetically Sealed	
Relay Type	Military/Aerospace High Performance	
Coil Latching	Without	



Product Type	Relay			
MOSFET Driver	Without			
Configuration Features				
Transistor Driver	Without			
Electrical Characteristics				
Coil Magnetic System	Non-Polarized, Monostable			
Vibration	30G's, 10 – 3000Hz			
Actuating System	DC			
Shock	75G's, 6ms			
Coil Power Measurement	Milliwatts			
TO-5/.100 Grid Relay Input Voltage	26.5 VDC			
Coil Suppression Diode	With			
Coil Voltage	26.5 VDC			
TO-5/.100 Grid Relay Coil Resistance	1560 Ω			
TO-5/.100 Grid Relay Coil Power Rating (DC)	450 mW			

#### JMACD-26XM

TO-5/.100 Grid Relays, 2 Form C, DPDT, 2 C/O, 26.5VDC TO-5/.100 Grid Relay Input Voltage, Coil Suppression Diode



Coil Polarity Protection Diode	With
TO-5/.100 Grid Relay Contact Switching Voltage (Max)	28
Contact Features	
Contact Current Class	Low Level – 1 A
TO-5/.100 Grid Relay Contact Arrangement	2 Form C, DPDT, 2 C/O
TO-5/.100 Grid Relay Contact Current Rating	1 A
Termination Features	
Termination Type	PC Pins
Mechanical Attachment	
TO-5/.100 Grid Relay Mounting Type	Printed Circuit Board
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
<b>Product Compliance</b> For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant

China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not lead free process capable	

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

#### JMACD-26XM

TO-5/.100 Grid Relays, 2 Form C, DPDT, 2 C/O, 26.5VDC TO-5/.100 Grid Relay Input Voltage, Coil Suppression Diode



# **Compatible Parts**



# Customers Also Bought



		I A TE	
TE Part #YDTS26F15-35SNV001 PLUG ASSY	TE Part #282191-1 SPLASH PROOF CONN. W.S.L.	TE Part #2102061-9 Mezalok, Socket, 114 p, 18 mm, 50 Au, TL	TE Part #488586-001 22759/43-18-9



TE Part #1-1616058-6 A703GC=RELAY

## Documents

**CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1-1617122-2\_H.2d\_dxf.zip

English

#### JMACD-26XM

TO-5/.100 Grid Relays, 2 Form C, DPDT, 2 C/O, 26.5VDC TO-5/.100 Grid Relay Input Voltage, Coil Suppression Diode



Customer View Model ENG\_CVM\_CVM\_1-1617122-2\_H.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-1617122-2\_H.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

RELAY

English

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for General Purpose Relays category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

PCN-105D3MH,000 59641F200 5JO-1000CD-SIL 5X827E 5X837F 5X840F 5X842F 5X848E LY2N-AC120 LY2S-AC220/240 LY2-US-AC120 LY2-US-DC24 LY3-US-AC120 LY4F-UA-DC12 LY4F-UA-DC24 LY4F-US-AC120 LY4F-US-AC240 LY4F-US-DC24 LY4F-VD-AC110 LYQ20DC12 M115C60 M115N010 M115N0150 603-12D 60HE1-5DC 60HE2S-12DC 61211T0B4 61212T400 61222Q400 61243B600 61243C500 61243Q400 61311BOA2 61311BOA6 61311BOA8 61311COA2 61311COA1 61311COA6 61311F0A2 61311QOA1 61311QOA4 61311T0D6 61311TOA6 61311TOA7 61311TOB3 61311TOB4 61311U0A6 61312Q600 61312T400 61312T600