


REV. 0
DCO 142074

COIL: @ 25°C		
RESISTANCE	1560 OHMS	10%
NOMINAL VOLTAGE	26.5 VDC	
MUST OPERATE	14.2 VDC	
	0.13 mADC	
MUST RELEASE	8.0 VDC MAX, 1.37 VDC MIN.	

ENVIRONMENT:		
VIBRATION	10 CPS TO 3000 CPS @ 30 g's	
SHOCK	75 g's 6 MS. DURATION	
TEMPERATURE	-65 °C TO +125 °C	

NOTES:		
TURN-ON TIME 2.0 MS MAX		
TURN-OFF TIME 7.5 MS MAX		
CONTACT STABILIZATION 2.0 MS MAX		

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO
1A 28 VDC RESISTIVE 100,000
OPERATIONS

DR. PBB 6/6/00

CR. J. J. J. 6/6/00

COMMUNICATIONS
INSTRUMENTS, INC.

CUST. OPL
CUST. NO. M28776/1-036P REV.

JMAT RELAY

JMACT-26XPS

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Relays](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[6-1617801-8](#) [6-1618107-9](#) [7-1618273-3](#) [EV250-4A-02](#) [EV250-6A-01](#) [FCA-125-CX8](#) [FCA-325-159](#) [FCA-410-138](#) [8000-S3121](#) [8-1618273-6](#)
[8-1618393-1](#) [GCA63A220VAC60HZ](#) [GCA63A277VAC60HZ](#) [GCA63A600VAC60HZ](#) [1-1672275-3](#) [1-1833005-4](#) [H-16/S1](#) [A711Z](#) [H-8C](#)
[H-8/S11](#) [H-8/S68](#) [ACC530U20](#) [ACC730U30](#) [RF303ZM4-12](#) [DH18DA](#) [1423675-8](#) [AR4-15F13-C01](#) [AR7-41F11](#) [AVR907](#) [15732A200](#)
[B07B032AC1-0329](#) [B329](#) [B490A](#) [1618279-1](#) [BHR124Y](#) [1810DDB-SX](#) [N417](#) [P30C42A12D1-120](#) [2-1617748-6](#) [2-1618375-1](#) [2-1618396-6](#)
[2-1618398-1](#) [JMAPD-5XL](#) [JMGACD-5M](#) [JMGSC-5LW](#) [JMGSCD-5L](#) [PBO-18A1218](#) [PBO-40A3040](#) [K8DSPH1200480VAC](#) [KA-3C-12A](#)