



K40P Make & Break Load Switching — 5.0 kV Relays

Product Facts for K40P

- Vacuum dielectric for power switching low current loads
- Fast, 1 millisecond operate time
- Long life: 10 million cycles
- 35 Amps continuous current rating at DC; 8 Amps at 32 MHz
- Ideal for high power antenna couplers
- Meets requirements of MIL-R-83725












Product Facts for K40P364

- Double sided terminals for ease of connection to bus bar
- Vacuum dielectric for power switching low current loads
- Fast switching, high current capabilities
- Small and lightweight









Product Specifications

Contact Arrangement — SPST-Latching

Contact Form — P

Test Voltage, DC or 60 Hz (Peak) -

Rated Operating Voltage (Peak) —

DC or 60 Hz - 5 kV 2.5 MHz — 4.5 kV

16 MHz — 3.5 kV 32 MHz — 2.8 kV

Continuous Carry Current, Max. —

DC or 60 Hz - 35 A 2.5 MHz — 21 A

Coil Hi-Pot (Vrms, 60 Hz) - 500 A

16 MHz — 14 A 32 MHz — 8 A

Contact Capacitance

Between Open Contacts — 1.2 pF Open Contacts to Ground — 1.2 pF

Contact Resistance, Max. -0.02 ohm

Operate Time, Max. — 1 ms

Shock, 11ms, 1/2 Sine (Peak) -50 g

Vibration —

Peak — 30 g (55 to 2000 Hz)

Operating Ambient Temperature Range — -55°C to +125°C

Mechanical Life —10 million cycles

Weight, Nominal — 28.35 g (1.0 oz.)

Release Time, Max. — N/A

Coil Data

Volts, Nominal	26.5 Vdc
Reset & Latch, Max.	16 Vdc
Dropout	N/A
Coil Resistance (±10%)	80 Ω

Ratings listed are for 25°C, sea level conditions.

Ordering Information

K40 P 3 Sample Part Number 3 Series: **Contact Form:** P = SPST-Latching Coil Voltage: -3 = 26.5 Vdc, Bus Wire **High Voltage Connections:** 3 = Solder Connection 6 = Double Sided Solder Connection Mounting:* 4 = Standard 2 = Flanged

*See page 7-87 for mounting methods.

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.

www.te.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for General Purpose Relays category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

PCN-105D3MH,000 59641F200 LY1SAC110120 5X827E 5X837F 5X840F 5X842F 5X848E LY2N-AC120 LY2S-AC220/240 LY2-US-AC120 LY3-US-AC120 LY4F-UA-DC12 LY4F-UA-DC24 LY4F-US-AC120 LY4F-US-AC240 LY4F-US-DC24 LY4F-VD-AC110 LYQ20DC12 M115C60 M115N010 M115N0150 6031007G 603-12D 61211T0B4 61212T400 61222Q400 61243B600 61243C500 61243Q400 61311BOA2 61311BOA6 61311BOA8 61311COA2 61311COA1 61311COA6 61311F0A2 61311QOA1 61311QOA4 61311T0B6 61311TOA6 61311TOA6 61311TOB3 61311TOB4 61311U0A6 61312Q600 61312T400 61312T600 61313U200 61313U400