

M83513/03-A03C Product Details

 [Live Product Chat](#)

No Image Available

M83513/03-A03C
(9-1532012-3)

TE Internal Number: 9-1532012-3

**Superseded**[Search for Replacement Parts](#)

Microminiature D Connectors

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- Product Series = MCK (Full Metal)
- Cable Connector
- Cadmium, Yellow Chromate Shell Plating
- Number of Positions = 9
- Contact Type = Pin

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [METAL SHELL "D" CONNECTOR PLUG MCK PER MIL-C-83513](#) (PDF, English)

Catalog Pages/Data Sheets:

- [MICRODOT CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Series = MCK (Full Metal)
- Product Type = Cable Connector
- Number of Positions = 9
- Comment = Also available in commercial grade.

Mechanical Attachment:

- Mounting Hardware = None
- Lead Length (mm [in]) = 457.20 [18.000]

Body Related Features:

- Shell Plating = Cadmium, Yellow Chromate
- Wire Size (AWG/CM) = 26 AWG
- Wire Type = 19 strand per MIL-C-22759/11
- Insulation Color = 10 solid color repeating per M-85513

Contact Related Features:

- Contact Type = Pin
- Contact Style = Wire Termination
- Contact Base Material = Copper Alloy
- Contact Mating Area Plating Material = Gold (50) per MIL-G-45204

Housing Related Features:

- Housing Material = Polyphenylene Sulfide

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Other:

- Brand = Microdot

[Provide Website Feedback](#) | [Need Help?](#)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub Mil Spec Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[M85049/50-5F](#) [D38999/24WG11PB-LC](#) [MDM-15PH006M7-A174](#) [MDM-15SH001M7-A174](#) [MDM-15SH003M7-A174](#) [MDM-15SH006M7-A174](#) [MDM-21PH046F](#) [MDM-21SH006B-A174](#) [MDM-21SH006P-A174](#) [MDM-21SH011P](#) [MDM-21SH011P-A174](#) [MDM-21SH034B-A174](#) [MDM25SL61P](#) [1484349-1](#) [17D25HV](#) [1996840-1](#) [308-CP3C1001-076](#) [1757682-1](#) [17D-E51218-1](#) [17SDA15S](#) [1883533-1](#) [1883889-1](#) [192900-0377](#) [308-CP6P0441-024H](#) [M83513/03-E09C](#) [MDM-15PH001F](#) [MDM-15PH001P-A174](#) [MDM-15PH011P](#) [MDM-15PH011P-A174](#) [MDM-15SH006M7](#) [MDM-15SH011F-A174](#) [MDM-15SH011P](#) [MDM-15SH011P-A174](#) [MDM-21PH006M7](#) [MDM-21PH041F](#) [MDM-21PH048F](#) [MDM-21SH046B-A174](#) [MDM-25PH001M7-A174](#) [MDM-25SH011P](#) [MDM-9PCBRM7-F222](#) [MDM-9SH001F](#) [MDM-9SH006P-A174](#) [5-1218949-1](#) [550-031NF1R6K](#) [550E001NF1R3J0L](#) [550T001NF1R6K0L](#) [557T283NF5B08](#) [DB121073-56](#) [DC121073157](#) [443869-5](#)