

## M83513/03-A04C Product Details

 [Live Product Chat](#)

No Image Available

**M83513/03-A04C**  
(9-1532012-4)

TE Internal Number: 9-1532012-4

**Superseded**[Search for Replacement Parts](#)

### Microminiature D Connectors

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- Product Series = MCK (Full Metal)
- Cable Connector
- Cadmium, Yellow Chromate Shell Plating
- Number of Positions = 9
- Contact Type = Pin

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)





### Documentation & Additional Information

#### Product Drawings:

- [METAL SHELL "D" CONNECTOR PLUG MCK PER MIL-C-83513](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- [MICRODOT CATALOG](#) (PDF, English)

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Series = MCK (Full Metal)
- Product Type = Cable Connector
- Number of Positions = 9
- Comment = Also available in commercial grade.

#### Mechanical Attachment:

- Mounting Hardware = None
- Lead Length (mm [in]) = 914.40 [36.000]

#### Body Related Features:

- Shell Plating = Cadmium, Yellow Chromate
- Wire Size (AWG/CM) = 26 AWG
- Wire Type = 19 strand per MIL-C-22759/11
- Insulation Color = 10 solid color repeating per M-85513

#### Contact Related Features:

- Contact Type = Pin
- Contact Style = Wire Termination
- Contact Base Material = Copper Alloy
- Contact Mating Area Plating Material = Gold (50) per MIL-G-45204

#### Housing Related Features:

- Housing Material = Polyphenylene Sulfide

#### Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

#### Other:

- Brand = Microdot

[Provide Website Feedback](#) | [Need Help?](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub MIL Spec Connectors](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[M85049/50-5F](#) [D38999/24WG11PB-LC](#) [MDM-9SH006A](#) [1218697-4](#) [D38999/26WJ61PC L/C](#) [1484349-1](#) [17D25HV](#) [1996840-1](#) [243082-15](#)  
[1757682-1](#) [17D-E51218-1](#) [17SDA15S](#) [1883533-1](#) [1883886-1](#) [1883889-1](#) [192900-0377](#) [M24308/8-347](#) [M83513/03-E09C](#) [443961-3](#) [5-](#)  
[1218949-1](#) [550-031NF1R6K](#) [3-1236089-2](#) [550E001NF1R3J0L](#) [550T001NF1R6K0L](#) [557T283NF5B08](#) [DB121073-56](#) [DC121073157](#)  
[443869-3](#) [443869-4](#) [443869-5](#) [550S004NF1R1B0F03](#) [557E283NF1A06](#) [527-019NF0303R2K1F](#) [5-446405-1](#) [550-031NF1R2E](#)  
[550E003M2R9J0F04](#) [550E003M3R9J0F05](#) [550E024M104R9J0](#) [550E024NF102R3J0B](#) [550E039NF1R3J1-02](#) [550S003M3R9B0F05](#)  
[550S004M4R7M0F04](#) [550S004NF1R1B1F02](#) [550S008M3F0K0F04](#) [550S086M5R3J0L](#) [550S100NF3F0E](#) [550T001M2R7E0L](#)  
[550T001NF1F0B1L](#) [550T001NF1R1K0G](#) [550T001NF1R3K0G](#)