

Ring Tongue Terminals-Nylon (Continued)


Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152

Plating — Tin per ASTM B-545



Military Specifications MS25036 (Continued)

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Terminal Insulation Color	Wire Insulation Diameter Max.	Class	MS25036 Dash Numbers	Part Numbers		
			W	C Min.	E Max.	L Max.					Loose Piece	Tape Mounted	
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	4	.250	.171	.575	.703	Blue	.150	1 & 2	152	324159*	—	
			6.35	4.34	14.61	17.86		3.81					
		6 M3.5	.250	.171	.575	.703	Blue	.150	1 & 2	106	320561	—	2-320561-2
			.312	.281	.685	.844	Blue	.150	1 & 2	107	51864*	—	51864-3
		8 M4	.312	.281	.685	.844	Blue	.150	1 & 2	153	51864-1*	—	51864-5
		10	.312	.281	.685	.844	Blue	.150	1 & 2	108	51864-2*	—	51864-4
		1/4 M6	.469	.437	.841	1.078	Blue	.150	1 & 2	154	320563*	—	2-320563-2
		5/16 M8	.469	.437	.841	1.078	Blue	.150	1 & 2	109	320575*	—	2-320575-1
		3/8	.531	.546	.950	1.218	Blue	.150	1 & 2	110	320564*	—	2-320564-3
1/2 M12	.713	.530	.934	1.293	Blue	.150	1 & 2	155	328976	—	—		
												18.11	13.46
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	6 M3.5	.375	.302	.893	1.083	Yellow	.230	1 & 2	111	320567*	—	
													9.53
		8 M4	.375	.302	.893	1.083	Yellow	.250	1 & 2	111	35107	—	2-35107-1
		10	.375	.302	.893	1.083	Yellow	.230	1 & 2	156	320568*	—	2-320568-1
		10	.375	.302	.893	1.083	Yellow	.250	1 & 2	156	35108*	—	2-35108-1
		10	.375	.302	.893	1.083	Yellow	.230	1 & 2	112	36161*	—	2-36161-2
		1/4 M6	.531	.468	1.054	1.322	Yellow	.250	1 & 2	112	35109*	—	2-35109-1
5/16 M8	.531	.468	1.054	1.322	Yellow	.230	1 & 2	113	320569*	—	2-320569-3		
												13.49	11.89
3/8	.531	.468	1.054	1.322	Yellow	.250	1 & 2	157	35110*	—	2-35110-1		
												13.49	11.89
1/2 M12	.593	.531	1.115	1.414	Yellow	.230	1 & 2	113	320576*	—	2-320576-1		
												15.06	13.49
1/2 M12	.593	.531	1.115	1.414	Yellow	.250	1 & 2	113	35111*	—	2-35111-1		
												15.06	13.49
1/2 M12	.715	.474	1.065	1.414	Yellow	.230	1 & 2	114	320577*	—	2-320577-3		
												18.16	12.04
1/2 M12	.715	.474	1.065	1.414	Yellow	.250	1 & 2	114	35112*	—	—		
												18.16	12.04

*Available in small packaging quantities.

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[00-054007-01074-6](#) [00-054007-70206-1](#) [00-054007-70210-8](#) [00-054007-70217-7](#) [00-054007-70226-9](#) [00-054007-70228-3](#) [00-054007-70248-1](#) [00-054007-70256-6](#) [00-054007-70301-3](#) [00-054007-70316-7](#) [0-0320562-0](#) [00-054007-49560-4](#) [00-054007-70209-2](#) [00-054007-70225-2](#) [00-054007-70227-6](#) [00-054007-70231-3](#) [00-054007-70241-2](#) [00-054007-70242-9](#) [00-054007-70244-3](#) [00-054007-70246-7](#) [00-054007-70263-4](#) [00-054007-70288-7](#) [00-054007-70290-0](#) [00-054007-70300-6](#) [00-054007-70304-4](#) [01-2065-1-0216](#) [01-2900-1-04412](#) [00581P0075](#) [600TS-10](#) [60205-1](#) [604200-1](#) [605601-1](#) [60598-1-CUT-TAPE](#) [61314-6-C](#) [61810-3](#) [61-S](#) [61-SN](#) [626-0194](#) [62-NBM-A](#) [62-SN](#) [62-SP](#) [63-S](#) [640179-1](#) [M55155/059I03](#) [M55155/079C01](#) [M55155/099H02](#) [M55155/109H01](#) [M55155/109H02](#) [M55155/12XH05](#) [M55155/16XH02](#)