# ATUM-3/1-0-SP <

#### Raychem ATUM

TE Internal #: NB10594001 Raychem ATUM, Heat Shrink Tubing, Black, Dual Wall, 3 mm [.118 in] Expanded Inside, .039 in [1 mm] Recovered Inside, 3:1 Shrink Ratio

#### View on TE.com >

Heat Shrink Tubing



Primary Product Color: Black

Wall Type: Dual

Expanded Inside Diameter (Min): 3 mm [.118 in ]

Recovered Inside Diameter (Max): 1 mm [.039 in ]

Shrink Ratio: 3:1

### Features



#### Product Type Features

Product Family	ATUM
Wall Type	Dual
Electrical Characteristics	
Voltage (Max)	.6 kV
Body Features	
Fluid Type	Aviation Fuel, Chemicals/Solvents, De-Icing Fluid, Diesel Fuel, Hydraulic Fluid, Lubricating Oil
Primary Product Color	Black
Shrink Ratio	3:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Flexible
Dimensions	
Recovered Wall Thickness (Tolerance)	.3 mm[.012 in]

#### ATUM-3/1-0-SP

Raychem ATUM, Heat Shrink Tubing, Black, Dual Wall, 3 mm [.118 in] Expanded Inside, .039 in [1 mm] Recovered Inside, 3:1 Shrink Ratio



Recovered Wall Thickness (Nominal)	1 mm[.039 in]
Expanded Inside Diameter (Min)	3 mm[.118 in]
Recovered Inside Diameter (Max)	1 mm[.039 in]
Heat Shrink Tubing Size Range	1 – 3 mm[.039 – .118 in]
Usage Conditions	
Shrink Temperature (Min)	80 °C
Fluid Resistance	Moisture, Splash Protection, Spray Protection
Heat Shrink Tubing Flammability	Flame-Retardant
Operating Temperature Range	-55 – 110 °C
Heat Shrink Tubing Resistance	Fluids, Mechanical Damage, Strain Relief
Recovery Temperature	110 °C
Product Availability	
Applicable Region	Global
Packaging Features	
Packaging Method	Reel
Other	

N / I I	ow Outaccina		
	$-\alpha u (\lambda) u + \alpha \alpha \alpha u \alpha \alpha$	Doguuromonto	

|--|

Product Source

Czech Republic

### Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

#### ATUM-3/1-0-SP

Raychem ATUM, Heat Shrink Tubing, Black, Dual Wall, 3 mm [.118 in] Expanded Inside, .039 in [1 mm] Recovered Inside, 3:1 Shrink Ratio



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




TE Part # CJ2087-000 HL2010E-KIT-120V



TE Part # EG1114-000 CV1981-ST-230V1600W-EU

Also in the Series | Raychem ATUM





## **Customers Also Bought**



#### ATUM-3/1-0-SP

Raychem ATUM, Heat Shrink Tubing, Black, Dual Wall, 3 mm [.118 in] Expanded Inside, .039 in [1 mm] Recovered Inside, 3:1 Shrink Ratio







### Documents

**Product Drawings** ATUM-3/1-0-SP

English

Datasheets & Catalog Pages ATUM Pages from 9-1773447-9

English

Product Specifications

**Product Specification** 

English

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

 5685710001
 CR9960-000
 5734012004
 607381P039
 611112-000
 6284592002
 CX4711-000
 CZ1420-000
 D-306-38
 770-006S302
 770 

 010Y106W1
 770-018S103
 770-018S202W1
 770-018S205W1
 770-020S705
 MFP-3/64"-Clear
 790-3012
 MHHT-4-15K2 

 G-104
 8003012003
 MIL-LT-1-1/2-4-SP
 MIL-LT-1-1/2-9-STK
 MIL-LT-1/2-2-STK
 MIL-LT-3/0-SP
 MIL-LT-3/32-0-SP
 MIL-LT-3/32-6-SP

 MIL-LT-3/4-4-STK
 MIL-LT-3/4-6-SP
 839602-000
 8423-6
 FP301-116-48"-Clear
 FP301-12-6"-Clear
 FP301-1/4-48"-White-Hdr

 FP301-18-48"-Black-Hdr
 FP301-1/8-6"-Black
 FP301-18-6"-Black-Bulk
 FP301-316-48"-Blue-Hdr
 912229N002
 R280637030
 HDCW-5515 

 1000
 HDT-0300-48A-BLACK
 HDT-0400-48A-Black
 HDT-0800-48A-RED
 HDT1100-48A-BLK
 HDT1500-48A-BLK
 HDT-2000-48A 

 Black
 RHW-70/20-1200/ADH-0
 DWP-125-0.450-4-55MM-CS879
 156082-000
 MT5500-3/8-X-SP
 SP