


Specification Control Drawing

RAYBRAID[®] PLATED COPPER BRAID

The complete requirements for procuring the wire described herein shall consist of this document.



Braid - Copper Tin Plated

Part	Braid Detail				
Number	Strand	Number of		Minimum	Nom.
	size			Coverage	Weight #
	AWG/ mm	Carriers	Ends	%	(kg/ km)
RAY-90-3.0	36/ 0.13	16	5	90.0	13
RAY-90-4.0	36/ 0.13	16	7	90.0	17
RAY-90-5.0	36/ 0.13	24	6	90.0	21
RAY-90-6.0	36/ 0.13	24	7	90.0	25
RAY-90-10.0	34/ 0.16	24	9	90.0	52
RAY-90-12.5	34/ 0.16	24	10	90.0	65
RAY-90-15.0	32/ 0.20	24	11	90.0	100
RAY-90-20.0	30/ 0.25	36	7	90.0	165
RAY-90-25.0	30/ 0.25	36	9	90.0	207
RAY-90-30.0	28/ 0.32	36	9	90.0	310

NOTE:

The last number of the part depicts the nominal internal diameter of the braid, e.g. RAY-90-5.0 Tin Plated Copper Braid with 5.00 mm nominal internal diameter.

'#' The nominal weight value excludes weight of former

PERFORMANCE To be tested to and meet the requirements of the issue in effect of WSD 1922. REQUIREMENTS:

APPROVAL:

Electronic sign off - no signatures will appear.

RAYBRAID® is a registered trademark of Tyco Electronics Corporation.

Tyco Electronics UK Ltd Faraday Road Dorcan SWINDON SN3 5HH Tel: (01793) 528171 Telex: 449409 Registration Number: 550926 London, England This drawing and the information set forth hereon are the property of Tyco Electronics UK Ltd, and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorised in writing by Tyco Electronics UK Ltd is prohibited. This specification sheet takes precedence over documents referenced herein. As Tyco Electronics UK Ltd. reserve the right to make changes in construction without notice please contact Tyco Electronics UK Ltd to ensure that this document is the latest issue.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spiral Wraps, Sleeves, Tubing & Conduit category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

601203-000 CTA-0053 8426-11 8445-7.5 8450 120-104-24 120-113-16B 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120-116-1-1-12BE 120-116-1-1-12BP 120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-06 120-123-10 120-123-14 120-123-16 120-125-12BL 120-125-12R 120-125-16 120-125-16R 120-125-16Y 120-125-20R 120-125-24Y 120-125-28 120-125-28R 120-125-32 120-125-32R 120-125-40 120-125-56 120-126-09 120-126-09BL 120-126-12 120-126-12BL 120-126-14 120-126-16 120-126-16BL 120-126-20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-126-52 120-126-52BL 120-104-12 120-104-20