



What can we help you find?

- [Products](#)
- [Industries](#)
- [Resources](#)
- [About TE](#)
- [My Account](#)
- [Innovation](#)
- [Support Center](#)

## 2-1393240-6 Product Details

- [Share](#)
- [Print](#)
- [Email](#)



**2-1393240-6**  
(RT33LA06)

TE Internal Number: 2-1393240-6

✔ Active

### Industrial Relays (General Purpose)

✔ Converted to EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- RT1 Inrush Series
- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- Contact - Rated Current = 16 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 1 Form A (NO)

[View all Features](#)

### Quick Links

- [▶ Pricing & Availability](#)
- [▶ Search for Tooling](#)
- [▶ Product Feature Selector](#)
- [▶ Contact Us About This Product](#)

- [Add to My Part List](#)
- [Request Sample](#)
- [Find Similar Products](#)
- [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li><a href="#">Power PCB Relay RT1 Inrush (PDF, English)</a></li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li><a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li><a href="#">Tooling</a></li> </ul>
<a href="#">List all Documents</a>	

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>Contact - Current Class = 10A to 20A Class, Greater Than 16A</li> <li>Contact - Rated Current (A) = 16</li> <li>Contact - Limiting Continuous Current (A) = 16</li> <li>Contact - Limiting Making Current (A) = 80</li> <li>Contact - Limiting Breaking Current (A) = 16</li> <li>Insulation - Initial Dielectric Between Coil/Contact Class = &gt;4000V Class</li> <li>Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000</li> <li>Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000</li> <li>Contact - Rated Voltage (VAC) = 250</li> <li>Contact - Switching Voltage Max. (VAC) = 400</li> <li>Contact - Limiting Short-Time Current (A) = 16</li> <li>Coil - Rated Voltage (VDC) = 6</li> <li>Coil - Resistance (Ω) = 90</li> <li>Coil - Rated Power, DC (mW) = 400</li> <li>Insulation - Creepage Class = &gt;8mm Class</li> <li>Insulation - Clearance Class = &gt;8mm Class</li> <li>Insulation - Special Features = Tracking Index of Relay Base PTI250</li> </ul> <p><b>Dimensions:</b></p> <ul style="list-style-type: none"> <li>Mechanical - Length Class = 25mm to 30mm Class</li> <li>Length (mm [in]) = 29.00 [1.142]</li> <li>Mechanical - Width Class = 12mm to 16mm Class</li> <li>Width (mm [in]) = 12.70 [0.500]</li> <li>Mechanical - Height Class = 15mm to 16mm Class</li> <li>Height (mm [in]) = 15.70 [0.618]</li> <li>Insulation - Clearance Between Contact and Coil (mm</li> </ul>	<p><b>Body Features:</b></p> <ul style="list-style-type: none"> <li>Mount Type = PCB, Socket</li> <li>Weight (g [oz]) = 14.00 [0.494]</li> </ul> <p><b>Contact Features:</b></p> <ul style="list-style-type: none"> <li>Terminal Type = PCB-THT, Plug-in</li> <li>Contact Material = AgSnO</li> <li>Contact - Number of Poles = 1</li> </ul> <p><b>Configuration Features:</b></p> <ul style="list-style-type: none"> <li>Contact - Arrangement = 1 Form A (NO)</li> <li>Coil - Magnetic System = Bistable, 1 Coil, polarized</li> <li>Coil - Special Features = UL Coil Insulation Class F</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>RoHS/ELV Compliance = RoHS compliant, ELV compliant</li> <li>Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C</li> <li>RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> <li>Approved/Registered Standards = cCSA us, cULus, VDE</li> </ul> <p><b>Environmental:</b></p> <ul style="list-style-type: none"> <li>Environmental - Category of Protection = RTII</li> <li>Environmental - Ambient Temperature, Max. (°C [°F]) = 85 [185]</li> <li>Environmental - Ambient Temperature Class = 70°C to 85°C Class</li> </ul> <p><b>Packaging Features:</b></p> <ul style="list-style-type: none"> <li>Packaging Method = Tube</li> </ul>

[in] = 10 [0.394]

- Insulation - Creepage Between Contact and Coil (mm [in] = 10 [0.394])

**Other:**

- Series = RT1 Inrush
- Brand = Schrack
- Accessories/Socket Type = DIN-rail Socket, PCB Socket

**Corporate Information**

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

**Quick Links**

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

**Customer Support**

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

**Keep Me Informed**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [General Purpose Relays](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[APF30318](#) [JVN1AF-4.5V-F](#) [PCN-105D3MHZ](#) [5JO-10000S-SIL](#) [5JO-1000CD-SIL](#) [5JO-400CD-SIL](#) [LY2S-AC220/240](#) [LYQ20DC12](#)  
[6031007G](#) [6131406HQ](#) [6-1393099-3](#) [6-1393099-8](#) [6-1393122-4](#) [6-1393123-2](#) [6-1393767-1](#) [6-1393843-7](#) [6-1415012-1](#) [6-1419102-2](#) [6-](#)  
[1423698-4](#) [6-1608051-6](#) [6-1608067-0](#) [6-1616170-6](#) [6-1616248-2](#) [6-1616282-3](#) [6-1616348-2](#) [6-1616350-1](#) [6-1616350-8](#) [6-1616358-7](#) [6-](#)  
[1616359-9](#) [6-1616360-9](#) [6-1616931-6](#) [6-1617039-1](#) [6-1617052-1](#) [6-1617090-2](#) [6-1617090-5](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617801-8](#) [6-](#)  
[1617802-2](#) [6-1618107-9](#) [6-1618248-4](#) [M83536/1-027M](#) [CX-4014](#) [MAHC-5494](#) [MAVCD-5419-6](#) [703XCX-120A](#) [7-1393100-5](#) [7-1393111-7](#)  
[7-1393144-5](#) [7-1393767-8](#)