

## TE'S RAYVOLVE SPLICE COVERS RVS ROLL-ON SPLICES FOR SINGLE CORE CABLES 0,6/1 kV

### KEY FEATURES

- Fast, easy and tool-free installation
- Reliable protection against humidity and water
- Suitable for outdoor and direct-buried applications
- Resists moisture, ozone, fungus and temperature extremes from -40°C to 130°C
- Qualified to ANSI C119.1 and CENELEC EN 50393, UL listed
- Halogen-free and UV-resistant
- Unlimited shelf-life
- Environmentally-friendly and not subject to labeling requirements

TE Connectivity's (TE) Rayvolve RVS kits are the easy roll-on way to insulate and seal cable connections up to 0,6/1 kV. The gripping force of the specially formulated EPDM elastomer combines with a high performance sealant to form a reliable, water-resistant, insulating sleeve that is UL listed and CSA certified for direct burial applications over in-line compression or shear bolt connectors.

In addition, TE's Rayvolve kits are well suited for evaluation in other applications: wind turbines, residential junction blocks, connections to secondary network protectors, joint covers for "Y" connections in street lighting circuits, cable connection for overhead bundled cable, coax cables in telecom applications, environmental seals for terminal lugs and insulated airport connectors.

Four sizes of TE's Rayvolve sleeves cover any common low voltage cable types from 10-500 mm<sup>2</sup>. TE's Rayvolve sleeves feature a dual-wall design with an entrapped lubricant, making installation fast and simple. The elastomeric sleeve rolls onto the cable with minimal effort, even at temperatures below -25°C. The cable can be energized immediately after installation. It is ideal for use where gas or electric heating devices are not allowed.

**Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.**

## TE's Rayvolve Splice Covers RVS



Qualified to ANSI C119.1, and CENELEC EN 50393, CSA certified to C22.2 No. 198.2. UL listed per 96J4 (file E91151). For use as a secondary tap or splice cover and on standard poly- or elastomeric insulated cables.

### PRODUCT SELECTION INFORMATION - DIMENSIONS ARE IN MM

Description	Conductor Size mm <sup>2</sup>	Cable Diameter mm	Max. Connector Dimensions		Max. Sleeve Length mm	Part Number
			Diameter mm	Length mm		
<b>RVS-11</b>	10 - 70	6 - 17	17	127	205	203743-000
<b>RVS-12</b>	50 - 120	12 - 23	25	115	240	383313-000
<b>RVS-13</b>	120 - 300	18 - 30	38	180	305	437449-000
<b>RVS-14</b>	300 - 500	25 - 38	48	225	356	690155-000

Each kit contains one TE's Rayvolve RVS splice cover sleeve and sealant strips. Kits do not contain connectors.

### FAST AND SIMPLE INSTALLATION

#### Step 1:


Prepare the cable ends. The TE's Rayvolve sleeve rolls quickly and easily onto the cable. It eliminates time-consuming taping.

#### Step 2:

After connecting the conductors, apply a strip of sealant on each side of the cable at the insulation cut-back.

#### Step 3:

Roll the TE's Rayvolve sleeve into position over the sealant and connector area, completing the joint.



[te.com/energy](http://te.com/energy)

©2018 TE Connectivity. All Rights Reserved. EPP-0629-10/18-EN-IEC

Rayvolve, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this brochure are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

#### FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 896 089 903
Spain:	+ 34 916 630 400
Italy:	+ 39 333 250 0915
Benelux:	+ 32 16 508 695
Russia:	+ 7 495-790 790 2-200
China:	+ 86 (0) 400-820-6015

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8423-6](#) [8426-11](#) [8429-9](#) [25](#) [202C302-13-0](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [5026790001](#) [100-003A1000](#) [102-060-008](#) [103-013-012](#) [5356510001](#) [8445-2.5](#) [24028-1](#) [100-001A203](#) [121-103-1-1-09BFTTH](#) [420AJ001Z11402](#) [T25R-M](#) [SAS-090-1-1048-1X](#) [SAS-160-1-1030-0](#) [RAY-101-3.0\(100\)](#) [8428-18](#) [8429-12](#) [8659](#) [8328](#) [100-003A750](#) [100-003A109](#) [102-072-008](#) [HC1B-7008-0312-0](#) [2030758-3](#) [22A00010-0DH16](#) [100-003A078](#) [OSPU 10](#) [CS-A900T](#) [THP6B](#) [330.012.2](#) [330.012.3](#) [330.016.2](#) [330.020.3](#) [373.016.2](#) [CYLG-29B](#) [61747000](#) [61806130](#) [61806140](#) [166-30730](#) [162-20100](#) [348.016.1](#) [3110000817](#)