

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	07APR2015	DL	CW
	AI	ECR-15-009224	23JUN2015	DL	CW
	B	ECR-15-018481	22FEB2016	DL	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:
 INSULATION MATERIAL: PC
 RATED VOLTAGE: POWER: CONDUCTOR-CONDUCTOR: 690 V;
 CONDUCTOR-GROUND: 400 V
 SIGNAL: CONDUCTOR-CONDUCTOR: 400 V;
 CONDUCTOR-GROUND: 250 V
 RATED CURRENT: POWER: 40 A; SIGNAL: 16 A
 INSULATION RESISTANCE: $\geq 400M\Omega$
 RATED IMPULSE VOLTAGE: POWER: 6 KV; SIGNAL: 4 KV
 POLLUTION DEGREE: 3
 FLAMMABILITY: UL94V-0
 MATING CYCLES: 500
 OPERATION TEMPERATURE: $-40+125^{\circ}C$
 WIRE RANGE: POWER: 2.5-10.0 mm² (14-7 AWG)
 SIGNAL: 0.5-2.5 mm² (16-14 AWG)
 CONTACT FINISH: SILVER PLATED
 CONTACT TYPE: SCREW CONTACT

M4 THREAD
RECOMMENDED TIGHTENING TORQUE 1.2Nm4 X M3 THREAD
RECOMMENDED TIGHTENING TORQUE 0.5Nm

注释:

1. 技术参数:
 绝缘材料: PC
 额定电压: 电源: 导体-导体: 690V; 导体-地: 400V;
 信号: 导体-导体: 400V; 导体-地: 250V;
 额定电流: 电源: 40A; 信号: 16A
 绝缘电阻: $\geq 400M\Omega$
 额定脉冲电压: 电源: 6 KV; 信号: 4 KV
 污染等级: 3
 阻燃等级: UL94V-0
 插拔次数: 500次
 工作温度: $-40+125^{\circ}C$
 接线范围: 电源: 2.5-10.0 mm² (14-7 AWG)
 信号: 0.5-2.5 mm² (16-14 AWG)
 端子表面处理: 镀银
 接线类型: 螺丝压接

PANEL CUT OUT FOR INSERTS FOR USING
WITHOUT HOODS/HOUSINGS

T2106062101-000

HWK6/6-012-M
HWK6/6-012 公插PART NUMBER
料号PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 07APR2015

DAVID LI

CHK 07APR2015

CHRIS WANG

APVD 07APR2015

XU XIANG

PRODUCT SPEC

108-137126

APPLICATION SPEC

114-137126

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±0
1 PLC	±0.1
2 PLC	±0.15
3 PLC	±0.2
4 PLC	±0.25
ANGLES	±0.5
FINISH	-

MATERIAL

-

-

NAME

HDC-HWK6/6-012-M

SIZE A3

CAGE CODE -

DRAWING NO. ©-T2106062101000

RESTRICTED TO -

SCALE 1:1

SHEET 1 OF 1

REV B

1470-19 (3/13)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[1424439](#) [1424438](#) [09330062652](#) [2-8675P1](#) [580129-2](#) [605601-1](#) [6340G1](#) [6341G1](#) [6360G1](#) [6373G1](#) [6374g2](#) [6396G1](#) [647757-1](#) [66394-4](#)
[6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646348-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651778-1](#) [6651788-1](#) [696465-1](#) [696475-1](#) [73000005059](#) [73000005349](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#)
[765-16-0080B](#) [789.700-44](#) [789.700-54](#) [80-1010](#) [80-9](#) [827381-1](#) [829992-1](#) [902-77-02113](#) [PL00U-301-10D10](#) [PM103MOOLOO](#)
[PM16S1620S32-50](#) [PM212MOOLOO](#) [PM309FOOLOO](#) [PM324FOOLCH](#)