

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|---------------|-----------|-----|------|
| | A | INITIAL | 14APR2015 | DW | CW |
| | B | ECR-15-018270 | 09DEC2015 | DW | CW |
| | B1 | ECR-16-006849 | 13MAY2016 | RL | CW |
| | C | ECR-21-111798 | 28SEP2021 | WQR | CW |

T2111122201-000 SHOWN,
带 LOGO, 产品型号, 认证标示

T2111122201-001 SHOWN, ALL DIMENSIONS ARE
SAME AS T2111122201-000, EXCEPT WITHOUT LOGO,
TYPE DESCRIPTION, TUV AND CUL MARK
不带 LOGO, 产品型号和认证标示

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250V
RATED CURRENT: 10A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40\sim+125^{\circ}C$
WIRE RANGE: $0.14\sim 2.5\text{ mm}^2$ (26~14 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20200X20XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 4KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40\sim+125^{\circ}C$
接线范围: $0.14\sim 2.5\text{ mm}^2$ (26~14 AWG)
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20200X20XX000)

| | |
|-------------------|---|
| T2111122201-001 | HMN-012-F WITHOUT LOGO HMN-012模块母插 不带LOGO, 产品型号和认证标示 |
| T2111122201-000 | HMN-012-F WITH LOGO HMN-012模块母插 |
| PART NUMBER 料号 | PART DESCRIPTION 描述 |

THIS DRAWING IS A CONTROLLED DOCUMENT.

| DIMENSIONS: | TOLERANCES UNLESS OTHERWISE SPECIFIED: |
|-------------|--|
| mm | |
| | 0 PLC \pm |
| | 1 PLC \pm |
| | 2 PLC \pm |
| | 3 PLC \pm |
| | 4 PLC \pm |
| | ANGLES \pm |
| MATERIAL | FINISH |
| - | - |
| - | - |

| | | |
|------------------|------------|------------|
| DWN | 14APR2015 | David Wang |
| CHK | 14APR2015 | Chris Wang |
| APVD | 14APR2015 | Xiang Xu |
| PRODUCT SPEC | 108-137121 | |
| APPLICATION SPEC | 114-137121 | |
| WEIGHT | - | |
| Customer Drawing | | |

| | | | | |
|-----------------|-----|------------------|-----------|-----------|
| TE Connectivity | | NAME | | HMN-012-F |
| | | SIZE | CAGE CODE | |
| DRAWING NO | | RESTRICTED TO | | |
| A300779 | | G-T2111122201000 | | |
| SCALE | 1:1 | SHEET | 1 OF 1 | REV |
| | | | | C |

1470-19 (3/13)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#)
[765-18-0080D](#) [829992-1](#) [902-77-02113](#) [PS00/A0620/6300](#) [PS25/A0420/63](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#)
[MS3117-14AC](#) [1643543-1](#) [1650540-1](#) [1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-](#)
[W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#)