

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	22DEC2014	DW	CW
	B	ECR-15-018481	23FEB2016	DW	CW
	C	ECR-21-111798	10SEP2021	WQR	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: POWER: 690 V; SIGNAL: 250V  
 RATED CURRENT: POWER: 40 A; SIGNAL: 10A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: POWER: 8 KV; SIGNAL: 4 KV  
 POLLUTION DEGREE: 2  
 CONTACT RESISTANCE: POWER:  $\leq 1 m\Omega$ ; SIGNAL:  $\leq 5 m\Omega$   
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500 CYCLES  
 OPERATION TEMPERATURE:  $-40+125^{\circ}C$   
 WIRE RANGE: POWER: 1-6 mm<sup>2</sup> (18-10 AWG)  
 SIGNAL: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
 CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.  
 (ORDER No. REFER TO DRAWING:  
 T20200X10XX000 FOR SIGNAL; T20400X10XX000 FOR POWER)

M4 THREAD  
RECOMMENDED TIGHTENING TORQUE 1.2Nm4-M3 THREAD  
RECOMMENDED TIGHTENING TORQUE 0.5Nm







PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 电源: 690 V; 信号: 250 V  
 额定电流: 电源: 40 A; 信号: 10 A  
 绝缘电阻:  $\geq 400M\Omega$   
 额定脉冲电压: 电源: 8 KV; 信号: 4 KV  
 污染等级: 2  
 接触电阻: 电源:  $\leq 1 m\Omega$ ; 信号:  $\leq 5 m\Omega$   
 阻燃等级: UL94V-0  
 插拔次数: 500次  
 工作温度:  $-40+125^{\circ}C$   
 接线范围: 电源: 1-6 mm<sup>2</sup> (18-10 AWG)  
 信号: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
 接线类型: 冷压接

2. 端子需要单独订购。  
 (订货号参考图面: 信号端子: T20200X10XX000; 电源端子: T20400X10XX000)

T2120422101-000

HK6/36-042-M  
HK6/36-042 公插PART NUMBER  
料号PART DESCRIPTION  
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 22DEC2014

David Wang

CHK 22DEC2014

Chris Wang

APVD 22DEC2014

Xiang Xu

PRODUCT SPEC

108-137053

APPLICATION SPEC

114-137053

WEIGHT -

Customer Drawing

DIMENSIONS:  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±--
3 PLC	±-
4 PLC	±-
ANGLES	±-
FINISH	-

NAME

HK6/36-042-M

SIZE

A3

CAGE CODE

00779

DRAWING NO

T2120422101000

RESTRICTED TO

-

SCALE

1:1

SHEET

1 OF 1

REV

C

1470-19 (3/13)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heavy Duty Power Connectors](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)  
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#)  
[765-18-0080D](#) [829992-1](#) [902-77-02113](#) [PS00/A0620/6300](#) [PS25/A0420/63](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#)  
[MS3117-14AC](#) [1643543-1](#) [1650540-1](#) [1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-](#)  
[W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#)