

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

ITEM	DESCRIPTION	MATERIAL	OTHERS
1	FEMALE CONTACT	COPPER ALLOY	FLASH GOLD
2	HOUSING	NYLON	BLACK
3	COUPLING NUT	COPPER ALLOY	-
4	OVER-MOLDING	POLYURETHANE	BLUE
5	CABLE	-	-
6	LABEL	-	-

2

45°

PIN 2-WHITE

PIN 1-BROWN

PIN 3-BLUE

PIN 5-GRAY

PIN 4-BLACK

34.95 REF.

"L"±0.05M

50 REF.

35±5

29.05 REF.

SW13

6

1

NOTE:

1. STRIP AND RETAIN THE INSULATION

2. CODE POSITION

3. RECOMMENDED TORQUE 0.6 Nm

4. -*:CABLE LENGTH
-0.5:0.5M,
-1.0:1.0M,
-1.5:1.5M,
-3.0:3.0M,
-5.0:5.0M,
-7.0:7.0M,
-10.0:10.0M,

5. CABLE ASSEMBLY TO BE PACKAGED IN POLYBAGS

6. LABEL CONTAINS: PN, DATE CODE...

TECHNICAL DATA

	T41614X0002-00X	T41614X0003-00X	T41614X0004-00X	T41614X0005-00X
RATED VOLTAGE	250V		60V	
RATED IMPULSE VOLTAGE	2500V		1500V	
RATED CURRENT	4A			
POLLUTION DEGREE	3			
OVERVOLTAGE CATEGORY	II			
MATERIAL GROUP	II			
DEGREE OF PROTECTION	IP67			

PIN ARRANGEMENT
A-CODE

T41614X0002-00X	T41614X0003-00X	T41614X0004-00X
T41614X0005-00X		

WIRE COLOR: WH/BR/BK/BL/GR

OD: APPROX.4.5MM FOR 2P/3P

APPROX.5.0MM FOR 4P/5P

-001:0.5M

-002:1.0M

-003:1.5M

-004:3.0M

-005:5.0M

-006:7.0M

-007:10.0M

FIXED:
-40°C~+80°C

FLXIBLE:
-25°C~+80°C

FIXED:
-10°C~+80°C

FLXIBLE:
-5°C~+80°C

GRAY

BLACK

PUR
(UL)

PVC
(UL)

RPC-M12-FR-5CON-PUR-**SH4

RPC-M12-FR-4CON-PUR-**SH4

RPC-M12-FR-3CON-PUR-**SH4

RPC-M12-FR-2CON-PUR-**SH4

RPC-M12-FR-5CON-PVC-**SH4

RPC-M12-FR-4CON-PVC-**SH4

RPC-M12-FR-3CON-PVC-**SH4

RPC-M12-FR-2CON-PVC-**SH4

5

4

3

2

1

T4161420005-00X

T4161420004-00X

T4161420003-00X

T4161420002-00X

T4161410005-00X

T4161410004-00X

T4161410003-00X

T4161410002-00X

CABLE CHARACTERISTIC	LENGTH "L"	TEMPERATURE RANGE	JACKET COLOR	JACKET MATERIAL	TYPE	POS.	TE PN

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±-

2 PLC ±-

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH -

-

DWN HAO WANG 13APR2016

CHK KOBBY ZHAO 13APR2016

APVD XIANG XU 13APR2016

PRODUCT SPEC 108-106140

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

M12X1 RA RECEPTACLE, FREE END
A-CODE,
SHIELDED,

SIZE A2

CAGE CODE -

DRAWING NO. C-T41614X00XX00X

RESTRICTED TO -

SCALE 2:1

SHEET 1 OF 1

REV A

1471-9 (3/13)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sensor Cables / Actuator Cables](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

- [60963](#) [60964](#) [703000D02F2002](#) [703001D02F0602](#) [703001D02F300](#) [704000D02F120](#) [773032K02F030](#) [802027107404-1](#) [802027213811-1](#)
- [804001A09M150](#) [805001A09M0502](#) [84914-0235](#) [84914-0237](#) [885030A09M020](#) [1200651332](#) [1200651713](#) [1200660844](#) [1200660845](#)
- [1200661173](#) [1200680071](#) [1200720053](#) [1200720081](#) [1200720099](#) [1200720217](#) [1200800231](#) [1200860125](#) [1200870123](#) [1200980102](#)
- [1200650267](#) [1200650298](#) [1200660183](#) [1200660782](#) [1200660849](#) [1200661295](#) [1200661297](#) [1200661342](#) [1200661343](#) [1200670080](#)
- [1200670220](#) [1200680331](#) [1200720252](#) [1200730184](#) [1200860344](#) [1200870359](#) [1200870643](#) [1200980008](#) [1200980031](#) [1210502211](#)
- [1210400542](#) [1211810021](#)