

## VTM1ACD Product Details



### VTM1ACD

(6-1437481-0)

TE Internal Number: 6-1437481-0

 **Active**

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- VTM1 On-Delay Timing Module Series
- Input Voltage = 120 VAC
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O Solid State
- Contact Rating = 1A
- Mounting Options = Mounting Holes

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)
 [Request Sample](#)
 [Find Similar Products](#)
 [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Dimensional Drawing](#)
- [Wiring Diagram](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Termination Type = .250 x .032 Quick Connect Terminals

#### Electrical Characteristics:

- Input Voltage (VAC) = 120
- Contact Rating = 1A

#### Body Related Features:

- [Series](#) = VTM1 On-Delay Timing Module

#### Contact Related Features:

- Mounting Options = Mounting Holes
- Mode of Operation = On-Delay
- Delay Time = 0.5 seconds to 10 seconds
- Type of Control = External Resistor
- Repeatability, Max. = +1%
- Approved Standards = CSA Certified, UL Recognized
- Approx. Dimensions (L x W x H) (mm [in]) = 50.80 x 50.80 x 22.48 [2.001 x 2.001 x .885]

#### Configuration Related Features:

- [Contact Arrangement](#) = 1 Form A, SPST-NO, 1 N/O Solid State
- Multiple Timing Ranges = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- Temperature Range (?C) = -40 - +65

#### Other:

- Brand = Agastat

### Corporate Information

[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)

### Quick Links

[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)

### Customer Support

[Email or Chat with Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Time Delay & Timing Relays](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[5NO30](#) [614-11B-0A2](#) [614-11B-0A3](#) [614-11B-0A4](#) [614-11B-0A6](#) [614-11B-0A8](#) [614-11C-0A1](#) [614-11C-0A2](#) [614-11C-0A5](#) [614-11Q-0A3](#) [614-11Q-0A6](#) [614-11T-0A3](#) [614-11T-0A6](#) [614-11T-0A7](#) [614-12B-4A1](#) [614-12C-400](#) [614-12Q-400](#) [614-12T-600](#) [614-22T-4A1](#) [614-43B-400](#) [614-43C-100](#) [614-43F-200](#) [614-43Q-0A2](#) [614-43Q-100](#) [614-43Q-600](#) [614-43T-0A9](#) [614-43T-600](#) [614-43U-400](#) [614-43U-4A1](#) [614-43U-6A2](#) [615-21T-200](#) [655-11T-100](#) [655-11U-500](#) [655-12T-300](#) [655-22T-400](#) [655-22T-600](#) [CUA-41-30001](#) [CUA-41-30030](#) [CUA-41-70180](#) [CUA-41-71038](#) [CUA-42-30005](#) [CUA-42-30010](#) [CUA-42-30120](#) [CUA-42-70120](#) [CUA-99-72502](#) [CUC-41-30030](#) [CUF-42-30010](#) [CUH-41-31006](#) [7012AFX](#) [7012GD](#)