

# TESS WIRELESS SENSOR TAG DEMO V1.1

Standard 2.4GHz Wireless Communication Tag

Humidity: 0 - 100% RH

Temperature: -20°C to +85°C Pressure: 300 to 1,200mBar

iOS, Android™ and Windows® PC Compatible

The sensor tag demo V1.1 reports humidity, temperature and barometric pressure through a standard low power 2.4GHz wireless communication protocol.

It is based on the MEAS low power digital component sensor MS8607 for pressure, humidity and temperature (datasheet DA8607-02BA01).

The mobile application is available for free download using the Google Play™ Store for Android™ or the App Store for iOS. It will turn your smart phone or tablet into a display and datalog terminal. Refer to the WPC001 and WPC005 for installation guidelines and user manual

An optional USB dongle is available to connect the sensor tag to your personal laptop. Refer to the WPC002 for Windows® application installation.

The tag has been designed for an expected life time of 1 year on a standard CR2032 cell battery at one acquisition per second.

# **Applications**

- Smart building
- Smart home
- HVAC controller
- Maintenance
- · Smartphones and tablets accessories

# **BLE Services**

#### MS8607 Service

UUID	F000AAA0-0451-4000-B000-0000000000000

#### **AVAILABLE CHARACTERISTICS**

Name	UUID	Bytes	Read / Write	Notified
Data	F000AAC1-0451-4000-B000-000000000000	9	Read	YES
Calibration	F000AAC3-0451-4000-B000-000000000000	10	Read	NO
Status	F000AACF-0451-4000-B000-000000000000	1	Read	NO

#### DATA CHARACTERISTIC BYTES FIELDS

Byte 0	Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	
D1 MSB	D1	D1 LSB	D2 MSB	D2	D2LSB	Humidity Word MSB	Humidity Word LSB	Humidity CRC	

D1 and D2 are both 24 bits words.

#### CALIBRATION CHARACTERISTIC BYTES FIELDS

Byte 0	C1 MSB
Byte 1	C1 LSB
Byte 2	C2 MSB
Byte 3	C2 LSB
Byte 4	C3 MSB
Byte 5	C3 LSB

Byte 6	C4 MSB
Byte 7	C4 LSB
Byte 8	C5 MSB
Byte 9	C5 LSB
Byte 10	C6 MSB
Byte 11	C6 LSB

#### **CONVERSION**

 $dT = D2 - C5 \times 2^8$ 

TEMP =  $2000 + dT \times C6 / 2^{23}$ 

 $OFF = C2 \times 2^{17} + (C4x dT) / 2^{6}$ 

SENS = C1 x  $2^{16}$  + (C3 x dT)/  $2^{7}$ 

 $P = (D1 \times SENS / 2^{21} - OFF) / 2^{15}$ 

Temperature (°C) = TEMP / 100

Pressure (hPa) = P / 100

Humidity (%RH) = -6 + 125 x Humidity Word /  $2^{16}$ 

Please refer to MS8607 Sensor Datasheet for more information.

#### **STATUS**

0x00	OK
0x01	Sensor error

# **TESS WIRELESS SENSOR TAG DEMO V1.1**

# **Battery Service**

UUID	F000180F-0451-4000-B000-0000000000000

#### **AVAILABLE CHARACTERISTICS**

Name	UUID	Bytes	Read / Write	Notified
Data	F0002A19-0451-4000-B000-000000000000	2	Read	YES

#### DATA CHARACTERISTIC BYTES FIELDS

Byte 0	Byte 1
Battery Level (%)	Status


#### **CONVERSION**

0% to 100% represents a supply voltage from 2.0V to 3.0V with 1%/bit resolution.

#### **STATUS**

0x00	Discharging
0x01	Charging

## Dimensions (mm)





# Ordering Information

Description	Part Number	
BLE Sensor Tag Demo for use with free Android or iOS application.	WPP100B009	
BLE Sensor Tag Demo for use with USB dongle Key for Windows PC.	WPP109B009	

## Reference Material

◆ WPC001:

Android™ Application installation guidelines

◆ WPC002:

Windows® PC Software installation guidelines

◆ WPC005:

iOS Application installation guidelines

#### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company 1000 Lucas Way Hampton, VA 23666 USA Tel +1 757 766 1500 Fax +1 757 766 4297

#### **EUROPE**

Measurement Specialties (Europe), Ltd., a TE Connectivity Company 4 Rue Gaye Marie 31027 Toulouse, France Tel +33 (0) 582 082 200 Fax +33 (0) 582 082 151

#### **ASIA**

Measurement Specialties (China), Ltd., a TE Connectivity Company No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 518057 China

Tel +86 755 3330 5088 Fax +86 755 3330 5099

#### te.com/sensorsolutions

Android is a trademark of Google Inc. Google Play is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Android and Windows are trademarks of their respective owners.

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, MEAS, TE Connectivity, TE connectivity (logo) are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.

WPPC003 Rev 0

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Temperature Sensor Development Tools category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

EVAL-ADT7516EBZ EVAL-ADT75EBZ T20321SS2B T2016P2CRRXC4S2 MAX1455EVKIT-NS DC2507A DS18B20EVKIT#

MAX6654EVKIT EV-TEMPSENSE-ARDZ MAX1617AEVKIT BB-WSK-REF-2 MCP9800DM-TS1 TMPSNSRD-RTD2 MIKROE-2273

MIKROE-2501 MIKROE-2539 MIKROE-2554 DPP201Z000 DPP901Z000 1899 EV-BUNCH-WSN-2Z DPP904R000 KIT0021 SEN0206

SEN0227 MIKROE-2769 3251 SEN-13314 3263 SEN0137 LM20XEVM 3328 TMP708EVM BOOSTXL-TMP107 DC1785B MHUM-01

3538 DPP201G000 DFR0066 WPP100B009 SDT310LTC100A3850 SI7005EVB-UDP-M3L1 2857 1782 2652 269 3245 3622 3648

3721