

# DEUTSCH DMC-M 30-23 MODULES

# ACHIEVE HIGHER DENSITY WITH A REVERSE DESIGN OFFERING ENHANCED PIN PROTECTION

#### **ROBUST**

- Secured design ensuring blind mating
- Reverse design protects against pin damage
- Designed for use in EN4165, BACC65, and ARINC 809 shells
- Quadratic moment of sleeve on female contact is 8x higher than on male contact pin

#### **SAVE SPACE AND WEIGHT**

- Size 23 contacts allow 50% higher contact density than existing 20-22 modules—with the same level of performance
- 30% weight and space savings (versus 20-22 modules for a 60 contact arrangement)
- Enables size reduction to harness and other equipment
- Module with plastic clip design increases density, saves weight

#### **COMPATIBLE**

 Can be used with DEUTSCH DMC-M multimodule and single-module connectors and DUAL01 connectors TE Connectivity (TE) knows that the next generation of aircraft will have serious challenges in terms of weight and system installation time. The DEUTSCH 30-23 module is designed with our customers' expectations in mind.

## Smaller, Lighter, Better

Providing the highest density system in the smallest possible area is crucial in aircraft. The new 30-position modules provides a 50% increase in contact counts over existing 20-22 modules. Two 30-23 modules will provide the same 60-contact density as three 20-22 modules. This reduces the connector and harness sizes and weights.

## Eliminate Pin Damage

DMC-M high-density 30-23 modules solve the issue of fragile contact pins being bent upon blind mating. Designed for EN4165, BACC65, and ARINC 809 shells, these new reverse design modules contain the pin contacts inside the module to prevent the possibility of pin damage.

#### TE Components ... TE Technology ... TE Know-how ...

AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH SEACON Phoenix | L.L. Rowe | Phoenix Optix | SEACON

Get your product to market faster with a smarter, better solution.



# **DEUTSCH DMC-M 30-23 MODULES**

Reverse-Design High-Density Modules with New Pin Protection Design

#### **MATERIALS**

• Modules: Thermoplastic and fluorosilicone

Contacts: Gold-plated copper alloy

#### **ELECTRICAL**

• Withstanding Voltage: 1300 Vrms, 50 Hz

Insulation Resistance: ≥5000 MΩ

• Maximum Current: 5 A

• Conductor Range: 26, 24, and 22 AWG

#### **APPLICATION TOOLING**

Crimping Tool: M22520/2-01

Positioner:

Pin: M22520/2-09 Socket: M22520/2-06

Contact Insert/Extraction Tool:

M81969/14-01

**Module Insert/Extraction Tool:** 

057-0289-00 A

#### **APPLICATIONS**

- In-flight entertainment and cabin systems
- High-speed internet access
- · Lighting and window dimming
- · Power distribution and control
- Electrical wiring and interconnect systems

#### **PHYSICAL PROPERTIES**

• Operating Temperature: -55°C to +175°C

Weight:





For over 20 years, aircraft manufacturers have specified DEUTSCH DMC-M connectors for their reliability and compact size. The line continues to evolve to meet new requirements for RoHS-compliant tinning on PCB contacts for higher densities, higher speeds, different contact finishes, and even greater weight and space savings.



**20-22 Modules** Size 22 Contacts 3 Modules **30-23 Modules** Size 23 Contacts 2 Modules

Achieving 60 Contacts **30% Weight Savings** 

**DMC-M 30-23 PCB Extension Coming Soon** 

#### Part Numbers

Module	Contacts	Contact Part No.	Contacts Supplied with Connector	TE Part No.
Socket	Pin	182-4043-23	Yes	DMC-MR 30-23 P*
			No	DMC-MR 30-23 A*
Plug	Socket	182-4042-23	Yes	DMC-MR 30-23 S*
			No	DMC-MR 30-23 B*

<sup>\* =</sup> Keying (N (normal), A, B, C, D)

#### te.com/DMCM-30-23

© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved. 1-1773871-2 ADM/RRD 1.5M 01/2016

DEUTSCH, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other product or company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectangular MIL Spec Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

891-011-15SA2-BSST CTS-S16/16 65002-062 CY4602-000 732-8020-01 77058-22-55PN 81542-20 86.030.0053.0 1241346-1 RM252-020-311-2900 DMC-M 08-16 SA 1589051-4 MSO34MPK1E1 BACC65CAMA BACC65CP1PN BACI10BC0816PNBA HSB-D4S03DM222X 2217548-1 891-006-9PS-BST1T 891-009-15SA2-BRT1T 27963-20T12 SIM2N40NC3 SIM2S100A 1604996-2 SMD25PN90L-4055 1900ND08S1B00A 22628-10-6P-791 33526M11-08PD RE04-212S M32139/03-G05SN CTD160E01F-6148 CTJ112E03B CTJ122E02D-8000 CTJ-3D-12 CTJ920E06N-513 CTJ920E12N-513 CTL-16-090 RM300-000-581-0000 CY4600-000 CY4601-000 38111-14-15SN 38112-14-15PN MMA23-0111R1 MMD25-0071P1 33516062020 33526M11-08PE DMC-M99-01AN Y59113WE20PNV00300 ZPF0000000000106310 105979-31