

Model 2290-10-SHVUC

SHV Male to Unterminated Cable

Keithley Instruments, Inc. 28775 Aurora Road Cleveland, Ohio 44139 1-888-KEITHLEY http://www.keithley.com

Description

A WARNING

The Model 2290-10 can contain hazardous voltages. Be certain that the high voltage is completely discharged before removing or connecting the high-voltage cable. High-voltage cables can store charge if they are disconnected from the supply while high voltage is turned on and can cause personal injury or death if not handled properly. Do not connect the HIGH-VOLTAGE output to exposed circuitry. Any load connected to the HIGH-VOLTAGE output should be enclosed in a metal shield that is connected to safety earth ground using #18AWG or larger wire.

The high-voltage 10 kV SHV unterminated cable connects to the Model 2290-10 SHVBH female bulkhead connector (refer to document number 077084700 for more information).

High-voltage installation:

- 1. Turn off power and allow all voltage to discharge.
- 2. Install the Model 2290-5-SHVUC cable to the Model 2290-10 SHVBH female bulkhead connector (see next figure).



Figure 1: Model 2290-10 SHVUC male to unterminated cable

Electrical characteristics

Length	10 feet (3.05 meters)
Туре	RG-213/U coax cable
Maximum operating voltage (RMS)	10,000 volts

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Benchtop Power Supplies category:

Click to view products by Tektronix manufacturer:

Other Similar products are found below :

NL200 PR20 ZUPNC403 ZUP/W ZUPNC402 TL89F2 TL89F1 TL89T1 1332A-NIST AX-3003P AX-6003P AX-8450A TPM-3003 HMP2020 HMP2030 HMP4040 1350 UT804 1410 XLNRC 1513 1514 1550 1651A 1665 1666 1667 1693 1694 1698 MX100TP 1739 1762 1788 TPM-3005 1902B 9174B GDM-8245 GDM-8255A GDM-8341 PSP-603 PSW 160-7.2 QL355P SII HCS-3400-USB MX180T MX180TP 382276 1403 RK153 ENP-120-48