

High-impedance Buffer Amplifier System

TCA-1MEG Datasheet



Features & Benefits

- Bandwidth - DC to ≥ 500 MHz
- Input Impedance - $1\text{ M}\Omega / 10\text{ pF}$
- Bandwidth Limiting - Full/100 MHz/20 MHz
- Input Coupling - DC/AC/GND
- Includes P6139A, 500 MHz, 10x Passive Probe
- TekConnect Interface Delivers Superior Signal Fidelity, Unparalleled Versatility, and Ease-of-use

Applications

- Verification, Characterization, and Debug of Sophisticated Designs in Communications, Computer, and Semiconductor Electronic Environments
 - Jitter and Timing Analysis (Computer Systems)
 - Disk Drive Analysis
 - Investigation of Transient Phenomena
 - Spectral Analysis
 - Power Supplies/Inverters (Switching and Linear)
 - Semiconductor Devices (SCRs, IGBTs, FETs, CMOS)
 - Electronic Ballasts
 - Industrial/Consumer Electronics
 - Mobile Communications (Phone, Satellite, Relay Stations)
 - Motor Drives
 - Transportation Systems (Electronic Vehicles, Electric Trains, Locomotives, Avionics)

Tektronix award-winning TDS/CSA7000B DPO and TDS6000 Series oscilloscopes allow engineers to make high-speed measurements quickly and efficiently. In addition to these high-speed measurements, many of today's designers also face the challenges of measuring high-voltage, current, power, or even microvolt-level signals to gain a more complete understanding of their designs.

The TekConnect® family of amplifiers, probes, and adapters make it the ideal solution for such challenges, delivering a variety of acquisition capabilities through the use of existing compatible TekConnect and TEKPROBE™ measurement tools.

TekConnect® TCA-1MEG Buffer Amplifier System Expands the Functionality of Tektronix High-performance Oscilloscopes

The TCA-1MEG high-impedance buffer amplifier system extends the capabilities of Tektronix high-performance oscilloscopes, making them ideal for a variety of general-purpose measurements. The TCA-1MEG amplifier system provides a 1 MΩ path that is easily removed and replaced with a wide array of TekConnect probes, amplifiers, and adapters.

This amplifier system delivers versatility to Tektronix high-performance oscilloscopes through the addition of input coupling (selectable), bandwidth limit (selectable), and a 1 MΩ input that provides access to a wide array of measurement solutions. These solutions include general-purpose passive probes, high-voltage probes (passive single-ended and active differential), microvolt differential probes, and current probes.

With this tool, Tektronix high-performance oscilloscopes may now perform measurements such as primary and secondary power supply voltage levels, currents, and elevated voltages, and assess the power requirements of the device-under-test.

For today's high-speed measurement solutions, having the 50 Ω and 1 MΩ terminations on the same input path compromises signal fidelity. By making the 1 MΩ path replaceable, the TCA-1MEG high-impedance buffer amplifier system eliminates a permanent degradation of the high-speed signal path. This also allows users to easily and quickly configure each channel for the input characteristics required for their measurements. By exchanging the TCA-1MEG for a high-performance 50 Ω path or other high-speed probing solution, maximum signal fidelity is maintained at the oscilloscope's input.

TekConnect® Interface Delivers Superior Signal Fidelity, Unparalleled Versatility, and Ease-of-use

The TekConnect interface ensures superior signal fidelity with useful bandpass up to 18 GHz at the oscilloscope input, while offering unparalleled versatility with the world's widest array of accessory signal acquisition solutions for high-performance, real-time oscilloscopes. This interface delivers a more robust oscilloscope interface for next-generation products with multi-GHz analog bandwidths, overcoming many of the inherent bandwidth limitations of BNC-based interfaces. The TekConnect interface preserves a low-voltage standing wave ratio (VSWR) 50 Ω environment as well as a reliable electrical connection. A convenient, one-button release and locking mechanism provides quick, easy installation and removal of probes, amplifiers, and adapters.

Characteristics

Model Specifications

Characteristic	Description
Bandwidth (-3 dB)	DC to ≥500 MHz (host instrument bandwidth >1.5 GHz)
Probe Tip Bandwidth (with P6139A at -3 dB)	DC to ≥500 MHz (host instrument bandwidth >1.5 GHz)
BW Limit	Full, 100 MHz ±25%, 20 MHz ±25%
DC Gain Accuracy	±3% (TCA-1MEG with or without P6139A probe)*1
Propagation Delay (Input-to-Output)	<2 ns
Input Impedance	1 MΩ / 10 pF (at DC)
Maximum Input Voltage (Derated with Frequency)	150 V _{RMS} CAT I 100 V _{RMS} CAT II Above 200 kHz derate at 20 dB per decade; limit to 13 V _{pk} AC at 3 MHz and above

*1 Probe calibration required in TekConnect host instrument.

Typical

Characteristic	Description
Displayed System Input Offset	±0.2 div
Rise Time (calculated small signal $t_r = 0.4/F_{-3\text{dB}}$)	≤0.8 ns (minimum rise time)
Linear Dynamic Range	The lesser of ±5 divisions or the dynamic range of the TekConnect host instrument
Linearity	±0.2%

Nominal

Inputs – 1 (TEKPROBE™ BNC 1 MΩ).

Input Coupling – DC, AC, or GND.

Physical Characteristics

Dimensions	mm	in.
Length	180.08	4.255
Width	31.5	1.240
Height	46.1	1.815

Safety Certifications U.S. NRTL Listing – UL3111-1. UL3111-2-032.

Canadian Certification – CAN/CSA C22.2 No.1010.1. CAN/CSA C22.2 No.1010.2.032.

European Union Compliance – EN61010-1/A2. EN61010-2-032.

Other – IEC61010-1/A2. IEC61010-2-032.

GPIO Programmable – Through Host Instrument Commands.

Power Requirements – TekConnect.

Adapter Model Compatibility – Refer to TDS7000 Series TekConnect Adapters Compatibility Table.

Warranty – One year.

TekConnect® Amplifier, Adapters, and Probes Compatibility*2

Accessory Type	Oscilloscope			TekConnect Amplifiers, Adapters, and Probes				
	TDS6000B TDS/CSA7000B TekConnect Series			TCA-1MEG High-impedance Buffer Amplifier (P6139A Included)	TCA-BNC Adapter (Standard w/ TDS7154 / TDS7254 / CSA7154)	TCA-SMA Adapter (Standard w/ TDS7404 / CSA7404)	TCA-N Adapter	TCA75 Adapter
	6 GHz 8 GHz	4 GHz	1.5 GHz 2.5 GHz					
Instrument Input Connection	TekConnect Interface			TEKPROBE BNC 1 MΩ-to-TekConnect Interface	TEKPROBE BNC 50 Ω-to-TekConnect Interface	SMA-to-TekConnect Interface	N-to-TekConnect Interface	75-to-50 Ω TekConnect Adapter
Instrument Input Impedance	TekConnect Interface Probes, Amplifier and Adapter Dependent			1 MΩ / 10 pF	50 Ω	50 Ω	50 Ω	50 Ω
Passive Voltage Probes (1x)	P6101B w/ TCA-1MEG			P6101B	N/A	N/A	N/A	N/A
Passive Voltage Probes (10x)	P6139A w/ TCA-1MEG			P6139A	N/A	N/A	N/A	N/A
50 Ω Divider Voltage Probes	P6150 w/ TCA-SMA P6158 w/ TCA-BNC			N/A	P6158	P6150	N/A	N/A
Active Voltage Probes General	P6245 w/ TCA-BNC P6243 w/ TCA-BNC			N/A	P6245 P6243	N/A	N/A	N/A
Active Voltage Probes >2 GHz	P7260*3 P7240*3 P6249 w/ TCA-BNC P6241 w/ TCA-BNC			N/A	P6249 P6241	N/A	N/A	N/A
Differential Voltage Probes >2 GHz	P7380*3 P7380SMA*3 P7350*3 P7350SMA*3 P6330 w/ TCA-BNC	P7380*3 P7380SMA*3 P7350*3 P7350SMA*3 P7330*3 P6330 w/ TCA-BNC	P7350*3 P7350SMA*3 P7330*3 P6330 w/ TCA-BNC	N/A	P6330	N/A	N/A	N/A
Differential Voltage Probes <1.8 GHz <8 V Logic	P6248 w/ TCA-BNC P6247 w/ TCA-BNC P6246 w/ TCA-BNC			N/A	P6248 P6247 P6246	N/A	N/A	N/A
Differential Voltage Probes Microvolt	ADA400A w/ TCA-1MEG			ADA400A	N/A	N/A	N/A	N/A
High-voltage Probes Differential	P5205 w/ TCA-1MEG P5210 w/ TCA-1MEG			P5205 P5210	N/A	N/A	N/A	N/A
High-voltage Probes Single-ended	P5100 w/ TCA-1MEG P6015A w/ TCA-1MEG			P5100	N/A	N/A	N/A	N/A
Current Probe AC/DC <15 A	TCP202 w/ TCA-BNC			N/A	TCP202	N/A	N/A	N/A
Current Probe AC/DC 5 mA to 20 A	TCP300/TCP400/AM5030S w/ TCA-BNC or TCA-1MEG			TCP300 / TCP400 / AM5030S	TCP300 / TCP400 / AM5030S	N/A	N/A	N/A
Current Probe AC High Frequency	CT6 w/ TCA-BNC CT1 w/ TCA-BNC			N/A	CT6 CT1	N/A	N/A	
Current Probe AC Low Frequency	P6021 w/ TCA-1MEG P6022 w/ TCA-1MEG			P6021 P6022	N/A	N/A	N/A	
O/E Converter Probes	P6701B w/ TCA-BNC P6703B w/ TCA-BNC			N/A	P6701B P6703B	N/A	N/A	

*2 Firmware version 2.1 or greater required for all referenced oscilloscopes.

*3 P7225, P7240, P7260, P7330, P7350, P7350SMA, P7380, and P7380SMA are high-speed active and differential probing solutions for Tektronix oscilloscopes with TekConnect interface. These probes require no other adapters.

Please refer to TekConnect Adapters data sheet for more information about adapters.

ASEAN / Australasia (65) 6356 3900
 Austria 00800 2255 4835*
 Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
 Belgium 00800 2255 4835*
 Brazil +55 (11) 3759 7627
 Canada 1 800 833 9200
 Central East Europe and the Baltics +41 52 675 3777
 Central Europe & Greece +41 52 675 3777
 Denmark +45 80 88 1401
 Finland +41 52 675 3777
 France 00800 2255 4835*
 Germany 00800 2255 4835*
 Hong Kong 400 820 5835
 India 000 800 650 1835
 Italy 00800 2255 4835*
 Japan 81 (3) 6714 3010
 Luxembourg +41 52 675 3777
 Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
 Middle East, Asia, and North Africa +41 52 675 3777
 The Netherlands 00800 2255 4835*
 Norway 800 16098
 People's Republic of China 400 820 5835
 Poland +41 52 675 3777
 Portugal 80 08 12370
 Republic of Korea 001 800 8255 2835
 Russia & CIS +7 (495) 7484900
 South Africa +41 52 675 3777
 Spain 00800 2255 4835*
 Sweden 00800 2255 4835*
 Switzerland 00800 2255 4835*
 Taiwan 886 (2) 2722 9622
 United Kingdom & Ireland 00800 2255 4835*
 USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

Ordering Information

Service Options

- Opt. C3 – Calibration Service 3 Years.
- Opt. C5 – Calibration Service 5 Years.
- Opt. D1 – Calibration Data Report.
- Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).
- Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).
- Opt. R3 – Repair Service 3 Years.
- Opt. R5 – Repair Service 5 Years.
- Opt. SILV600 – Standard Warranty Extended to 5 Years.

Recommended Accessories

Passive Voltage Probes

- P6101B – 15 MHz, 1x, Passive.
- P6139A – 500 MHz, 10x, Passive.

High-voltage Probes

- P5205 – 1.3 kV_{RMS}, 100 MHz, Active Differential.
- P5210 – 4.4 kV_{RMS}, 50 MHz, Active Differential.
- P6015A – 20 kV, 1000x, 75 MHz, Passive.
- P5100 – 2.5 kV, 100x, 250 MHz, Passive.

Microvolt Differential Probe

- ADA400A – 1 MHz, 100x/10x/1x/0.1x, Microvolt Differential Preamplifier.

Current Measurement Tools

- AM503S – AC/DC, 5 mA to 700 A, Current Amplifier Measurement System. (Extended Current Capability by ordering additional Current Probes).
- P6021 – AC, 60 MHz, Current Probe.
- P6022 – AC, 120 MHz, Current Probe.

Cables and Terminations

- 012-0057-01 – 50 Ω BNC to BNC Coaxial Cable.
- 012-0482-00 – 50 Ω BNC to BNC Coaxial Cable, Precision 1%, Male-to-Male.
- 011-0049-02 – 50 Ω feed through termination.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

27 Jul 2012

60W-15629-3



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Benchtop Oscilloscopes](#) category:

Click to view products by [Tektronix](#) manufacturer:

Other Similar products are found below :

[MDO32 3-BW-1000](#) [TBS2102B](#) [TBS1072C](#) [TBS1102C](#) [TBS1202C](#) [DSO3064A](#) [DSO5102P](#) [CC-650](#) [GDS-2072A](#) [GDS-2074E](#) [GDS-2202E](#)
[GDS-2204E](#) [2555](#) [2557](#) [2568](#) [BK2190E](#) [HDO4024A](#) [2540C](#) [2542C](#) [2569-MSO](#) [2190E](#) [DSOX2002A/DSO0000-903](#) [GDS-2202A](#) [MDO-](#)
[2202EG](#) [MDO-2204EX](#) [HANTEK DSO4084B](#) [HANTEK DSO4084C](#) [HANTEK DSO4104B](#) [HANTEK DSO4104C](#) [HANTEK DSO4204B](#)
[HANTEK DSO4204C](#) [HANTEK DSO4254B](#) [DSO-2090](#) [DSO-2150](#) [DSO5062B](#) [RTB2K-202](#) [RTC1K-COM2](#) [UTD2025CL](#) [UTD2052CL](#)
[CC-65](#) [MSO5102D](#) [MSO5202D](#) [PICOSCOPE5444DMSO](#) [GDS-1054B](#) [GDS-1072B](#) [GDS-1074B](#) [GDS-1102B \(CE\) 2CH](#) [GDS-1104B](#)
[GDS-2072E](#) [GDS-2102E](#)