

| PART NUMBER | DESCRIPTION |
|-------------|--|
| CCRT-33S | Commercial Latching SPDT, DC-18GHz, Internal 50Ω Termination |
| CRT-33S | Elite Latching SPDT, DC-22GHz, Internal 50Ω Termination |

The CCRT-33S/CRT-33S is an internally terminated, broadband, SPDT, electromechanical coaxial switch designed to switch a microwave signal from a common input to either of two outputs. The characteristic impedance is 50 Ohms. Internal terminations provide an impedance match for the unselected port. The switches are small with the minimum spacing that is compatible with SMA connectors.



Available with USB & Ethernet Control!




| ENVIRONMENTAL AND PHYSICAL CHARACTERISTICS | |
|--|--------------------------|
| Operating Temperature | |
| Commercial Model, CCRT-33S | -25°C to 65°C |
| Elite Model, CRT-33S*** | -55°C to 85°C |
| Vibration (MIL-STD-202 Method 214, Condition D, non-operating) | 10 g's RMS |
| Shock (MIL-STD-202 Method 213, Condition D, non-operating) | 500 g's |
| Standard Actuator Life | 5,000,000 cycles |
| Actuator Life w/ Additional Features | 1,000,000 cycles |
| Connector Type | SMA |
| Humidity (Moisture Seal) | Available |
| Weight | 2.65 oz. (75.13g) (max.) |

| ELECTRICAL CHARACTERISTICS | |
|-----------------------------------|-------------------------|
| Form Factor | SPDT, break before make |
| Frequency Range | |
| CCRT-33S | DC–18 GHz |
| CRT-33S | DC–22 GHz |
| Characteristic Impedance | 50 Ohms |
| Terminations | 50Ω, 2 Watts CW max. |
| Operate Time | 10 ms (max.) |
| Release Time | 10 ms (max.) |
| Actuation Voltage Available | 12 15 24 28 V |
| Actuation Current, max. @ ambient | 420 350 280 200 mA |

| TYPICAL PERFORMANCE CHARACTERISTICS | | | | |
|-------------------------------------|----------|----------|-----------|-----------|
| Frequency | DC–6 GHz | 6–12 GHz | 12–18 GHz | 18–22 GHz |
| Insertion Loss, dB, max. | 0.2 | 0.4 | 0.5 | 0.6 |
| Isolation, dB, min. | 70 | 60 | 60 | 50 |
| VSWR, max. | 1.25:1 | 1.4:1 | 1.5:1 | 1.6:1 |

For maximum limits, please see charts on page 3-5

PART NUMBERING SYSTEM



Connector
S: SMA Female

Actuator Voltage
6: 28 Vdc Latching
7: 15 Vdc Latching
8: 12 Vdc Latching
9: 24 Vdc Latching

Actuator Type
0: Standard Contacts
C: Indicator Contacts***
D: Self Cutoff Only
E: Indicators and Self Cutoff***

***SEE PARTS LIST ON PAGE 8

Options
T: TTL Drivers with Diodes
D: Transient Suppression Diodes
R: Positive + Common
M: Moisture Seal
S: 9 Pin D-Sub Connector

For other options, contact factory.






*** Indicator Contacts Operating Temperature -50°C to 85°C (Elite Model Only)

Series CCRT-33S/CRT-33S

Internal 50Ω Termination DC-18 GHz/DC-22 GHz
Latching SPDT Coaxial Switch



SCHEMATICS AND MECHANICAL OUTLINE




“-S OPTION” 9-PIN D-SUB CONNECTOR (EXAMPLE: CCRT-33S60-S)

| 9 PIN D-SUB PINOUT FOR LATCHING SPDT | | | | |
|--------------------------------------|---------|------------|--------|------------------|
| Pin No. | OPTIONS | | | |
| | Basic | Indicators | TTL | Indicators & TTL |
| 1 | 1 | 1 | | |
| 2 | 2 | 2 | | |
| 3 | C | C | Common | Common |
| 4 | | | 1 | 1 |
| 5 | | | 2 | 2 |
| 6 | | | Vsw | Vsw |
| 7 | | A | | A |
| 8 | | B | | B |
| 9 | | C | | C |


| TRUTH TABLE (with TTL option) | | | | | |
|-------------------------------|---|---------------|---------|---------------------------|---|
| Logic Input | | RF Path | | Indicator (if applicable) | |
| 1 | 2 | IN to 1 | IN to 2 | A | B |
| 0 | 0 | No Change | | | |
| 1 | 0 | On Terminated | | C | 0 |
| 0 | 1 | Terminated On | | 0 | C |
| 1 | 1 | Forbidden | | | |

TYPICAL NARROWBAND RF INSERTION LOSS PERFORMANCE CURVES


Insertion Loss (DC-6 GHz)




Insertion Loss (6-12 GHz)




Insertion Loss (12-18 GHz)







Insertion Loss (18-22 GHz)




ELITE MODEL ONLY







TYPICAL NARROWBAND RF ISOLATION PERFORMANCE CURVES




ELITE MODEL ONLY



TYPICAL NARROWBAND RF VSWR PERFORMANCE CURVES




ELITE MODEL ONLY



TYPICAL POWER PERFORMANCE CURVE

Power Handling vs. Frequency



Estimates based on the following reference conditions:

- Ambient temperature of 40°C or less
- Sea level operation
- Load VSWR of 1.20:1 maximum
- No high-power (hot) switching

Please contact Teledyne Coax Switches for derating factors when applications do not meet the foregoing reference conditions.

GLOSSARY

Actuator

An actuator is the electromechanical mechanism that transfers the RF contacts from one position to another upon DC command.

Arc Suppression Diode

A diode is connected in parallel with the coil. This diode limits the “reverse EMF spike” generated when the coil de-energizes to 0.7 volts. The diode cathode is connected to the positive side of the coil and the anode is connected to the negative side.

Date Code

All switches are marked with either a unique serial number or a date code. Date codes are in accordance with MIL-STD-1285 Paragraph 5.2.5 and consist of four digits. The first two digits define the year and the last two digits define the week of the year (YYWW). Thus, 1032 identifies switches that passed through final inspection during the 32nd week of 2010.

Latching

A latching switch remains in the selected position whether or not voltage is maintained. This can be accomplished with either a magnetic or mechanical latching mechanism.

Indicator

Indicators tell the system which position the switch is in. Other names for indicators are telemetry contacts or tellback circuit. Indicators are usually a set of internally mounted DC contacts linked to the actuator. They can be wired to digital input lines, status lights, or interlocks. Unless otherwise specified, the maximum indicator contact rating is 30 Vdc, 50 mA, or 1.5 Watts into a resistive load.

Internal Termination

Unselected ports are internally terminated to a matched load. The load is 50Ω resistive device. The max RF power rating is 2 Watts CW. Without the internal termination option, the unselected ports are open circuits.

Isolation

Isolation is the measure of the power level at the output connector of an unconnected RF channel as referenced to the power at the input connector. It is specified in dB below the input power level.

Self-Cutoff

The self-cutoff option disables the actuator current on completion of actuation. Either a series contact (linked to the actuator) or an IC driver circuit provides the current cutoff. This option results in minimum power consumption by the RF switch. Cutthroat is another name used in the industry for this option. Pulse latching is a term used to describe a switch without this feature.

SPDT Switch

A single-pole double-throw, bi-directional switch that can be used as having one input and two outputs or two inputs and one output.

Switching Time

Switching time is the total interval beginning with the arrival of

the leading edge of the command pulse at the switch DC input and ending with the completion of the switch transfer, including contact bounce. It consists of three parts: (1) inductive delay in the coil, (2) transfer time of the physical movement of the contacts, and (3) the bounce time of the RF contacts.

TTL Switch Driver Option

As a special option, switch drivers can be provided for both failsafe and latching switches, which are compatible with industry-standard low-power Schottky TTL circuits.

Performance Parameters vs Frequency

Generally speaking, the RF performance of coaxial switches is frequency dependent. With increasing frequency, VSWR and insertion loss increase while isolation decreases. All data sheets specify these three parameters as “worst case” at the highest operating frequency. If the switch is to be used over a narrow frequency band, better performance can be achieved.

Actuator Current vs Temperature

The resistance of the actuator coil varies as a function of temperature. There is an inverse relationship between the operating temperature of the switch and the actuator drive current. For switches operating at 28 VDC, the approximate actuator drive current at temperature, T, can be calculated using the equation:

$$I_T = \frac{I_A}{[1 + .00385 (T-20)]}$$

Where:

I_T = Actuator current at temperature, T

I_A = Room temperature actuator current – see data sheet

T = Temperature of interest in °C

Magnetic Sensitivity

An electro-mechanical switch can be sensitive to ferrous materials and external magnetic fields. Neighboring ferrous materials should be permitted no closer than 0.5 inches and adjacent external magnetic fields should be limited to a flux density of less than 5 Gauss.

SPECIAL FEATURE

Switching High-Power or Highly Sensitive Signals

Ensure the most linear response with the best galvanically matched contact system in the industry. Extremely low passive intermodulation is standard on all of our switches.

| Carrier Frequency 1 | Carrier Frequency 2 | PIM 3rd Order Frequency | PIM 5th Order Frequency |
|---------------------|---------------------|-------------------------|-------------------------|
| 870 MHz | 893 MHz | 847 MHz | 824 MHz |

| | 3rd Order Intermodulation | 5th Order Intermodulation |
|------|---------------------------|---------------------------|
| SPDT | –91 dBm | –110 dBm |
| | –134 dBc | –153 dBc |

Series CCRT-33S/CRT-33S
 Internal 50Ω Termination DC-18 GHz/DC-22 GHz
 Latching SPDT Coaxial Switch



LATCHING CCRT-33S/CRT-33S PART NUMBER LIST

| | PART No. | | PART No. | | PART No. |
|----|-----------------|----|-----------------|-----|----------------|
| 1 | CCRT-33SXC | 43 | CCRT-33SX0 | 85 | CRT-33SXD-MS |
| 2 | CCRT-33SXC-D | 44 | CCRT-33SX0-D | 86 | CRT-33SXD-R |
| 3 | CCRT-33SXC-DM | 45 | CCRT-33SX0-DM | 87 | CRT-33SXD-RM |
| 4 | CCRT-33SXC-DMS | 46 | CCRT-33SX0-DMS | 88 | CRT-33SXD-RMS |
| 5 | CCRT-33SXC-DR | 47 | CCRT-33SX0-DR | 89 | CRT-33SXD-RS |
| 6 | CCRT-33SXC-DRM | 48 | CCRT-33SX0-DRM | 90 | CRT-33SXD-S |
| 7 | CCRT-33SXC-DRMS | 49 | CCRT-33SX0-DRMS | 91 | CRT-33SXD-T |
| 8 | CCRT-33SXC-DRS | 50 | CCRT-33SX0-DRS | 92 | CRT-33SXD-TM |
| 9 | CCRT-33SXC-DS | 51 | CCRT-33SX0-DS | 93 | CRT-33SXD-TMS |
| 10 | CCRT-33SXC-M | 52 | CCRT-33SX0-M | 94 | CRT-33SXE |
| 11 | CCRT-33SXC-MS | 53 | CCRT-33SX0-MS | 95 | CRT-33SXE-M |
| 12 | CCRT-33SXC-R | 54 | CCRT-33SX0-R | 96 | CRT-33SXE-MS |
| 13 | CCRT-33SXC-RM | 55 | CCRT-33SX0-RM | 97 | CRT-33SXE-R |
| 14 | CCRT-33SXC-RMS | 56 | CCRT-33SX0-RMS | 98 | CRT-33SXE-RM |
| 15 | CCRT-33SXC-RS | 57 | CCRT-33SX0-RS | 99 | CRT-33SXE-RMS |
| 16 | CCRT-33SXC-S | 58 | CCRT-33SX0-S | 100 | CRT-33SXE-RS |
| 17 | CCRT-33SXC-T | 59 | CCRT-33SX0-T | 101 | CRT-33SXE-S |
| 18 | CCRT-33SXC-TM | 60 | CCRT-33SX0-TM | 102 | CRT-33SXE-T |
| 19 | CCRT-33SXC-TMS | 61 | CCRT-33SX0-TMS | 103 | CRT-33SXE-TM |
| 20 | CCRT-33SXC-TS | 62 | CCRT-33SX0-TS | 104 | CRT-33SXE-TMS |
| 21 | CCRT-33SXD | 63 | CRT-33SXC | 105 | CRT-33SX0 |
| 22 | CCRT-33SXD-M | 64 | CRT-33SXC-D | 106 | CRT-33SX0-D |
| 23 | CCRT-33SXD-MS | 65 | CRT-33SXC-DM | 107 | CRT-33SX0-DM |
| 24 | CCRT-33SXD-R | 66 | CRT-33SXC-DMS | 108 | CRT-33SX0-DMS |
| 25 | CCRT-33SXD-RM | 67 | CRT-33SXC-DR | 109 | CRT-33SX0-DR |
| 26 | CCRT-33SXD-RMS | 68 | CRT-33SXC-DRM | 110 | CRT-33SX0-DRM |
| 27 | CCRT-33SXD-RS | 69 | CRT-33SXC-DRMS | 111 | CRT-33SX0-DRMS |
| 28 | CCRT-33SXD-S | 70 | CRT-33SXC-DRS | 112 | CRT-33SX0-DRS |
| 29 | CCRT-33SXD-T | 71 | CRT-33SXC-DS | 113 | CRT-33SX0-DS |
| 30 | CCRT-33SXD-TM | 72 | CRT-33SXC-M | 114 | CRT-33SX0-M |
| 31 | CCRT-33SXD-TMS | 73 | CRT-33SXC-MS | 115 | CRT-33SX0-MS |
| 32 | CCRT-33SXE | 74 | CRT-33SXC-R | 116 | CRT-33SX0-R |
| 33 | CCRT-33SXE-M | 75 | CRT-33SXC-RM | 117 | CRT-33SX0-RM |
| 34 | CCRT-33SXE-MS | 76 | CRT-33SXC-RMS | 118 | CRT-33SX0-RMS |
| 35 | CCRT-33SXE-R | 77 | CRT-33SXC-RS | 119 | CRT-33SX0-RS |
| 36 | CCRT-33SXE-RM | 78 | CRT-33SXC-S | 120 | CRT-33SX0-S |
| 37 | CCRT-33SXE-RMS | 79 | CRT-33SXC-T | 121 | CRT-33SX0-T |
| 38 | CCRT-33SXE-RS | 80 | CRT-33SXC-TM | 122 | CRT-33SX0-TM |
| 39 | CCRT-33SXE-S | 81 | CRT-33SXC-TMS | 123 | CRT-33SX0-TMS |
| 40 | CCRT-33SXE-T | 82 | CRT-33SXC-TS | 124 | CRT-33SX0-TS |
| 41 | CCRT-33SXE-TM | 83 | CRT-33SXD | | |
| 42 | CCRT-33SXE-TMS | 84 | CRT-33SXD-M | | |

* X = 6 (28Vdc), 7 (15Vdc), 8 (12Vdc) and 9 (24Vdc)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Teledyne manufacturer](#):

Other Similar products are found below :

[CR-38S33C-T](#) [611-13](#) [M28776/3-036L](#) [712DM2-12](#) [732DM-12](#) [EUM099-M265](#) [EUM139-M265](#) [FB512FSZ](#) [MOSD5050R200L](#)
[MOSFD5050R200L](#) [MOSFD5050R50H](#) [MOSFD5050R50L](#) [PK007-003](#) [PK007-019](#) [PK007-026](#) [PK007-027](#) [PK116-2](#) [PK116-3](#) [PK1-5MM-](#)
[102](#) [PK1-5MM-105](#) [PK1-5MM-120](#) [PK400-1](#) [PK702](#) [PKIT3-5MM-101](#) [PK-ZS-003](#) [PK-ZS-006](#) [PK-ZS-008](#) [PK-ZS-012](#) [PK-ZS-015](#) [PK-](#)
[ZS-021](#) [PK-ZS-022](#) [PK-ZS-024](#) [GEN500-16B-60](#) [DRDT600240A10](#) [MS-250](#) [E3PT48A12](#) [E3PT48A50H](#) [EFD113R-D70](#) [EFM099R-M79](#)
[EFM119-M160](#) [EFM411-M359*](#) [EFM759-M166*](#) [EFMT524-M159](#) [EFMT723-M159](#) [EFR1200480A150](#) [EFRD1200480R150](#)
[EFRTP600240R150](#) [EISC82-TD](#) [MSO-DLS-18](#) [ER114DM4-12A/Q](#)