

Quad Output DC Power Supply

4-in-1 Power Supply

Four power supplies built into one — Two fully adjustable supplies combined with two auxiliary outputs

Features:

- Two 0 to 30V/0 to 5A outputs with selectable Constant Voltage and Constant Current modes
- Outputs up to 60V in series mode or 10A in parallel mode
- Two auxiliary outputs with fixed current of 3 to 6.5V/3A and 8 to 15V/1A
- Overload and short circuit protection
- Complete with power cord and 4 pairs of test leads (banana plug to alligator clip)



Single power supply with multiple DC outputs

Specifications	Range
Output Voltage (4)	0 to 30V, 0 to 30V, 3 to 6.5V, 8 to 15V
Output Current (4)	0 to 5A, 0 to 5A, 3A (fixed), 1A (fixed)
Load Voltage Regulation	0.5mV ±3mV
Line Voltage Regulation	0.1mV ±3mV
Load Current Regulation	2mA ±5mA
Line Current Regulation	2mA ±3mA
Ripple and Noise	<0.5mVrms
Power	110 to 240VAC, 50/60Hz (Switchable)
Dimensions	10.2 x 6.3 x 14.5" (260 x 160 x 370mm)
Weight	26.5lbs (12kg)

Ordering Information:

382270Quad Output DC Power Supply

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Benchtop Power Supplies](#) category:

Click to view products by [Teledyne FLIR / Extech](#) manufacturer:

Other Similar products are found below :

[NL200](#) [PR20](#) [ZUPNC403](#) [ZUP/W](#) [Z60-7-L-U](#) [ZUPNC402](#) [TL89F2](#) [TL89K1](#) [TL89T1](#) [1332A-NIST](#) [CPX200DP](#) [AX-3003P](#) [AX-6003P](#)
[AX-8450A](#) [TPM-3003](#) [HMC8012](#) [HMP2020](#) [HMP2030](#) [HMP4040](#) [1350](#) [UT804](#) [1410](#) [XLNRC](#) [1513](#) [1514](#) [1550](#) [1651A](#) [1665](#) [1666](#) [1693](#)
[1694](#) [1698](#) [MX100TP](#) [1739](#) [1762](#) [1788](#) [TPM-3005](#) [1902B](#) [9174B](#) [GDM-8245](#) [GDM-8255A](#) [GDM-8341](#) [PSP-603](#) [PSW 160-7.2](#) [QL355P](#)
[SII](#) [HCS-3400-USB](#) [MX180T](#) [MX180TP](#) [382276](#) [1403](#)