

BR250-5 Video Borescope/Wireless Inspection Camera



Extech's Video Borescope with a 5.2 mm diameter camera probe makes it possible to inspect hard to access areas through a small opening. It provides a glare-free close-up field of view. A color wireless monitor is included and can be detached from the base and viewed from a remote location up to 32 ft (9.75 m) away. Capture images/videos with date/time stamp and play back on the monitor or viewed on a PC.

Applications:

- HVAC (inspect inside ducts, behind motors/compressors)
- Home inspection (mold, electrical wires, or pipes in walls)
- Automotive (view inside or around engines and transmissions)



Features

- Detachable wireless 3.5" (89 mm) TFT LCD color monitor can be viewed from a remote location up to 32 ft (10 m) from the borescope
 - 16 GB microSD memory card (with included SD adaptor) for storing images (JPEG) and videos (AVI) with date/time stamp that can be played back on the wireless monitor or transferred to a PC
 - Mini waterproof (IP67) 5.2 mm diameter camera probe with 39" (1 m) gooseneck cable retains configured shape
 - Built-in six bright LED lamps with dimmer function to illuminate viewed object
 - Glare-free close-up field of view
 - Magnetic mount conveniently holds the monitor in a remote area for viewing
 - Easy-to-navigate menu in 10 languages
 - Video output for connecting additional monitor
- Complete with 5.2 mm camera probe (BR-5CAM-A), probe tools (mirror, hook, magnet, and fixture), 4 AA batteries, rechargeable display battery, microSD memory card with SD adaptor, USB cable, video cable, Universal adaptor with multi-plugs (US, EU, UK, AUS), magnetic base stand, and hard case

Specifications and Ordering information next page



BR250-5 UPC Code: 793950633557
BR-5CAM-A UPC Code: 793950635506

Specifications

Camera Probe and Handle

Pixels	640 x 480 (NTSC)
Transmission frequency	2.4 GHz
Transmission range	32 ft (10 m) unobstructed view
Viewing direction	Viewing Angle 48°
Focus distance from object	~1.2" to 3.1" (3 to 8 cm)
Shaft diameter	5.2 mm
Camera probe cable length	39" (1 m)
Minimum bend radius	2.36" (60 mm)
Handle dimensions	7.3 x 5.7 x 1.6" (186 x 145 x 41 mm)
Weight	13.4 oz (381 g)

Monitor

LCD Screen Type	3.5" TFT
Pixels	320 x 240
Video Output Level	0.9 to 1.3 V @75 Ω
Frame Rate	5, 10, 15, 20, 25, 30 FPS
Video Resolution	640 x 480 (avi format)
Image Resolution	640 x 480 (jpeg format)
Languages	English, Chinese, German, French, Spanish, Portuguese, Italian, Japanese, Dutch, and Russian
Monitor Dimensions	4 x 2.8 x 1" (101.5 x 70.5 x 25 mm)
Operating/Charge Time	1.5 hours/3 hours
Weight	4.6 oz (130 g)

Ordering

BR250-5 Video Borescope/Wireless Inspection Camera (5.2 mm diameter Camera Head Probe w/1 m Cable)

BR-5CAM-A Replacement 5.2 mm Borescope Camera Head Probe with 1 m Cable

Optional Accessories for BR250

BR-9CAM 9 mm Borescope Camera Head Probe with 1 m Cable

BR-9CAM-5M 9 mm Borescope Camera Head Probe with 5 m Cable

UA100-BR Universal AC Adaptor (100-240 Vm 50/60 Hz) for BR250

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Teledyne FLIR / Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [2837806](#) [4328074](#) [4366444](#) [S-11](#) [382153](#) [700PTP-1](#) [GEO-](#)
[CABLE-REEL-50M](#) [H115](#) [H300](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-H2S-100](#) [AW-NmHc-100](#) [ES1-CO-1000-01](#) [P 2801](#) [P 2802](#) [TM-197](#)
[ULD-420-EUR](#) [TM-192](#) [TM-192D](#) [TM-305U](#) [UT309C](#) [EL-P-TC-T-SURFACE](#) [1500000059](#) [HS115](#) [MR59](#) [12227021](#) [13123602](#) [13123661](#)
[12255930](#) [12983030](#) [30171091](#) [30198712](#) [30198755](#) [30209323](#) [12228657](#) [12229067](#) [12230090](#) [7358958](#) [12231398](#) [12231487](#) [7390674](#)
[7390682](#) [12231550](#)