EXTECH ®

CLT600 Advanced Cable Locator and Tracer Kit

The CLT600 is a reliable, easy-to-use tool for detecting electrical power cables, telecommunication cables, and wires in building applications. Featuring non-contact voltage technology, worklights, and an ergonomic design, professionals can safely and efficiently locate hidden wires and cables. Combining premium features including coded signals and sound and visual indications, the CLT600 is a complete solution for field troubleshooting, wiring diagnostics, and verification of electrical installations.

Features

- Trace powered and unpowered wires and cables in walls, ceilings, and floors
- Identify location of breaks in cables and wires
- Detect and locate hidden cables and wires in walls
- Avoid touching live wires with non-contact voltage detection technology
- Measure AC/DC voltage to 450 V and verify if a wire is energized
- Inspect safely with CAT III-450 V safety rating
- Identify related fuses or breakers on panels
- Set up automatic or manual signal detection
- Discover signal strength on LCD screen bar display and by sound indication
- Use mute mode in quiet locations
- Work efficiently in dark areas with backlit LCD screens and worklights
- Increase precision with coded transmission option

- Optional UK and EU socket adapters available (see ordering section)
- Complete with cable locator transmitter, cable locator receiver, instruction guide, 2 test leads, 2 alligator clips, grounding rod/spike, 12 batteries, socket adapter with North American 3-pin Type-B plug, and hard carrying case

See next page for product specifications and ordering information

EN 61010-1 CAT III 450V CE

CLT600 UPC Code: 793950660010
CLT-ADP-US UPC Code: 793950660027
CLT-ADP-EU UPC Code: 793950660034
CLT-ADP-UK UPC Code: 793950660041
GR15 UPC Code: 793950383032
CLT-TL UPC Code: 793950660058

www.extech.com

Transmitter Specifications

Output signal frequency	125 kHz
Voltage measurement range and accuracy	12 to 450 V AC / DC, ±(2% rdg + 2 digits)
Display	LCD shows function, voltage, bargraph and battery status
Power source	1.5 V (AAA) battery × 6
Fuse	690 V / 0.5 A
Dimensions	7.40 × 3.54 × 1.85 in (188 × 90 × 47 mm)
Weight (batteries included)	Approx. 0.86 lbs (389 g)

Receiver Specifications

Maximum detection depth	Level 3: ~19.7 in (50 cm) Level 2: ~11.9 in (30 cm) Level 1: ~4 in (10 cm)
Display	LCD shows function, signal strength bargraph, NCV (UAC) battery status warning
Power source	1.5 V (AAA) battery × 6
Dimensions	9.72 × 3.07 × 1.77 in (247 × 78 × 45 mm)
Weight (batteries included)	Approx. 0.72 lbs (324 g)

Kit Weight and Dimensions

Weight	Approx. 5.51 lbs (2500 g)
Hard case dimensions	16.34 × 11.77 × 3.54 in (41.5 × 29.9 × 9 cm)

Ordering

CLT600 .... Cable Locator and Tracer Kit

Optional Accessories:
CLT-ADP-US ..... Socket Adapter with North American 3-pin Type B Plug
CLT-ADP-EU...... Socket Adapter with European 2-pin Type C Plug
CLT-ADP-UK ..... Socket Adapter with UK 3-pin Type G Plug
GR15 .... Set of 2 Grounding rods
CLT-TL............... Set of 2 Test Leads and 2 Alligator Clips for CLT600
(Note: This product is supplied with a US Socket Adapter. Socket Adapters for Europe
(CLT-ADP-EU) and UK (CLT-ADP-UK) are available separately.)

www.extech.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LAN/Telecom/Cable Testing *category:*

Click to view products by Teledyne FLIR / Extech *manufacturer:*

Other Similar products are found below :

1673606-1 SEFRAM95 KE8000 POECHECK TCT-1620 TCT-2210 TCT-680 TCT-2690PRO TESTER-MS6811 TESTER-MS6812 262 N044-000-R MCT-468 TM-901N TM-902 TM-903 LAN-1 24-517 CT20 40180 TG20 CLM-1000E CLM-1000 HDMI-100 TEP-100 KE3100 KE3150 KE501 KE850 VDV501-851 LC-90 P 3434 SEFRAM96 UT681C UT682D UT681HDMI UT681L UT682 UTP05 VTLAN6 VTTEST11 VTTEST11N PA901066 VDV526-052 VDV501-826 VDV501-815 VDV501-829 VDV500-060 MS-POE MS-POE-KIT