



IGM technology guides you where to measure



Verify amperage measurements

# FLIR CM174

Imaging 600A AC/DC Clamp Meter with IGM™

The FLIR CM174 Imaging 600A AC/DC Clamp Meter with IGM is the first clamp meter equipped with a built-in thermal imager that can quickly lead you to problems you can't see with a standard clamp meter. Featuring Infrared Guided Measurement (IGM) technology, the CM174 visually guides you to the precise location of a potential electrical problem, identifying dangerous and unknown problem areas safely. Confirm your findings with accurate amperage and voltage measurements, and center-point temperature readings. The narrow jaw enables greater accessibility, and its compact form-factor fits easily into your back pocket - so you can have thermal imaging at your fingertips everywhere you go. The FLIR CM174 will quickly become your primary electrical troubleshooting tool.

#### Find problems faster with IGM.

Visually identify electrical issues with the first thermal imaging clamp meter

- Conquer cluttered wires and cables IGM can quickly guide you in the right direction
- All-in-one tool carry just one device and always have access to thermal imaging
- Work safely scan a panel or cabinet for hazards using IGM without direct contact

### **Confirm your findings.**

Verify problems, check load, and validate hot spots

- Center-point temperature to confirm hot spot
- Amperage and voltage measurements to check the load
- Laser and crosshair pinpoint the location of the problem found in thermal image

#### Solve complex electrical issues.

Design and functionality vital to professionals

- Narrow jaw and built-in worklights help you access difficult locations with lighting issues
- Advanced electrical features: True RMS, LoZ, VFD Mode, Inrush, Smart Diode with Disable
- Expandable to 3000 Amps AC with FLIR flex accessories



## **Specifications**

FLIR CM174: Imaging Clamp Me Imaging Detector		FLIR Lepton <sup>®</sup> microbolometer		
Thermal Image Resolution		4800 pixels (60 × 80)		
Field of View (V x H)	38.6° x 50.0°			
Color Palettes	Iron, Rainbow, Grayscale			
Image Frame Rate	9Hz			
Temperature Measurement	Center point of thermal image			
Temperature Range	-10°C to 150°C (-14°F to 302°F)			
Temperature Distance to Spot Ratio	30:1			
Temperature Accuracy	± 3°C (5.4°F) or ±3% of rdg			
Spectral Response	8 to 14µm			
Temperature Targeting	Class 1 Laser Pointer	Class 1 Laser Pointer and Crosshair on display		
Emissivity Settings	4 Presets with 0	4 Presets with Custom Adjustment		
Electrical Measurements	Range	Basic Accuracy		
AC/DC Voltage	1000V	±1.0%		
VFD AC Voltage	1000V	±1.0%		
LoZ Mode AC Voltage	1000V	±1.0%		
LoZ Mode DC Voltage	1000V	±1.0%		
DC Current	600.0A	±2.0%		
AC Current	600.0A	±2.0%		
VFD AC Current	600.0A	±2.0%		
Inrush AC Current	600.0A	±3.0%		
Inrush AC Current Threshold	Min 0.5A Integration Time 100ms			
Frequency	60.00kHz	±0.1%		
Resistance	6000Ω	±1.0%		
Continuity	600.0Ω	±1.0%		
Capacitance	1000µF	±1.0%		
Diode	1.5V	±1.5%		
General information				
Display	6000 Count 2.0" (50mm) Color TFT			
Jaw Opening	1.38" (35mm), 1250MCM			
Category Rating	CAT IV-600V, CAT III-1000V			
Certifications	UL, CE			
Battery Type	4 x AAA			
Warranty	10 Years on Proc	10 Years on Product and Detector*		
Includes	Clamp Meter, 4 x AAA Batteries, Premium Silicone Test Leads Quick Start, User Manual (CD), Extended Warranty Registration Card			







-Test Leads Input

Ordering Information	UPC	EAN
FLIR CM174 Imaging 600A AC/DC Clamp Meter with IGM™	793950371749	0793950371749
FLIR TA72 Universal Flex Current Probe Accessory 10"(25cm)	793950377727	0793950377727
FLIR TA74 Universal Flex Current Probe Accessory 18"(45cm)	793950377741	0793950377741
FLIR TA15 Soft Sided Carrying Case	793950377154	0793950377154
FLIR TA55 Line Splitter	793950377550	0793950377550
FLIR TA52 Magnet Mount	793950377529	0793950377529
FLIR TA42 Belt Clip	793950374207	0793950374207
FLIR TA80 Premium Silicone Test Leads	793950377802	0793950377802
FLIR TA70 Alligator Clips	793950377703	0793950377703



#### USA-NASHUA

EUROPE

FLIR Systems

www.flir.com

NASDAQ: FLIR

Luxemburgstraat 2 2321 Meer Belgium PH : +32 (0) 3665 5100

FLIR Systems, Inc. 9 Townsend West Nashua, NH 03063 USA PH: +1 866.477.3687 USA-PORTLAND Corporate Headquarters FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070 USA PH: +1 866.477.3687

#### UNITED KINGDOM

FLIR Systems UK 2 Kings Hill Av. - Kings Hill West Malling Kent ME19 4AQ United Kingdom Tel. : +44 (0)1732 220 011 Fax : +44 (0)1732 843 707 E-mail : flir@flir.com

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2015 FLIR Systems, Inc. All rights reserved. (Updated 08/24/17)



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Clamp Multimeters & Accessories category:

Click to view products by Teledyne FLIR / Extech manufacturer:

Other Similar products are found below :

 I800
 MT-8006B
 3PK-NT023N
 MT-7057N
 TESTO 770-3
 0590
 7703
 AX-3550
 AX-M266C
 BM079
 BM089
 BM162
 BM197
 KEW2210R

 FLUKE 80I-110S
 FLUKE A3002FC
 FLUKE I200
 FLUKE I310S
 TESTO 770-2
 0590
 7702
 KEW2433R
 KEW8112
 FLUKE 772
 ACDC 

 100
 MA440
 MA443
 MA445
 FLUKE-374 FC
 FLUKE-1630-2FC
 CM42
 FLUKE-376 FC
 A193 (800 MM)
 F201
 F205
 F65
 DIGIFLEX

 4000A 350MM
 DIGIFLEX 400A 170MM
 DIGIFLEX 400A 250MM
 MN93A
 FLUKE 16000SFLEX-24
 KEW2010
 P1670
 FLK-A3004FC

 AMP-330-EUR
 APPA SFLEX-18D
 UT200A
 UT205
 UT205A
 UT206A
 UT210A
 UT210B