

CO30 Carbon Monoxide CO) Monitor



The Extech CO30 displays Carbon Monoxide (CO) concentration, Air Temperature, and Relative Humidity. Programmable audible alarm, with high decibel beeper, sounds when CO concentration rises to unsafe levels. Can be wall mounted or used on a desktop close to areas of concern.



- Office buildings and conference rooms
- Boats, planes, and RVs
- Indoor work places such as warehouses that use propane- and gasoline-powered fork lifts
- Manufacturing plants of temporary heating units and gasoline-powered appliances

Features

- Alternately displays Carbon Monoxide (CO) concentration, Air Temperature, and Relative Humidity readings (cycles approximately every 6 seconds)
- Visible bright tri-colored LED indicator: Green <10ppm, Yellow = 10 to 29ppm, and Red >30ppm
- · LCD displays alarm icon, LED light turns red, and loud audible beeper sounds when indoor CO level exceeds set point (defaults at 30ppm - adjustable); beeper can be temporarily turned off for false alarm
- · Adjustable audible alarm sounds when reading exceeds one of the selected ranges: 25ppm, 30ppm, 35ppm, 50ppm, 100ppm or 200ppm
- "ZERO" Re-Calibration function

- Manual Temperature and Relative Humidity Compensation (adjustable)
- · CO Calibration function in fresh air
- · Four display error codes for troubleshooting
- · Low battery indicator
- · Recover to factory setting function
- · Complete with built-in stand, side cover, Universal AC Adaptor (multi-plugs US, EU, UK, and AU), and 4 AAA batteries

EXTECH

•	<10ppm	Normal
	=10 to 29ppm	Caution
	>30ppm	Danger

Bright Tri-colored LED Indicator for CO Level

Specifications	Range	Resolution	Basic Accuracy	
Carbon Monoxide (CO)	0 to 999ppm	1ppm	±5% of reading or ±10ppm	
Temperature (Air)	32 to 122°F (0 to 50°C)	0.1°F/°C	±2°F/1°C	
Relative Humidity	20 to 90%RH	1%RH	±5%RH @ 25°C	
Dimensions/ Weight	4.4x4.3x2.1" (113x108x53mm)/	4.4x4.3x2.1" (113x108x53mm)/ 5.6oz (159g)		

Ordering

CO30 Carbon Monoxide CO Monitor

NOTE: The CO30 Carbon Monoxide Monitor is intended for general purpose Air Quality monitoring only, and has not been certified for use pursuant to any state or city safety Carbon Monoxide Alarm or Monitoring requirements

The CO30 Carbon Monoxide Monitor has not been tested by an independent lab to comply with UL 2034 or IAS 6-96 standard.

It is the responsibility of the customer to obtain and apply current local, state, and national regulations with regard to CO alarms, monitoring and testing.

UPC Code: 793950500309

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Air Quality Sensors category:

Click to view products by Teledyne FLIR / Extech manufacturer:

Other Similar products are found below:

GMS-MSTH2.S.V.3 MO86571 MO86561 076074 01 DE800.A.1 MF010-2-LC1 MF020-2-LC3 KGZ10-5PIN GMS10SENSORS IR25TT 208280-0001 IR11BD IR11GM IR12GM IR21BD GMS10-18C KGZ12 S-300L-3V-5000-SLEEP-UART MP7227-TC SGPC3-TR-2.5KS T6713-6H POLOLU-1482 3.000.475 3.000.496 HPMA115S0-XXX SGPC3-2.5k T3032-2-10K-24-P VQ6MB INIR-CD-5% VQ23TB IR11GJ VQ31MB IR11BR GP2Y1026AU0F VQ549ZD MHM501-00 MHM500-00A MHM305-01 MICS-4514 VQ548ZD-S SEN-09403 IR15TT MICS-5524 MICS-5914 MICS-2714 INIR-ME-100% T8100-D VQ21TB IR21EJ VQ603/2