



IMAGING TRMS MULTIMETER

FLIR DM166™

The FLIR DM166 is the most affordable multimeter with built-in thermal imaging – a must-have tool for commercial electricians, automation, electronics, and HVAC technicians. Featuring Infrared Guided Measurement (IGM™) powered by an 80 x 60 FLIR thermal imager, the DM166 visually guides you to the precise location of temperature anomalies and potential problems faster, more safely, and efficiently. The feature-packed multimeter is an ideal tool for troubleshooting and diagnosing complex issues in both high-voltage and low-voltage applications.

www.flir.com/professionalDMMs



TROUBLESHOOT FASTER

One tool gets the job done

- Quickly scan for overheating components with IGM
- Diagnose faults with broad DMM test functions
- Troubleshoot easier with the unique combination of onboard thermal imaging and traditional DMM test functions



WORK SAFER

Identify energized and potentially faulty equipment from a safe distance

- Safely check for live connections using non-contact temperature measurement
- Carefully measure voltage with integrated non-contact voltage detection
- Work with peace of mind knowing your meter has a CAT III-600V, CAT IV-300V safety rating



DIAGNOSE PROBLEMS MORE EFFICIENTLY

Rich feature set covers both high-voltage and low-voltage applications

- Reliably take 600 V AC/DC voltage measurements and 10 A AC/DC current measurements
- Remove high-frequency noise that affects readings with the Variable Frequency Drive (VFD) measurement function
- Precisely measure resistance up to 60 MΩ, frequency up to 50 KHz, and capacitance up to 10,000 μF

SPECIFICATIONS

| Thermal Imaging | | DM166 | |
|--|--|---|--|
| IR Resolution | 80 x 60 pixels (4,800 pixels) | | |
| Thermal Imaging Detector | FLIR Lepton® microbolometer | | |
| Temperature Sensitivity | ≤ 150 mK | | |
| Emissivity Settings | 4 presets with custom adjustment | | |
| Temperature Accuracy | 3°C or 3% | | |
| Temperature Range | 14° F to 302°F (-10C to 150° C) | | |
| Field of View | 50° x 38° | | |
| Laser Pointer | Yes | | |
| Focus | Fixed | | |
| Thermal Imaging Palette | Iron, Rainbow, Grayscale | | |
| Level & Span | Auto | | |
| Measurements | | | |
| True RMS | Yes | | |
| | Range | Basic Accuracy | |
| AC / DC Volts | 600.0 V | ±0.7% / 0.5% | |
| AC / DC mVolt | 600.0 mV | ±1% / 0.3% | |
| VFD AC Volts | 600.0 V | ±1.0% | |
| AC / DC Amps | 10.00 A | ±1.0% / 0.7% | |
| AC / DC mAmps | 600.0 mA | ±1.0% / 0.7% | |
| AC / DC μAmps | 6000 μA | ±1.5% / 1.0% | |
| Resistance | 6.000 MΩ | ±0.9% | |
| | 60.00 MΩ | ±1.5% | |
| Capacitance | 2.000 mF | ±2.0% | |
| | 10.00 mF | ±5.0% | |
| Diode Test | 3.000 V | ±0.9% | |
| Frequency Counter | 50.00 kHz | ±0.3% | |
| Temperature, Type-K Thermocouple | -40°F to 752.0°F | ±1.0% + 3°F | |
| | -40°C to 400°C | ±1.0% + 1.5°C | |
| Additional Measurements | | DM166 | |
| Continuity Check | 30 Ω and 480 Ω | | |
| Measuring rate | 5 samples per second | | |
| General Information | | | |
| Auto Power Off | Yes | | |
| Display Size | 2.4 in TFT screen | | |
| Battery | 3 AA batteries; optional TA04 Li-Poly rechargeable battery | | |
| Drop Test | 3 m | | |
| IP Rating | IP40 | | |
| Safety Category Rating | CAT III-600V, CAT IV-300V | | |
| Size (L x W x H) | 190 × 86.4 × 48.3 mm (7.5 × 3.4 × 1.9 in) | | |
| Weight | 428.3 g (15.1 oz) | | |
| Warranty | 10 year on product and detector | | |
| Box Contents | | DM166, L91 lithium batteries, silicone test leads, soft carrying case | |
| Ordering Information | | Order # | |
| FLIR DM166 Thermal Imaging TRMS Multimeter with IGM | | 793950391662 | |
| For a complete list of available accessories, go to: flir.com/store/instruments/testaccessories | | | |

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.flir.com

CORPORATE HEADQUARTERS
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 7080

CANADA
FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5K6
Canada
PH: +1 800.613.0507

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 09/22/17

17-2458-INS-TAM



The World's Sixth Sense®

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Teledyne FLIR / Extech](#) manufacturer:

Other Similar products are found below :

[I800](#) [MT-8006B](#) [3PK-NT023N](#) [MT-7057N](#) [TESTO 770-3 0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM162](#) [BM197](#) [KEW2210R](#)
[FLUKE 80I-110S](#) [FLUKE A3002FC](#) [FLUKE I200](#) [FLUKE I310S](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [ACDC-100](#) [MA440](#) [MA443](#)
[MA445](#) [FLUKE-374 FC](#) [FLUKE-1630-2FC](#) [CM42](#) [FLUKE-376 FC](#) [A193 \(800 MM\)](#) [F201](#) [F205](#) [F65](#) [DIGIFLEX 4000A 350MM](#)
[DIGIFLEX 400A 170MM](#) [DIGIFLEX 400A 250MM](#) [MN93A](#) [FLUKE I6000SFLEX-24](#) [KEW2010](#) [P1670](#) [FLK-A3004FC](#) [AMP-330-EUR](#)
[APPA SFLEX-18D](#) [UT200A](#) [UT201](#) [UT205](#) [UT205A](#) [UT206](#) [UT206A](#) [UT210A](#) [UT210B](#) [UT213A](#)