

LT510 Light Meter



Measures light intensity up to 1860 Foot-candles (20,000 Lux) with resolution to 0.1 Fc/1Lux. Ideal for indoor lighting tests and for checking security and safety illumination in parking garages, night time ATM areas, stairwells, landings, and hallways.

Applications:

- Buildings
- Banks/ATMs
- Parking lots
- Arenas
- Hospitals
- Photography
- and more!



Features

- Measure light levels in Foot-Candle (Fc) or Lux units using a precision photo diode with cosine and color correction filter
- Zero function
- Backlit LCD to view in dimly lit areas
- Data Hold and Min/Max functions
- Auto power off with disable
- Tripod mount (optional TR100 Tripod sold separately)
- Complete with light sensor cover, wrist strap, and three AAA batteries

Specifications	Range	Max Resolution	Basic Accuracy
Foot-Candle (Fc)	0 to 1860Fc	0.1Fc	±5%rdg
Lux	0 to 20,000Lux	1Lux	±5%rdg
Dimensions	5.5x1.8x1.2" (141x45x20mm)		
Weight	5.6oz (160g)		

Ordering

LT510..... Light Meter



UPC Code: 793950475119

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) *category:*

Click to view products by [Teledyne FLIR / Extech](#) *manufacturer:*

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [2837806](#) [4328074](#) [4366444](#) [S-11](#) [382153](#) [700PTP-1](#) [GEO-](#)
[CABLE-REEL-50M](#) [H115](#) [H300](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-H2S-100](#) [AW-NmHc-100](#) [ES1-CO-1000-01](#) [P 2801](#) [P 2802](#) [TM-197](#)
[ULD-420-EUR](#) [TM-192](#) [TM-192D](#) [TM-305U](#) [UT309C](#) [EL-P-TC-T-SURFACE](#) [1500000059](#) [HS115](#) [MR59](#) [12227021](#) [13123602](#) [13123661](#)
[12255930](#) [12983030](#) [30171091](#) [30198712](#) [30198755](#) [30209323](#) [12228657](#) [12229067](#) [12230090](#) [7358958](#) [12231398](#) [12231487](#) [7390674](#)
[7390682](#) [12231550](#)