



BALL PROBE MOISTURE METER WITH BLUETOOTH®

FLIR MR59™

The MR59 is an affordable pinless meter for professionals in moisture remediation, pest control, home or building inspection, and floor installation. It is a high-quality, reliable, and easy-to-use moisture-detection tool. Wireless connectivity makes it easy to view readings on a mobile device from the FLIR Tools® Mobile app when the meter's display is out of view. Thanks to the ball-probe sensor, the user can cover a large area in a short time without making a mark; measure into corners, over uneven surfaces, and around baseboards; and detect problems below the surface. The MR59 is a reliable standalone meter—or a useful accessory to pair with a FLIR thermal imager.

www.flir.com/mr59



LOCATE HIDDEN MOISTURE EFFICIENTLY

Survey large areas quickly and non-destructively

- Easily run the meter over and around objects on the measuring surface with the ball-probe sensor
- Create a heat map of the affected area and follow the migration path to a hidden source of moisture
- Identify potential moisture problems up to 100 mm (4 in) below the surface



INSPECT ANYWHERE WITH EASE

Designed to make your job easier and more efficient

- Wirelessly connect the meter to FLIR Tools Mobile to view readings on a mobile device
- Work in dim lighting with the backlit display and bright worklight
- Use with the MR04 extension pole to reduce the need for a ladder, or to optimize ergonomics for 'high' and 'low' measuring targets (accessory not included)



RELY ON THIS METER TO GET THE JOB DONE

Take the durable, drop-tested meter to every job

- Detect moisture in a wide range of common building materials
- Receive stable, repeatable readings. The meter's handgrip is designed to prevent hands from interfering with measurements
- Take advantage of product enhancements by upgrading firmware as needed via micro USB port (located in battery compartment)

SPECIFICATIONS

Moisture Measurement	Range	Accuracy
Moisture	0 - 100%	Relative measurement
Measurement Detection Depth	Up to 100 mm (4 in) depending upon material under test	
General Information		
Connectivity	Bluetooth BLE Communications Protocol: METERLINK®	
Worklight	White LED	
Display	Backlit, multifunction LCD	
Measurement Principle	Capacitive (non-invasive)	
Warranty	Limited 3 years	
Battery Type	9 V battery	
Battery Life	Typical 40 hours without worklight	
Battery Status Indicator	4-bar battery icon (100% to empty)	
Auto Power Off (APO)	After 30 minutes	
Operating RH/Temperature	90%, 0°C to 30°C (32°F to 86°F) 75%, 30°C to 40°C (86°F to 104°F) 45%, 40°C to 50°C (104°F to 122°F)	
IP Rating	IP40	
Safety Compliance	CE, RCM, FCC/IC	
Drop Test	2 m (6.6 ft)	
Housing Material	Impact-resistant plastic	
Weight	245 g (8.6 oz)	
Dimensions	240.5 x 67 x 38 mm (9.5 x 2.6 x 1.5 in)	

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

NASHUA

FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

LATIN AMERICA

FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 7080

CANADA

FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5K6
Canada
PH: +1 800.613.0507

Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2018 FLIR Systems, Inc. All rights reserved. 07/18

18-1211-INS



The World's Sixth Sense®

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Teledyne FLIR / Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LRS](#) [2837806](#) [4328074](#) [4366444](#) [S-11](#) [382153](#) [700PTP-1](#) [12420](#) [H115](#) [H300](#) [F150-SLC50](#) [DEM701](#) [HS115](#)
[TESTO 175-H1 0572 1754](#) [TESTO 830-T1 0560 8311](#) [AX-5002](#) [AX-5003](#) [AX-B150](#) [AX-B180](#) [AX-B350](#) [AX-BCX9MM-1](#) [AX-L230](#) [AX-](#)
[PH02](#) [12227021](#) [12228657](#) [12229067](#) [12230090](#) [12226653](#) [12230146](#) [12230171](#) [12229190](#) [12228797](#) [12228801](#) [12228665](#) [12229360](#)
[12229378](#) [12229394](#) [12229415](#) [12228835](#) [12228941](#) [F61SD-9150](#) [F61SD-9175](#) [F61TB-9200](#) [IR-710-EUR](#) [IR-720-EUR](#) [LHI807TC](#)
[1500000059](#) [1500001391](#)