

NETcat® Pro2 NC-520

NC-500 Structured Wiring Troubleshooter and NC-510 Accessory Kit

TESTING | TROUBLESHOOTING | ACCURACY

Product Features:

One Touch Testing Verifies Network Cabling and Service.

The NETcat® Pro2 is a digital tool for fast, accurate checking of cables, wiring and network service. Operated using a back-lit touch screen display, the NETcat® Pro2 tests wiring continuity and proper pair allocation, measures the length of cables, determines if network service is available and identifies Power over Ethernet (PoE) cables. When used with the NC-510 Accessory Kit, containing seven (7) expansion remote test modules, the NETcat® Pro2 can uniquely test coax or twisted pair jacks from a central location eight (8) at a time. Using a fingertip or the built-in stylus, the screen can be used to control and display a range of tests from fault finding to TDR length measurement. The display can be set to English, Spanish, French or German language.

NC-510 NETcat® Pro2 Accessory Kit contents:

- Seven additional remote jack test and ID units, Tj45 and F (male).
- Carrying case to hold additional remote test ID units and content of NC-500 main kit.

New Features of NC-500:

- Identifies active network devices on 10/100/1000 Base-T Ethernet (802.3) networks.
- Identifies PoE (source device detection).
- Memo Pad/reminder feature - stored in non-volatile memory.
- Field replaceable "F" type connector.



Follow us on Social Media
@TempoComms



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.

Other Features of the NC-500:

- NVP cable library allows for 5 commonly used fixed and 5 user selectable cable types - stored in non-volatile memory.
- Graphical touch screen display with contrast adjustment and backlight.
- Tests shielded twisted pair (STP), unshielded twisted pair (UTP) and coaxial cables.
- 0-2,000 foot (600 Meter) cable length via TDR.
- Patch cable and remote jack wire-map.
- Detects shorts, opens, reversed, crossed and split pairs.
- Office identification using remote ID units.
- Troubleshoots and verifies a wide range of networks.
- Remote jack ID and verification.
- Generate four distinct, precision tones for tracing low-loss cables like Cat 5.
- Operates on a single 9V battery, with low battery indicator.
- Compatible with Tempo precision digital probes.

Specifications:

Dimensions:	3.3" x 1.4" x 6.7" (8.5 cm x 3.5 cm x 17 cm)
Weight:	0.45 lb. (200 g)
Power Requirements:	9V Alkaline Battery (PP3)
Display LCD:	Dot Pixels: 128 x 128 dots
Viewing Area:	60.0 x 58.4
Backlight:	White LED
Buttons:	LCD touch-screen, single momentary contact push button
Operating Temperature:	0°C to 50°C
Storage Temperature:	-20°C to 70°C
Interface Connections:	RJ45 shielded jacks, F-type threaded female coaxial connectors

TDR Calibrations:	User selectable based on a known cable length. Range: 50 to 2,000 ft. - 40% to 100% in step of 1%.
Length:	2,000 ft. Maximum
Resolution:	1 ft.
Accuracy to Open/Short:	+4% or 2 ft. - whichever is greater
Remote Identifier:	2,000 ft. (609.6 meters) maximum distance
Wiremap:	358 ft. (100 meters) maximum distance
Memo Pad Size:	60 Characters
NVP Library-Twisted Pair Cables:	5 fixed and 5 user definable
NVP Library-COAX Cables:	5 fixed and 5 user definable

Ordering Information:

CAT. NO.	DESCRIPTION
NC-520	NETcat Pro2 Digital VDV Wiring Troubleshooter and Accessory Kit
NC-500	NETcat Pro2 Digital VDV Wiring Troubleshooter
NC-510	NETcat Pro2 Accessory Kit w/carry case and seven (7) digital remotes
PA901074	F-Type (female) to BNC (male) adapter
PA9675	F-Type (female) to F-type (female) 2 pack barrel adapters

1390 Aspen Way Vista, CA • 92081

TC-NC-520 02/20

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050

©2020 Tempo Communications Inc. • An ISO 9001 Company

EMEA Office: Tempo Europe Limited

Brecon House, William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



Renewed Vision. Innovation Forward.



Follow us on Social Media
@TempoComms

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LAN/Telecom/Cable Testing](#) category:

Click to view products by [Tempo Semiconductor](#) manufacturer:

Other Similar products are found below :

[7000031757](#) [MS2-KIT](#) [MT-8202-05](#) [MS2-100](#) [00486](#) [00984](#) [TCT-1620](#) [TCT-680](#) [150050](#) [150058](#) [150059](#) [150060](#) [158050](#) [158051](#) [158053](#)
[158055](#) [TCT-2690PRO](#) [TCT-700](#) [TESTER-MS6811](#) [TESTER-MS6812](#) [PA901066](#) [23636](#) [23639](#) [262](#) [VDV526-052](#) [MS-POE](#) [MS-POE-](#)
[KIT](#) [REMOTEID-KIT](#) [00533](#) [N044-000-R](#) [3353](#) [TM-902](#) [TM-903](#) [60584](#) [LAN-1](#) [ADAPTOR RJ45-COAX](#) [LP-SPT](#) [24-517](#) [231A](#) [CT20](#)
[40180](#) [CLT600](#) [TG20](#) [GBE FIBRE KIT LX](#) [GBE FIBRE KIT SX](#) [HDMI-100](#) [TEP-100](#) [KE301](#) [KE3100](#) [KE3150](#)