



**FIBER TOOLS**

# MICRO OPTICAL POWER METER

Essential Tools for the Premise Technician

TESTING | TROUBLESHOOTING | ACCURACY

## Product Features:

- Wide measurement range (+10 to -70dBm)
- High power CATV range (+26 to -50dBm)
- VFL for safe and effective fault locating
- Singlemode and multimode compatible
- Calibrated wavelengths of 850/1300/1310/1490/1550/1625nm
- 270Hz, 1kHz and 2kHz tone detect
- Auto power off

## CONTENTS:

- Micro OPM with VFL
- Lanyard
- Instruction Sheet

## ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
OPM210	Standard Power OPM with VFL
OPM220	High Power OPM with VFL
03579	1.25mm Adapter
08325	Micro OPM Carry Case
CAL CERT	Calibration Certificate



Follow us on Social Media  
**@TempoComms**



**TEMPO**  
COMMUNICATIONS

*Renewed Vision. Innovation Forward.*



# FIBER TOOLS

## SPECIFICATIONS:

PARAMETER	SPECIFICATIONS	
Model:	<b>OPM210</b>	<b>OPM220</b>
Measurement Range:	-70 to +10dBm (1310/1490/1550/1625)	-50 to +26dBm (1310/1490/1550/1625)
	-60 to +10dBm (850/1300)	-40 to +26dBm (850/1300)
Calibrated Wavelengths:	850, 1300, 1310, 1490, 1550, 1625nm	
Display Resolution:	0.01dB	
Accuracy*:	+/-0.25dB	
Linearity*:	+/-0.5dB (+10 to -3dBm)	+/-0.5dB +26 to -3dBm
	+/-0.1dB (-3 to -50dBm)	+/-0.1dB -3 to -50dBm
	+/-0.5dB (-50 to -70dBm)	
Connector:	Universal 2.5mm	
Wavelength Response:	700 - 1700nm	
Detector:	InGaAs	
Power Supply:	AAA x 2 Alkaline	
Battery Lifetime:	>60 Hours (OPM mode)	
Operating Temperature:	-10 to +50°C (<90% Relative Humidity)	
Storage Temperature:	-20 to +60°C (<90% Relative Humidity)	
VFL Wavelength:	650nm +/-20nm	
VFL Output:	≤ 1mW/ 2Hz	
VFL Range:	4km	
Size:	106 x 58 x 28mm (4.17 x 2.28 x 1.10")	
Weight:	106g (0.23lbs)	
Auto Power Off:	10 minutes of no activity	
Certifications:	CE, RoHS, CDRH, WEEE	

\* at -10dBm with FC connector at 23C Specifications subject to change without notice.

1390 Aspen Way Vista, CA • 92081

TC6910 06/21

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050

©2021 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Communications Limited • Brecon House,  
William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



# TEMPO<sup>®</sup>

COMMUNICATIONS

*Renewed Vision. Innovation Forward.*



Follow us on Social Media  
**@TempoComms**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LAN/Telecom/Cable Testing](#) category:*

*Click to view products by [Tempo Semiconductor](#) manufacturer:*

Other Similar products are found below :

[7000031757](#) [MS2-KIT](#) [MT-8202-05](#) [MS2-100](#) [00486](#) [00984](#) [TCT-1620](#) [TCT-680](#) [150050](#) [150058](#) [150059](#) [150060](#) [158050](#) [158051](#) [158053](#)  
[158055](#) [TCT-2690PRO](#) [TCT-700](#) [TESTER-MS6811](#) [TESTER-MS6812](#) [PA901066](#) [23636](#) [23639](#) [262](#) [VDV526-052](#) [MS-POE](#) [MS-POE-](#)  
[KIT](#) [REMOTEID-KIT](#) [00533](#) [N044-000-R](#) [3353](#) [TM-902](#) [TM-903](#) [60584](#) [LAN-1](#) [ADAPTOR RJ45-COAX](#) [LP-SPT](#) [24-517](#) [231A](#) [CT20](#)  
[40180](#) [CLT600](#) [TG20](#) [GBE FIBRE KIT LX](#) [GBE FIBRE KIT SX](#) [HDMI-100](#) [TEP-100](#) [KE301](#) [KE3100](#) [KE3150](#)