





ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1876	A	RELEASED	EO	03/21/06	TL	5/15/06	HO	5/15/06



Specification:

- 1- Body: ABS, White Color
- 2- Contact Terminal: Brass, Gold-Plated
- 3- Extend Terminal: Brass, Gold-Plated
- 4- Spring: Steel, Nickel-Plated

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

Unless Otherwise Specified

- .X ±0.2 [0.008]
- .XX ±0.12 [0.005]

DRAWN BY:	DATE:
EKLAS ODISH	03/21/06
CHECKED BY:	DATE:
THOMAS LEE	5/15/06
APPROVED BY:	DATE:
HISHAM ODISH	5/15/06

DRAWING TITLE:
40 PIN INTERGRATED TEST CLIP, RoHS

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	SPC15160	79K4766.DWG	A

SCALE: NTS U.O.M.: mm [INCHES] SHEET: 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tenma](#) manufacturer:

Other Similar products are found below :

[21-10130 UK+EU](#) [21-10140](#) [21-10142](#) [21-10144](#) [21-10146](#) [21-10148](#) [21-10150](#) [21-10152](#) [21-10154](#) [21-10156](#) [21-10158](#) [21-10160](#) [21-10162](#) [21-10164](#) [21-10168](#) [21-10170](#) [21-1040](#) [21-1042](#) [21-1046](#) [21-1047](#) [21-1050](#) [21-10563](#) [21-11445](#) [21-1190](#) [21-2235](#) [21-2240](#) [21-3315](#) [21-360](#) [21-550](#) [21-560](#) [21-565](#) [21-570](#) [21-605](#) [21-670](#) [21-685](#) [21-690](#) [21-8221](#) [21-8226](#) [21-8236](#) [21-8241](#) [72-10390A](#) [72-10391](#) [72-10395](#) [72-10445](#) [72-10455](#) [72-10465](#) [72-10480](#) [72-10495](#) [72-10500](#) [72-10505](#)