



FE1.1

USB 2.0 HIGH SPEED 4-PORT HUB CONTROLLER

PRODUCT BRIEF

INTRODUCTION

The FE1.1 is a highly integrated, high quality, high performance, low power consumption, yet low cost solution for USB 2.0 4-Port Hub.

It adopts *Multiple Transaction Translator* (MTT) architecture to explore the maximum possible throughput. Six, instead of two, non-periodic transaction buffers are used to minimize potential traffic jamming. The whole design is based on state-machine-control to reduce the response delay time; no micro controller is used in this chip.

To guarantee high quality, the whole chip is covered by *Test Scan Chain* – include even the high speed (480MHz) modules, so that all the logic components could be fully tested before shipping. Special *Build-In-Self-Test* mode is designed to exercise all high, full, and low speed analog components on the packaging and testing stage as well.

Low power consumption is achieved by using 0.18 μ m technology and comprehensive power/clock control mechanism. Most part of the chip will not be clocked unless needed.



FEATURES

- Low power consumption
 - 115 mA when four Downstream ports enabled in High-Speed mode;
 - 64 mA when one Downstream port enabled in High-Speed mode;
- Fully compliant with Universal Serial Bus Specification Revision 2.0 (USB 2.0);
 - Upstream facing port supports High-Speed (480MHz) and Full-Speed (12MHz) modes;
 - 4 downstream facing ports support High-Speed (480MHz), Full-Speed (12MHz), and Low-Speed (1.5MHz) modes;
- Integrated USB 2.0 Transceivers;
- Integrated upstream 1.5K Ω pull-up, downstream 15K Ω pull-down, and serial resistors;
- Integrated 5V to 3.3V and 1.8V regulator.
- Integrated Power-On-Reset circuit;
- Integrated 12MHz Oscillator with feedback resistor, and crystal load capacitance;
- Integrated 12MHz-to-480MHz Phase Lock Loop (PLL);
- *Multiple Transaction Translators* (MTT) –
 - One TT for each downstream port;
 - Alternate Interface 0 for Single-TT, and



- Alternate Interface 1 for Multiple-TT;
 - Each TT could handle 64 periodic Start-Split transactions, 32 periodic Complete-Split transactions, and 6 none-periodic transactions;
- Automatic self-power status monitoring;
 - Automatic re-enumeration when Self-Powered switching to Bus-Powered;
- Board configured options –
 - *Ganged or Individual Power Control Mode* select;
 - *Global or Individual Over-Current Detection Mode* select;
 - *Removable or Non-Removable Downstream Devices* configuration;
- Comprehensive Port Indicators support:
 - Standard downstream port status indicators (Green and Amber LED control for each downstream port);
 - Hub active LED support;
- Support Microsoft Windows 98SE/ME, 2000, XP, and Vista;
- Support Mac OS 8.6 and above;
- Support Linux kernel 2.4.20 and above.

PACKAGE

48-pin LQFP (Body Size: 7x7 mm)

48-pin QFN (Body Size: 6x6 mm, 0.4 pitch)

TERMINUS TECHNOLOGY INC.
1052, 10F, No. 3-2, YUANQU ST. NANGANG
TAIPEI, TAIWAN, ROC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Interface IC](#) category:

Click to view products by [Terminus](#) manufacturer:

Other Similar products are found below :

[CY7C65210-24LTXI](#) [CY7C69356-48LTXC](#) [CYUSB2304-68LTXI](#) [CYPD2119-24LQXI](#) [USB2227-NU-11](#) [USB3319C-GJ-TR](#) [USB3370B-EZK-TR](#) [PTN5150AHXMP](#) [CY7C65215A-32LTXI](#) [CYPD2120-24LQXI](#) [CYWB0164BB-BZXI](#) [CYWB0224ABS-BZXI](#) [CY7C65211A-24LTXI](#) [USB3803CI-1-GL-TR](#) [USB2422T-I/MJ](#) [UPD720114GA-YEU-AT](#) [CYPD2122-20FNXIT](#) [CYPD2122-24LQXIT](#) [LIF-UC120-SWG36ITR50](#) [UPD360-B/6HX](#) [UPD360-A/6HX](#) [CP2102NP1174GM](#) [CY7C65642-28LTXCT](#) [CG8454AM](#) [CYUSB2025-BZXI](#) [FUSB303BTMX](#) [PTN3816EWY](#) [UPD720211K8-711-BAL-A](#) [PTN38003AEWY](#) [PTN38007EWY](#) [CYPM1111-40LQXI](#) [CY7C65216D-32LTXI](#) [USB3317C-GJ-TR](#) [iW657P-65-56BB](#) [CY7C68034-56LTXC](#) [TUSB213IRGYT](#) [TUSB213RGYT](#) [TUSB214RWBT](#) [USB2517I-JZX-TR](#) [USB3318-CP](#) [USB3343-CP](#) [USB3503T-I/ML](#) [CHY100D-TL](#) [STUSB1602AQTR](#) [TUSB214IRWBT](#) [TUSB8043RGCT](#) [USB3319C-CP-TR](#) [USB2532I-1080AEN](#) [CY7C63310-SXC](#) [CY7C64215-28PVXI](#)