# productinformation

## tesa® 51006

PET cloth tape for bundling and wire protection of automotive harnesses against abrasion

tesa® 51006 is a PET cloth tape with a rubber-based adhesive providing reliable abrasion protection of automotive harnesses. The high initial tack, a constant unwind force and the flexible backing enable smooth and efficient application in the car body.

The high adhesion and good flag resistance ensure secure harness bundling. Its properties are optimized for manual application. The temperature resistance depends on the insulation material.

#### Main features:

- Resistant to abrasion
- High initial tack and adhesion
- Optimized for manual application
- Flag-resistant
- Can withstand environmental influences
- Constant unwind force optimized for manual application
- Aging-resistant
- Flame-retardant
- Flexible and smooth

#### Main Application

tesa® 51006 has been specially designed for bundling and wire protection against abrasion. The main application field is the engine compartment of a car, with demanding temperature-related and environmental conditions.

### Technical Data

Backing material	PET cloth
Total thickness	320 μm
Type of adhesive	rubber based
Adhesion to steel	4.5 N/cm
Elongation at break	22 %
Tensile strength	175 N/cm
Temperature resistance min.	-40 °C

	Temperature resistance (3000h)	150 °C
•	Abrasion resistance (10mm	Class C (acc. to
	mandrel)	LV312)
•	Abrasion resistance (5mm	Class B (acc. to
	mandrel)	LV312)
•	Flame resistance as composite	Class B (acc. to
		LV312)
•	Unwind force (roll width ≤ 9mm)	6 N/roll (30 m/min)
•	Unwind force (roll width > 9mm)	10 N/roll (30 m/min)
	Noise damping (decibel)	Class A (acc. to

LV312)

age 1 of 2 - As of 14/06/2019 - e

For latest information on this product please visit <a href="http://l.tesa.com/?ip=51006">http://l.tesa.com/?ip=51006</a>

## tesa® 51006

PET cloth tape for bundling and wire protection of automotive harnesses against abrasion

#### Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mmApplicable for red ring assembly aid

\*On ETFE wires. Other insulation materials to be tested.

Page 2 of 2 - As of 14/06/2019 - er

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by Tesa manufacturer:

Other Similar products are found below:

56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-1"X36YD 69-1"X36YD 764
1"x36yd-Red 764-1"x36yd-White PG ASSY 967454-1 1181 19MM X 16,5 METERS 130C-1X15FT 1900-48mm 22-1/2X36YD 88
SUPER-34X44FT 890103N001 2670 96 EVK-TA-TM047NBH01 20-1"X60YDS 2020-18mmx55m H150 363 3900-Blue 3939
24mmx55m 4462-SN100 4462W-12"x72yd 44-TAN-14"X90YD 471-Trans-1"x36yd-Bulk 35-Gray-1/2 4008-12"X36YD 4104-34"x18yd

4116 444-1"x36yd 44661" 4466W-1/2"x36yd 4492B-12"x72yd 4492B-1"x72yd 4496W-12"x36yd 4508-1"x36yd 4516-3/8x36 4726

1/2"X36YD 054007-43154 054007-40651 054007-43152 06149 5419 1/2" 56 TAPE (1/2") 56-YELLOW-58"X72YD