productinformation

tesa® 51026

PET cloth wire-harness tape for high abrasion protection and high temperature resistance up to 150°C

tesa® 51026 PET Cloth tape is an efficient solution for engine compartment wire harnessing where very high abrasion and high temperature resistance is required.

Its new-generation acrylic adhesive is compatible with new halogen-free cable jacketing materials (PE/PP) and provides enhanced durability. It is optimised for manual and automatic application.

Features:

- high abrasion resistance
- high temperature resistance 150°C/3000h
- oil and fuel resistant
- UV resistant
- flame retardant
- fogging-free
- excellent compatibility with PVC, PE and PP cable insulation
- stable unwind strength
- resistant to ageing
- rot-proof
- tear resistant
- strong adhesion
- flexible and smooth

Main Application

tesa® 51026 PET Cloth tape is designed for the engine compartment wire harnessing, providing high abrasion protection.

Technical Data

| | Backing material | PET cloth |
|---|-----------------------------|-----------|
| | Total thickness | 260 μm |
| • | Type of adhesive | acrylic |
| | Adhesion to steel | 5.5 N/cm |
| • | Elongation at break | 40 % |
| • | Tensile strength | 275 N/cm |
| | Temperature resistance min. | -40 °C |
| | | |

| remperature resistance (500011) |
|---------------------------------|
| Abrasion resistance (10mm |
| mandrel) |
| Abrasion resistance (5mm |
| mandrel) |
| Flame resistance as composite |
| |

| Unwind force (roll width ≤ 9mm) |
|---------------------------------|
| Unwind force (roll width > 9mm) |
| Noise damping (decibel) |

5 N/roll (30 m/min) 11 N/roll (30 m/min) Class A (acc. to LV312)

150 °C

LV312)

LV312)

LV312)

Class D (acc. to

Class D (acc. to

Class B (acc. to

Page 1 of 2 - as of 04/09/2019 - el

For latest information on this product please visit http://l.tesa.com/?ip=51026

tesa® 51026

PET cloth wire-harness tape for high abrasion protection and high temperature resistance up to 150°C

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm
- Applicable for red ring assembly aid
- = " = RAL 2007. Some color fadings can occur under continous strong heat conditions. A standard for color is not specified.

°age 2 of 2 − as of 04/09/2019 − e

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by Tesa manufacturer:

Other Similar products are found below:

56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-1"X36YD 69-1"X36YD 764
1"x36yd-Red 764-1"x36yd-White PG ASSY 967454-1 1181 19MM X 16,5 METERS 130C-1X15FT 1900-48mm 22-1/2X36YD 88
SUPER-34X44FT 890103N001 2670 96 EVK-TA-TM047NBH01 20-1"X60YDS 2020-18mmx55m H150 363 3900-Blue 3939
24mmx55m 4462-SN100 4462W-12"x72yd 44-TAN-14"X90YD 471-Trans-1"x36yd-Bulk 35-Gray-1/2 4008-12"X36YD 4104-34"x18yd

4116 444-1"x36yd 44661" 4466W-1/2"x36yd 4492B-12"x72yd 4492B-1"x72yd 4496W-12"x36yd 4508-1"x36yd 4516-3/8x36 4726

1/2"X36YD 054007-43154 054007-40651 054007-43152 06149 5419 1/2" 56 TAPE (1/2") 56-YELLOW-58"X72YD