



**DESCRIPTION:**

Mercury Free Alkaline Manganese Battery, 9V Size / Non-Rechargeable

**CHEMICAL SYSTEM:**

Alkaline Manganese

**SHELF LIFE:**

7 years

**NOMINAL VOLTAGE:**

9,0 Volts

**NOMINAL DIMENSIONS:**

26.5(L)mm × 17.5(W)mm × 48.5(H)mm

**TERMINALS:**

Nickel plated miniature snap fasteners

**JACKET:**

Foil jacket

**APPLICATIONS:**

All electronics devices e.g. toys, microphones, smoke detectors, photographic equipment.

**STORAGE TEMPERATURE:**

+10 °C to + 25 °C

Should be stored in dry and cool place.

**NOMINAL WEIGHT:**

44,2 g

**CROSS REFERENCES:**

TESLA	JIS	IEC	EVEREADY	DURACELL
6LR61	6LR61	6LR61	522	MN1604

**ELECTRICAL CHARACTERISTICS:**

TEST ITEM	TEST CONDITIONS 20±2 °C,60±15%RH	SPECIFICATION(VOLT), MIN
OCV	24 Hrs/Day	0.9V

**TYPICAL SERVICE LIFE:**

TEST ITEM	TEST CONDITIONS 20±2 °C,60±15%RH (EV=END VOLTAGE)	SERVICE LIFE
OCV	270 Ω Intermittent 1Hrs/ Day , EV=5.40V	21.5HRS
	620 Ω Intermittent 2Hrs/ Day , EV=5.40V	50.0Hrs
	10 kΩ background 24Hrs/ Day,620 Ω 1s/h pluse EV=7.50V	21.5Days

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cylindrical Battery Contacts, Clips, Holders & Springs](#) category:*

*Click to view products by [TESLA](#) manufacturer:*

Other Similar products are found below :

[12BH36A-GR](#) [200](#) [161](#) [183](#) [270](#) [QX3506](#) [5220](#) [5230](#) [1055](#) [1088](#) [5250](#) [KT0008](#) [1119](#) [5207](#) [246](#) [BWCD-L4.5W2.0H2.3](#) [BWCD-L6.0W2.0H2.0](#) [BW0041BG-L2.5W1.0H1.5](#) [BW0031AG-L3.5W1.0H3.0](#) [BWCD-L5.0W2.0H2.5](#) [BW0019CG-L3.5W1.5H4.3](#) [BW0036AG-L3.5W1.0H1.4](#) [BW0034AG-L3.5W0.9H1.5](#) [BW0033BG-L3.4W0.9H2.0](#) [BW0041CG-L2.5W1.0H1.8](#) [BW0028AG-L3.5W1.5H2.05](#) [BW0098DG-L4.0W1.5H2.0](#) [BW0019BG-L3.5W1.5H3.8](#) [BWCD-L6.5W2.0H2.0](#) [BWCD-L4.0W2.0H1.0](#) [BWCD-L5.5W2.0H3.0](#) [BW0019AG-L3.5W1.5H3.5](#) [BWCD-L3W2.0H1.0](#) [ECT818002831](#) [ECT81800A081](#) [ECT818003141](#) [ECT81800B009](#) [ECT818002399](#) [F9-7-6-0.4Z](#) [F8-10-0.4-1.3](#) [F10-10-6-0.4-1.3](#) [F8-8-5-0.4Z](#) [F10-12-0.4-1.3](#) [F10-10-6.5-0.4P](#) [F10-10-6.5-0.4 Z](#) [GP SUPER 14A \(LR14\) SHRINK 2 LR20 INDUSTRIAL INTENSE](#) [CW332](#) [PCL5A](#) [EGWW29](#)