



<b>Model / Order-No.</b>	<b>TT-HVP 15B / 15010</b>
Division Ratio	1000:1
Input Resistance	100MΩ
Input Capacitor	3,0pF ± 0,5pF
Max. DC+AC peak	20kV CAT 0
Max. AC RMS.	7kV CAT 0
Max. DC	10kV CAT 0
Band Width	DC~40MHz (-3dB)
Rise Time	≤ 8,8ns
Signal / Noise	DC: > 60dB @ 1kHz ; > 50dB @ 1MHz
DCV Accuracy	≤ 6%
Temp. Coefficient	≤ 200 ppm/°C
Compensation Range	15pF ~ 30pF
Safety Standard	meets IEC61010-031:2015
Measurement Category	CAT 0 / Pollution Degree 2
Cable Length	2m ± 0.2m
Operation Temp.	-10°C to 55°C
Humidity	85% RH or less (@ 35°C)
Storage Temp.	-20°C to 70°C
Color: Handel / Body	Black / Yellow
Weight / Volume	250g / 75(W) x 75(H) x 340(L) mm

Fritz-Klatte-Str. 6,D - 65933 Frankfurt / E-Mail: [info@testec.de](mailto:info@testec.de)  
 Telefon: +49 (0) 69 - 94 333 5 – 0, Fax: +49 (0) 69 - 94 333 5 - 55

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Probes](#) category:*

*Click to view products by [Testec](#) manufacturer:*

Other Similar products are found below :

[6214](#) [6474](#) [815003](#) [923832-BK-B](#) [P-KIT-1](#) [KT-MS001](#) [925250-R](#) [973368101](#) [972318101](#) [972318100](#) [MXHQ87WJ3000](#) [PK106-3](#) [PK2-5MM-102](#) [TAS90](#) [VL1735/45](#) [973368100](#) [972327100](#) [972327101](#) [973995100](#) [973995101](#) [CT3982B-120](#) [MO50-PINS](#) [CT4386](#) [PP023-1](#) [PK1-5MM-127](#) [PK103](#) [PK-ZS-013](#) [P6139B-PK10](#) [PQ215](#) [PQ218](#) [RT-ZI10C](#) [TT-SI 8071](#) [TT-SI 8050](#) [TT-SI 8010A](#) [TT-SI 7005](#) [GE.3421](#) [GE.2521](#) [GE.3121](#) [GE.1511](#) [GE.1521](#) [GE.2511](#) [GE.4511](#) [HVP15B](#) [TT-SI7002](#) [4005](#) [4011](#) [4012](#) [4013](#) [4014](#) [4015](#)