

ACTIVE DIFFERENTIAL PROBES SERIES 8000

The new TT-SI 8010A and TT-SI 8010B active differential probes allow safe, accurate high voltage measurements between two voltage points where neither point is referenced to ground. These two probes are perfect designed for a wide variety of measurements up to 100MHz / $\pm 7000V$ and are compatible with oscilloscopes from all major manufacturers.



	TT-SI 8010A	TT-SI 8010B
Order Number	15411	15412
Bandwidth	70MHz	100MHz
Attenuation	x100 / x1000	
DC-Accuracy	$\pm 2\%$	
Max. Input Voltage Differential Mode	$\pm 700V$ (DC + AC peak) @ x10 $\pm 7000V$ (DC + AC peak) @ x100	
Max. Input Voltage Common Mode	$\pm 7000V$ (DC + peak AC)	
Maximum Input Voltage (each side to ground)	1000Vrms CAT III 2300Vrms	
Safety Standard	IEC1010-031:2015	
Supplied Accessories	2 x Test Leads with insulated 4mm Banana Plugs (red & black) 2 x Grabber (red & black), 2 x Pincer (red & black) 2 x Alligator Clips (red & black), 1 x Insulated BNC Cable, 100cm 1 x USB power lead, 1 x Mains Adapter 220V EU Version	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Probes](#) category:

Click to view products by [Testec](#) manufacturer:

Other Similar products are found below :

[6214](#) [6474](#) [815003](#) [923832-BK-B](#) [P-KIT-1](#) [KT-MS001](#) [925250-R](#) [973368101](#) [972318101](#) [972318100](#) [MXHQ87WJ3000](#) [PK106-3](#) [PK2-5MM-102](#) [TAS90](#) [VL1735/45](#) [973368100](#) [972327100](#) [972327101](#) [973995100](#) [973995101](#) [CT3982B-120](#) [MO50-PINS](#) [CT4386](#) [PP023-1](#) [PK1-5MM-127](#) [PK103](#) [PK-ZS-013](#) [P6139B-PK10](#) [PQ215](#) [PQ218](#) [RT-ZI10C](#) [TT-SI 8071](#) [TT-SI 8050](#) [TT-SI 8010A](#) [TT-SI 7005](#) [GE.3421](#) [GE.2521](#) [GE.3121](#) [GE.1511](#) [GE.1521](#) [GE.2511](#) [GE.4511](#) [HVP15B](#) [TT-SI7002](#) [4005](#) [4011](#) [4012](#) [4013](#) [4014](#) [4015](#)